

SIDE FLARE -

DETAIL "A"

TYPICAL PLACEMENT OF DETECTABLE

DETECTABLE
 WARNING SURFACE

(TYP.)

NOTES:

1. LIMITS OF PAYMENT FOR RAMP INCLUDES THE CONCRETE GUTTER WIDTH ALONG THE RAMP OPENING.

2. WHEN ADJACENT TO CONCRETE PAVEMENT, THE RAMP WIDTH, CURB TRANSITION, AND LANDING LIMITS SHALL BE DOWELED INTO

CENTERS). THE COST OF THE DOWELING SHALL BE SUBSIDIARY TO THE COST OF THE CURB RAMP.

DESIGNER TO COMPLY WITH THE MASTER THOROUGHFARE PLAN ADOPTED MAY 2016.

3. VALVE BOXES/CLEANOUTS ARE NOT TO BE PLACED IN RAMP

THE CURB AND PAVEMENT WITH #3 BARS (12" LONG ON 18"

NOTES TO DESIGNER:

SIDEWALK

FACE OF CURB

WARNING SURFACE

DETAIL "B"

TYPICAL PLACEMENT OF DETECTABLE

NON-WALKING SURFACE

EXPANSION JOINT

2% MAX.

AIL

次 DAVID C. GREGORY 89296 A STORY 11-11-22

Date: 12/30/2019 Scale:

Drawn By: Reviewed By:

SHEE 7