

SECTION 011000 - SUMMARY

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings/Exhibits and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 WORK COVERED BY CONTRACT DOCUMENTS

- A. Project Identification: Project consists of complete remodeling of Service Building Counting/Foyer Rooms in the at Fort Worth Transit Authority Hershel R. Payne (HRP) facility.

- 1. Project Location: 1600 E. Lancaster Ave.
Fort Worth, Texas 76102

- 2. Owner:
Fort Worth Transportation Authority
801 Grove Street
Fort Worth, Texas 76102

B. Not Used

- 1.

- C. Contractor: In Division 1 through 16 Specifications, the term “Construction Manager” and “Contractor” are synonymous.

- D. The Work consists of: Construction of but not limited to the following:

- 1. The Work includes but may not be limited to Exterior construction including:

- a. See plans

- 2. The Work includes but may not be limited to Interior construction including:

- a. Installtion Non-Slip Epoxy Flooring
 - b. Repair, Prep, Prime and Paint wall surfaces, doors, and frames
 - c. Installation of Hollow Metal frames.
 - d. Door Hardware.
 - e. Gypsum Board wall.
 - f. Replacement of existing signage

- g. Acoustical Ceilings tiles and grid
 - h. Replacement of ceiling insulation
 - i. Acrylic sheets to protect walls
- 3. The Work includes but may not be limited to Mechanical and Electrical Systems including:
 - a. HVAC - replacement of ceiling diffuser/grille/register.
 - b. Electrical-Replacement of receptacles.
 - c. Communication- data cabling and conduit runs .

1.3 SECTION NOT USED

1.4 USE OF PREMISES

- A. Site: Contractor will have limited access to the site during the construction phase. Contractor shall work in a manner that allows uninterrupted on-going operation of the existing facility

1.5 SUMMARY

- A. Section Includes:
 - 1. Project information.
 - 2. Work covered by Contract Documents.
 - 3. Work by Owner.
 - 4. Work under separate contracts.
 - 5. Purchase contracts.
 - 6. Owner-furnished products.
 - 7. Contractor-furnished, Owner-installed products.
 - 8. Access to site.
 - 9. Coordination with occupants.
 - 10. Work restrictions.
 - 11. Specification and drawing conventions.
 - 12. Miscellaneous provisions.
- B. Related Requirements:
 - 1. Not Used

1.6 PROJECT INFORMATION

- A. Project Identification: TM HRP Money Room.

1. Project Location: 1600 E Lancaster Ave, Fort Worth, Texas
- B. Owner: Fort Worth Transportation Authority
 1. Owner's Representative: As Designated
- C. Section Not Used.

1.7 OWNER-FURNISHED PRODUCTS

- A. Owner will furnish products indicated to be incorporated into Work by Contractor, including but not limited to:
 1. Furniture, tables, money machines, chairs, phones
 - 2.
 - 3.

1.8 SPECIFICATION FORMATS AND CONVENTIONS

- A. Specification Format: The Specifications are organized into Divisions and Sections using the 16-division format and CSI/CSC's "MasterFormat" numbering system.
- B. Specifications Content: The Specifications use certain conventions for the style of language and the intended meaning of certain terms, words, and phrases when used in particular situations. These conventions are as follows:
 1. Abbreviated Language: Language used in the Specifications and other Contract Documents is abbreviated. Words and meanings shall be interpreted as appropriate. Words implied, but not stated, shall be inferred as the sense requires. Singular words shall be interpreted as plural and plural words shall be interpreted as singular where applicable as the context of the Contract Documents indicates.
 2. Imperative mood and streamlined language are generally used in the Specification Requirements expressed in the imperative mood are to be performed by Contractor. Occasionally, the indicative or subjunctive mood may be used in the Section Text for clarity to describe responsibilities that must be fulfilled indirectly by Contractor or by others when so noted.
 - a. The word "shall," "shall be," or "shall comply with," depending on the context, are implied where a colon (:) is used within a sentence or phrase.

1.9 SPRINKLER SYSTEM APPROVAL

- A. N/A

1.10 ACCESS TO SITE

- A. General: Contractor shall have full use of Project site for construction operations during construction period. Contractor's use of Project site is limited only by Owner's right to perform work or to retain other contractors on portions of Project.

1.11 WORK RESTRICTIONS

- A. Work Restrictions, General: Comply with restrictions on construction operations as set forth by the City of Fort Worth and by the Owner.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION (Not Used)

END OF SECTION 011000

SECTION 013100 - PROJECT MANAGEMENT AND COORDINATION

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes administrative provisions for coordinating construction operations on Project including, but not limited to, the following:
 - 1. General coordination procedures.
 - 2. Coordination drawings.
 - 3. Requests for Information (RFIs).
 - 4. Project Web site.
 - 5. Project meetings.
- B. Related Requirements:
 - 1. Section 013200 "Construction Progress Documentation" for preparing and submitting Contractor's construction schedule.
 - 2. Section 017300 "Execution" for procedures for coordinating general installation and field-engineering services, including establishment of benchmarks and control points.

1.3 GENERAL COORDINATION PROCEDURES

- A. Coordination: Coordinate construction operations included in different Sections of the Specifications to ensure efficient and orderly installation of each part of the Work. Coordinate construction operations, included in different Sections, that depend on each other for proper installation, connection, and operation.
 - 1. Schedule construction operations in sequence required to obtain the best results where installation of one part of the Work depends on installation of other components, before or after its own installation.
 - 2. Coordinate installation of different components to ensure maximum performance and accessibility for required maintenance, service, and repair.
 - 3. Make adequate provisions to accommodate items scheduled for later installation.
 - 4. Where availability of space is limited, coordinate installation of different components to ensure maximum performance and accessibility for required maintenance, service, and repair of all components, including mechanical and electrical.
- B. Prepare memoranda for distribution to each party involved, outlining special procedures required for coordination. Include such items as required notices, reports, and list of attendees at meetings.

1. Prepare similar memoranda for Owner and separate contractors if coordination of their Work is required.
- C. Administrative Procedures: Coordinate scheduling and timing of required administrative procedures with other construction activities and activities of other contractors to avoid conflicts and to ensure orderly progress of the Work. Such administrative activities include, but are not limited to, the following:
1. Preparation of Contractor's construction schedule.
 2. Preparation of the schedule of values.
 3. Installation and removal of temporary facilities and controls.
 4. Delivery and processing of submittals.
 5. Progress meetings.
 6. Preinstallation conferences.
 7. Project closeout activities.
 8. Startup and adjustment of systems.
- D. Conservation: Coordinate construction activities to ensure that operations are carried out with consideration given to conservation of energy, water, and materials. Coordinate use of temporary utilities to minimize waste.
1. Salvage materials and equipment involved in performance of, but not actually incorporated into, the Work.

1.4 COORDINATION DRAWINGS

- A. Coordination Drawings, General: Prepare coordination drawings according to requirements in individual Sections, and additionally where installation is not completely shown on Shop Drawings, where limited space availability necessitates coordination, or if coordination is required to facilitate integration of products and materials fabricated or installed by more than one entity.
1. Content: Project-specific information, drawn accurately to a scale large enough to indicate and resolve conflicts. Do not base coordination drawings on standard printed data. Include the following information, as applicable:
 - a. Use applicable Drawings as a basis for preparation of coordination drawings. Prepare sections, elevations, and details as needed to describe relationship of various systems and components.
 - b. Coordinate the addition of trade-specific information to the coordination drawings by multiple contractors in a sequence that best provides for coordination of the information and resolution of conflicts between installed components before submitting for review.
 - c. Indicate functional and spatial relationships of components of architectural, structural, civil, mechanical, and electrical systems.
 - d. Indicate space requirements for routine maintenance and for anticipated replacement of components during the life of the installation.
 - e. Show location and size of access doors required for access to concealed dampers, valves, and other controls.
 - f. Indicate required installation sequences.

- g. Indicate dimensions shown on the Drawings. Specifically note dimensions that appear to be in conflict with submitted equipment and minimum clearance requirements. Provide alternate sketches to Architect indicating proposed resolution of such conflicts. Minor dimension changes and difficult installations will not be considered changes to the Contract.
- B. Coordination Digital Data Files: Prepare coordination digital data files according to the following requirements:
 - 1. File Preparation Format: TBD.
 - 2. File Submittal Format: Submit or post coordination drawing files using TBD format.

1.5 SUBMITTALS

- A. Coordination Drawings: Prepare Coordination Drawings if limited space availability necessitates maximum utilization of space for efficient installation of different components or if coordination is required for installation of products and materials fabricated by separate entities. Coordination drawings to be provided showing routing above ceilings for HVAC, plumbing and electrical work.
 - 1. Content: Project-specific information, drawn accurately to scale. Do not base Coordination Drawings on reproductions of the Contract Documents or standard printed data. Include the following information, as applicable:
 - a. Indicated functional and spatial relationships of components of architectural, structural, civil, mechanical, and electrical systems.
 - b. Indicate required installation sequences.
 - c. Indicate dimensions shown on the Contract Drawings and make specific note of dimensions that appear to be in conflict with submitted equipment and minimum clearance requirements. Provide alternate sketches to Architect for resolution of such conflicts. Minor dimension changes and difficult installations will not be considered changes to the Contract.
- B. Staff Names: Within 15 days of starting construction operations, submit a list of principal staff assignments, including superintendent and other personnel in attendance at Project site. Identify

individuals and their duties and responsibilities; list addresses and telephone numbers, including home and office telephone numbers. Provide names, address, and telephone numbers of individuals assigned as standbys in the absence of individuals assigned to Project.

1. Post copies of list in Project meeting room, in temporary field office, and by each temporary telephone.

1.6 MOCK UP COORDINATION

- A. Coordinate scheduling and timing of required mock ups with other construction activities and activities of other contractors to avoid conflicts and to ensure orderly progress of the work. Such activities include, but are not limited to, the following:
 1. Preparation of Mock Up Schedule.
 2. Submittal and processing of Mock Up shop drawings and materials samples.
 3. Coordination of location of Mock Up.

1.7 ADMINISTRATIVE AND SUPERVISORY PERSONNEL

- A. General: In addition to Project superintendent, provide other administrative and supervisory personnel as required for proper performance of the Work.

1.8 PROJECT MEETINGS

- A. General: Schedule and conduct meetings and conferences at Project site unless otherwise indicated.
 1. Attendees: Inform participants and others involved, and individuals whose presence is required, of date and time of each meeting. Notify Owner and Architect of scheduled meeting dates and times.
 2. Agenda: Prepare the meeting agenda. Distribute the agenda to all invited attendees.
 3. Minutes: Entity responsible for conducting meeting will record significant discussions and agreements achieved. Distribute the meeting minutes to everyone concerned, including Owner and Architect, within three days of the meeting.
- B. Preconstruction Conference: Contractor will schedule and conduct a preconstruction conference before starting construction, at a time convenient to Owner and Architect, but no later than 15 days after execution of the Agreement.
 1. Attendees: Authorized representatives of Owner, Architect, and their consultants; Contractor and its superintendent; major subcontractors; suppliers; and other concerned parties shall attend the conference. All participants at the conference shall be familiar with Project and authorized to conclude matters relating to the Work.
 2. Agenda: Discuss items of significance that could affect progress, including the following:
 - a. Tentative construction schedule.
 - b. Critical work sequencing and long-lead items.

- c. Designation of key personnel and their duties.
 - d. Lines of communications.
 - e. Procedures for processing field decisions and Change Orders.
 - f. Procedures for RFIs.
 - g. Procedures for testing and inspecting.
 - h. Procedures for processing Applications for Payment.
 - i. Distribution of the Contract Documents.
 - j. Submittal procedures.
 - k. Preparation of record documents.
 - l. Use of the premises.
 - m. Working hours.
 - n. Owner's occupancy requirements.
 - o. Responsibility for temporary facilities and controls.
 - p. Parking availability.
 - q. Office, work, and storage areas.
 - r. Equipment deliveries and priorities.
 - s. First aid.
 - t. Security.
 - u. Progress cleaning.
3. Minutes: Entity responsible for conducting meeting will record and distribute meeting minutes.
- C. Preinstallation Conferences: Conduct a preinstallation conference at Project site before each construction activity that requires coordination with other construction.
- 1. Attendees: Installer and representatives of manufacturers and fabricators involved in or affected by the installation and its coordination or integration with other materials and installations that have preceded or will follow, shall attend the meeting. Advise Architect of scheduled meeting dates.
 - 2. Agenda: Review progress of other construction activities and preparations for the particular activity under consideration, including requirements for the following:
 - a. Contract Documents.
 - b. Options.
 - c. Related RFIs.
 - d. Related Change Orders.
 - e. Purchases.
 - f. Deliveries.
 - g. Submittals.
 - h. Review of mockups.
 - i. Possible conflicts.
 - j. Compatibility requirements.
 - k. Time schedules.
 - l. Weather limitations.
 - m. Manufacturer's written instructions.
 - n. Warranty requirements.
 - o. Compatibility of materials.
 - p. Acceptability of substrates.
 - q. Temporary facilities and controls.
 - r. Space and access limitations.

- s. Regulations of authorities having jurisdiction.
 - t. Testing and inspecting requirements.
 - u. Required performance results.
 - v. Protection of construction and personnel.
3. Record significant conference discussions, agreements, and disagreements, including required corrective measures and actions.
 4. Reporting: Distribute minutes of the meeting to each party present and to other parties requiring information.
- D. Progress Meetings: Conduct progress meetings at regular intervals.
1. Coordinate dates of meetings with preparation of payment requests.
 2. Attendees: In addition to representatives of Owner and Architect, each contractor, subcontractor, supplier, and other entity concerned with current progress or involved in planning, coordination, or performance of future activities shall be represented at these meetings. All participants at the meeting shall be familiar with Project and authorized to conclude matters relating to the Work.
 3. Agenda: Review and correct or approve minutes of previous progress meeting. Review other items of significance that could affect progress. Include topics for discussion as appropriate to status of Project.
 - a. Contractor's Construction Schedule: Review progress since the last meeting. Determine whether each activity is on time, ahead of schedule, or behind schedule, in relation to Contractor's construction schedule. Determine how construction behind schedule will be expedited; secure commitments from parties involved to do so. Discuss whether schedule revisions are required to ensure that current and subsequent activities will be completed within the Contract Time.
 - b. Review present and future needs of each entity present, including the following:
 - 1) Interface requirements.
 - 2) Sequence of operations.
 - 3) Resolution of BIM component conflicts.
 - 4) Status of submittals.
 - 5) Deliveries.
 - 6) Off-site fabrication.
 - 7) Access.
 - 8) Site utilization.
 - 9) Temporary facilities and controls.
 - 10) Progress cleaning.
 - 11) Quality and work standards.
 - 12) Work hours.
 - 13) Hazards and risks.
 - 14) Status of Change Orders.
 - 15) Documentation of information for payment requests.
 4. Minutes: Entity responsible for conducting the meeting will record and distribute the meeting minutes to each party present and to parties requiring information. Include a brief summary in narrative form, of progress since the previous meeting and report.

- a. Schedule Updating: Revise Contractor's construction schedule after each progress meeting where revisions to the schedule have been made or recognized. Issue revised schedule concurrently with the report of each meeting.

- E. Coordination Meetings: Conduct Project coordination meetings as necessary with subcontractor at regular intervals. Project coordination meetings are in addition to specific meetings held for other purposes, such as progress meetings and preinstallation conferences.
 - 1. Agenda: Review and correct or approve minutes of the previous coordination meeting. Review other items of significance that could affect progress. Include topics for discussion as appropriate to status of Project.
 - a. Combined Contractor's Construction Schedule: Review progress since the last coordination meeting. Determine whether each contract is on time, ahead of schedule, or behind schedule, in relation to combined Contractor's construction schedule. Determine how construction behind schedule will be expedited; secure commitments from parties involved to do so. Discuss whether schedule revisions are required to ensure that current and subsequent activities will be completed within the Contract Time.
 - b. Schedule Updating: Revise combined Contractor's construction schedule after each coordination meeting where revisions to the schedule have been made or recognized. Issue revised schedule concurrently with report of each meeting.
 - c. Review present and future needs of each contractor present, including the following:
 - 1) Interface requirements.
 - 2) Sequence of operations.
 - 3) Resolution of BIM component conflicts.
 - 4) Status of submittals.
 - 5) Deliveries.
 - 6) Off-site fabrication.
 - 7) Access.
 - 8) Site utilization.
 - 9) Temporary facilities and controls.
 - 10) Work hours.
 - 11) Hazards and risks.
 - 12) Progress cleaning.
 - 13) Quality and work standards.
 - 14) Change Orders.
 - 2. Reporting: Record meeting results and distribute copies to everyone in attendance and to others affected by decisions or actions resulting from each meeting.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION (Not Used)

END

OF

SECTION

013100

SECTION 013300 - SUBMITTAL PROCEDURES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes requirements for the submittal schedule and administrative and procedural requirements for submitting Shop Drawings, Product Data, Samples, and other submittals.
- B. Related Requirements:
 - 1. Section 013200 "Construction Progress Documentation" for submitting schedules and reports, including Contractor's construction schedule.
 - 2. Section 017823 "Operation and Maintenance Data" for submitting operation and maintenance manuals.
 - 3. Section 017839 "Project Record Documents" for submitting record Drawings, record Specifications, and record Product Data.
 - 4. Section 017900 "Demonstration and Training" for submitting video recordings of demonstration of equipment and training of Owner's personnel.

1.3 DEFINITIONS

- A. Action Submittals: Written and graphic information and physical samples that require Architect's responsive action. Action submittals are those submittals indicated in individual Specification Sections as "action submittals."
- B. Informational Submittals: Written and graphic information and physical samples that do not require Architect's responsive action. Submittals may be rejected for not complying with requirements. Informational submittals are those submittals indicated in individual Specification Sections as "informational submittals."
- C. Portable Document Format (PDF): An open standard file format licensed by Adobe Systems used for representing documents in a device-independent and display resolution-independent fixed-layout document format.

1.4 ACTION SUBMITTALS

- A. Submittal Schedule: Submit a schedule of submittals, arranged in chronological order by dates required by construction schedule. Include time required for review, ordering, manufacturing, fabrication, and delivery when establishing dates. Include additional time required for making

corrections or revisions to submittals noted by Architect and additional time for handling and reviewing submittals required by those corrections.

1. Coordinate submittal schedule with list of subcontracts, the schedule of values, and Contractor's construction schedule.
2. Initial Submittal: Submit concurrently with startup construction schedule. Include submittals required during the first 60 days of construction. List those submittals required to maintain orderly progress of the Work and those required early because of long lead time for manufacture or fabrication.
3. Format: Arrange the following information in a tabular format:
 - a. Scheduled date for first submittal.
 - b. Specification Section number and title.
 - c. Submittal category: Action; informational.
 - d. Description of the Work covered.
 - e. Scheduled date for Architect's final release or approval.
 - f. Scheduled date of fabrication.
 - g. Scheduled dates for purchasing.
 - h. Scheduled dates for installation.

1.5 SUBMITTAL ADMINISTRATIVE REQUIREMENTS

- A. Architect's Digital Data Files: Electronic digital data files of the Contract Drawings will be provided by Architect for Contractor's use in preparing submittals.
 1. Architect will furnish Contractor digital data drawing files of the Contract Drawings for use in preparing Shop Drawings at mutually agreed intervals.
 - a. Architect makes no representations as to the accuracy or completeness of digital data drawing files as they relate to the Contract Drawings.
 - b. The following digital data files will be furnished for each appropriate discipline:
 - 1) Revit files.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities.
 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals, and related activities that require sequential activity.
 2. Submit all submittal items required for each Specification Section concurrently unless partial submittals for portions of the Work are indicated on approved submittal schedule.
 3. Submit action submittals and informational submittals required by the same Specification Section as separate packages under separate transmittals.
 4. Coordinate transmittal of different types of submittals for related parts of the Work so processing will not be delayed because of need to review submittals concurrently for coordination.
 - a. Architect reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received. Architect to notify the contractor if another submittal is required to complete the review.

- C. Processing Time: Allow time for submittal review, including time for resubmittals, as follows. Time for review shall commence on Architect's receipt of submittal. No extension of the Contract Time will be authorized because of failure to transmit submittals enough in advance of the Work to permit processing, including resubmittals.
1. Initial Review: Allow 15 days for initial review of each submittal. Allow additional time if coordination with subsequent submittals is required. Architect will advise Contractor when a submittal being processed must be delayed for coordination.
 2. Intermediate Review: If intermediate submittal is necessary, process it in same manner as initial submittal.
 3. Resubmittal Review: Allow 15 days for review of each resubmittal.
 4. Sequential Review: Where sequential review of submittals by Architect's consultants, Owner, or other parties is indicated, allow 21 days for initial review of each submittal.
 5. Concurrent Consultant Review: Where the Contract Documents indicate that submittals may be transmitted simultaneously to Architect and to Architect's consultants, allow 15 days for review of each submittal. Submittal will be returned to Architect before being returned to Contractor.
 6. Concurrent Contractor Review: Kitchell Contractors, Inc. shall reserve the right to request concurrent review of submittals as required to facilitate the schedule. With this approach, review of the submittals shall be completed concurrently by both the Architect and Contractor for a period not exceeding 15 days.
- D. Paper Submittals: Place a permanent label or title block on each submittal item for identification.
1. Indicate name of firm or entity that prepared each submittal on label or title block.
 2. Provide a space approximately 4 by 6 inches on label or beside title block to record Contractor's review and approval markings and action taken by Architect.
 3. Include the following information for processing and recording action taken:
 - a. Project name.
 - b. Date.
 - c. Name of Architect.
 - d. Name of Construction Manager.
 - e. Name of Contractor.
 - f. Name of subcontractor.
 - g. Name of supplier.
 - h. Name of manufacturer.
 - i. Submittal number or other unique identifier, including revision identifier.
 - 1) Submittal number shall use Specification Section number followed by a decimal point and then a sequential number (e.g., 061000.01). Resubmittals shall include an alphabetic suffix after another decimal point (e.g., 061000.01.A).
 - j. Number and title of appropriate Specification Section.
 - k. Drawing number and detail references, as appropriate.
 - l. Location(s) where product is to be installed, as appropriate.
 - m. Other necessary identification.

4. Additional Paper Copies: Unless additional copies are required for final submittal, and unless Architect observes noncompliance with provisions in the Contract Documents, initial submittal may serve as final submittal.
 - a. Submit one copy of submittal to concurrent reviewer in addition to specified number of copies to Architect.
5. Transmittal for Paper Submittals: Assemble each submittal individually and appropriately for transmittal and handling. Transmit each submittal using a transmittal form. Architect will return without review submittals received from sources other than Contractor.
 - a. Transmittal Form for Paper Submittals: Use form provided by Architect.
 - b. Transmittal Form for Paper Submittals: Provide locations on form for the following information:
 - 1) Project name.
 - 2) Date.
 - 3) Destination (To:).
 - 4) Source (From:).
 - 5) Name and address of Architect.
 - 6) Name of Construction Manager.
 - 7) Name of Contractor.
 - 8) Name of firm or entity that prepared submittal.
 - 9) Names of subcontractor, manufacturer, and supplier.
 - 10) Category and type of submittal.
 - 11) Submittal purpose and description.
 - 12) Specification Section number and title.
 - 13) Specification paragraph number or drawing designation and generic name for each of multiple items.
 - 14) Drawing number and detail references, as appropriate.
 - 15) Indication of full or partial submittal.
 - 16) Transmittal number, numbered consecutively.
 - 17) Submittal and transmittal distribution record.
 - 18) Remarks.
 - 19) Signature of transmitter.

- E. Electronic Submittals: Identify and incorporate information in each electronic submittal file as follows:
 1. Assemble complete submittal package into a single indexed file incorporating submittal requirements of a single Specification Section and transmittal form with links enabling navigation to each item.
 2. Name file with submittal number or other unique identifier, including revision identifier.
 - a. File name shall use project identifier and Specification Section number followed by a decimal point and then a sequential number (e.g., LNHS-061000.01). Resubmittals shall include an alphabetic suffix after another decimal point (e.g., LNHS-061000.01.A).

3. Provide means for insertion to permanently record Contractor's review and approval markings and action taken by Architect.
 4. Transmittal Form for Electronic Submittals: Use electronic form acceptable to Owner, containing the following information:
 - a. Project name.
 - b. Date.
 - c. Name and address of Architect.
 - d. Name of Construction Manager.
 - e. Name of Contractor.
 - f. Name of firm or entity that prepared submittal.
 - g. Names of subcontractor, manufacturer, and supplier.
 - h. Category and type of submittal.
 - i. Submittal purpose and description.
 - j. Specification Section number and title.
 - k. Specification paragraph number or drawing designation and generic name for each of multiple items.
 - l. Drawing number and detail references, as appropriate.
 - m. Location(s) where product is to be installed, as appropriate.
 - n. Related physical samples submitted directly.
 - o. Indication of full or partial submittal.
 - p. Transmittal number, numbered consecutively.
 - q. Submittal and transmittal distribution record.
 - r. Other necessary identification.
 - s. Remarks.
- F. Options: Identify options requiring selection by Architect.
- G. Deviations and Additional Information: On an attached separate sheet, prepared on Contractor's letterhead, record relevant information, requests for data, revisions other than those requested by Architect on previous submittals, and deviations from requirements in the Contract Documents, including minor variations and limitations. Include same identification information as related submittal.
- H. Resubmittals: Make resubmittals in same form and number of copies as initial submittal.
 1. Note date and content of previous submittal.
 2. Note date and content of revision in label or title block and clearly indicate extent of revision.
 3. Resubmit submittals until they are marked with approval notation from Architect's action stamp.
- I. Distribution: Furnish copies of final submittals to manufacturers, subcontractors, suppliers, fabricators, installers, authorities having jurisdiction, and others as necessary for performance of construction activities. Show distribution on transmittal forms.
- J. Use for Construction: Retain complete copies of submittals on Project site. Use only final action submittals that are marked with approval notation from Architect's action stamp.

PART 2 - PRODUCTS

2.1 SUBMITTAL PROCEDURES

- A. General Submittal Procedure Requirements: Prepare and submit submittals required by individual Specification Sections. Types of submittals are indicated in individual Specification Sections.
1. Post electronic submittals as PDF electronic files directly to Prolog Converge as established by the Contractor.
 - a. Architect will return annotated file. Annotate and retain one copy of file as an electronic Project record document file.
 2. Submit electronic submittals via email as PDF electronic files.
 - a. Architect will return annotated file. Annotate and retain one copy of file as an electronic Project record document file.
 3. Action Submittals: Consultant Review: Contractor to submit seven (7) copies. Architect to return six (6) copies.
 4. Action Submittal with Consultant Review: Contractor to submit eight (8) copies. Architect to return six (6) copies.
 5. Informational Submittals: Submit two paper copies of each submittal unless otherwise indicated. Architect will not return copies.
 6. Certificates and Certifications Submittals: Provide a statement that includes signature of entity responsible for preparing certification. Certificates and certifications shall be signed by an officer or other individual authorized to sign documents on behalf of that entity.
- B. Product Data: Collect information into a single submittal for each element of construction and type of product or equipment.
1. If information must be specially prepared for submittal because standard published data are not suitable for use, submit as Shop Drawings, not as Product Data.
 2. Mark each copy of each submittal to show which products and options are applicable.
 3. Include the following information, as applicable:
 - a. Manufacturer's catalog cuts.
 - b. Manufacturer's product specifications.
 - c. Standard color charts.
 - d. Statement of compliance with specified referenced standards.
 - e. Testing by recognized testing agency.
 - f. Application of testing agency labels and seals.
 - g. Notation of coordination requirements.
 - h. Availability and delivery time information.
 4. For equipment, include the following in addition to the above, as applicable:
 - a. Wiring diagrams showing factory-installed wiring.

- b. Printed performance curves.
 - c. Operational range diagrams.
 - d. Clearances required to other construction, if not indicated on accompanying Shop Drawings.
 - 5. Submit Product Data before or concurrent with Samples.
 - 6. Submit Product Data in the following format:
 - a. PDF electronic file.
 - b. Three paper copies of Product Data unless otherwise indicated. Architect will return two copies.
- C. Shop Drawings: Prepare Project-specific information, drawn accurately to scale. Do not base Shop Drawings on reproductions of the Contract Documents or standard printed data, unless submittal based on Architect's digital data drawing files is otherwise permitted.
- 1. Preparation: Fully illustrate requirements in the Contract Documents. Include the following information, as applicable:
 - a. Identification of products.
 - b. Schedules.
 - c. Compliance with specified standards.
 - d. Notation of coordination requirements.
 - e. Notation of dimensions established by field measurement.
 - f. Relationship and attachment to adjoining construction clearly indicated.
 - g. Seal and signature of professional engineer if specified.
 - 2. Sheet Size: Except for templates, patterns, and similar full-size drawings, submit Shop Drawings on sheets at least 8-1/2 by 11 inches, but no larger than 30 by 42 inches.
 - 3. Submit Shop Drawings in the following format:
 - a. PDF electronic file.
 - b. Two opaque (bond) copies of each submittal. Architect will return one copy(ies).
 - c. Three opaque copies of each submittal. Architect will retain two copies; remainder will be returned.
- D. Samples: Submit Samples for review of kind, color, pattern, and texture for a check of these characteristics with other elements and for a comparison of these characteristics between submittal and actual component as delivered and installed.
- 1. Transmit Samples that contain multiple, related components such as accessories together in one submittal package.
 - 2. Identification: Attach label on unexposed side of Samples that includes the following:
 - a. Generic description of Sample.
 - b. Product name and name of manufacturer.
 - c. Sample source.
 - d. Number and title of applicable Specification Section.
 - e. Specification paragraph number and generic name of each item.

3. For projects where electronic submittals are required, provide corresponding electronic submittal of Sample transmittal, digital image file illustrating Sample characteristics, and identification information for record.
 4. Disposition: Maintain sets of approved Samples at Project site, available for quality-control comparisons throughout the course of construction activity. Sample sets may be used to determine final acceptance of construction associated with each set.
 - a. Samples that may be incorporated into the Work are indicated in individual Specification Sections. Such Samples must be in an undamaged condition at time of use.
 - b. Samples not incorporated into the Work, or otherwise designated as Owner's property, are the property of Contractor.
 5. Samples for Initial Selection: Submit manufacturer's color charts consisting of units or sections of units showing the full range of colors, textures, and patterns available.
 - a. Number of Samples: Submit one full set(s) of available choices where color, pattern, texture, or similar characteristics are required to be selected from manufacturer's product line. Architect will return submittal with options selected.
 6. Samples for Verification: Submit full-size units or Samples of size indicated, prepared from same material to be used for the Work, cured and finished in manner specified, and physically identical with material or product proposed for use, and that show full range of color and texture variations expected. Samples include, but are not limited to, the following: partial sections of manufactured or fabricated components; small cuts or containers of materials; complete units of repetitively used materials; swatches showing color, texture, and pattern; color range sets; and components used for independent testing and inspection.
 - a. Number of Samples: Submit three sets of Samples. Architect will retain one Sample sets; remainder will be returned. Mark up and retain one returned Sample set as a project record sample.
 - 1) Submit a single Sample where assembly details, workmanship, fabrication techniques, connections, operation, and other similar characteristics are to be demonstrated.
 - 2) If variation in color, pattern, texture, or other characteristic is inherent in material or product represented by a Sample, submit at least two sets of paired units that show approximate limits of variations.
- E. Product Schedule: As required in individual Specification Sections, prepare a written summary indicating types of products required for the Work and their intended location. Include the following information in tabular form:
1. Type of product. Include unique identifier for each product indicated in the Contract Documents or assigned by Contractor if none is indicated.
 2. Manufacturer and product name, and model number if applicable.
 3. Number and name of room or space.
 4. Location within room or space.
 5. Submit product schedule in the following format:

- a. PDF electronic file.
 - b. Three paper copies of product schedule or list unless otherwise indicated. Architect will return two copies.
- F. Coordination Drawing Submittals: Comply with requirements specified in Section 013100 "Project Management and Coordination."
- G. Contractor's Construction Schedule: Comply with requirements specified in Section 013200 "Construction Progress Documentation."
- H. Application for Payment and Schedule of Values: Comply with requirements specified in Section 012900 "Payment Procedures."
- I. Test and Inspection Reports and Schedule of Tests and Inspections Submittals: Comply with requirements specified in Section 014000 "Quality Requirements."
- J. Closeout Submittals and Maintenance Material Submittals: Comply with requirements specified in Section 017700 "Closeout Procedures."
- K. Maintenance Data: Comply with requirements specified in Section 017823 "Operation and Maintenance Data."
- L. Installer Certificates: Submit written statements on manufacturer's letterhead certifying that Installer complies with requirements in the Contract Documents and, where required, is authorized by manufacturer for this specific Project.
- M. Manufacturer Certificates: Submit written statements on manufacturer's letterhead certifying that manufacturer complies with requirements in the Contract Documents. Include evidence of manufacturing experience where required.
- N. Product Certificates: Submit written statements on manufacturer's letterhead certifying that product complies with requirements in the Contract Documents.
- O. Material Certificates: Submit written statements on manufacturer's letterhead certifying that material complies with requirements in the Contract Documents.
- P. Material Test Reports: Submit reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting test results of material for compliance with requirements in the Contract Documents.
- Q. Product Test Reports: Submit written reports indicating that current product produced by manufacturer complies with requirements in the Contract Documents. Base reports on evaluation of tests performed by manufacturer and witnessed by a qualified testing agency, or on comprehensive tests performed by a qualified testing agency.
- R. Research Reports: Submit written evidence, from a model code organization acceptable to authorities having jurisdiction, that product complies with building code in effect for Project. Include the following information:
- 1. Name of evaluation organization.
 - 2. Date of evaluation.

3. Time period when report is in effect.
 4. Product and manufacturers' names.
 5. Description of product.
 6. Test procedures and results.
 7. Limitations of use.
- S. Preconstruction Test Reports: Submit reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of tests performed before installation of product, for compliance with performance requirements in the Contract Documents.
- T. Compatibility Test Reports: Submit reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of compatibility tests performed before installation of product. Include written recommendations for primers and substrate preparation needed for adhesion.
- U. Field Test Reports: Submit written reports indicating and interpreting results of field tests performed either during installation of product or after product is installed in its final location, for compliance with requirements in the Contract Documents.
- V. Design Data: Prepare and submit written and graphic information, including, but not limited to, performance and design criteria, list of applicable codes and regulations, and calculations. Include list of assumptions and other performance and design criteria and a summary of loads. Include load diagrams if applicable. Provide name and version of software, if any, used for calculations. Include page numbers.

2.2 DELEGATED-DESIGN SERVICES

- A. Performance and Design Criteria: Where professional design services or certifications by a design professional are specifically required of Contractor by the Contract Documents, provide products and systems complying with specific performance and design criteria indicated.
1. If criteria indicated are not sufficient to perform services or certification required, submit a written request for additional information to Architect.

PART 3 - EXECUTION

3.1 CONTRACTOR'S REVIEW

- A. Action and Informational Submittals: Review each submittal and check for coordination with other Work of the Contract and for compliance with the Contract Documents. Note corrections and field dimensions. Mark with approval stamp before submitting to Architect.
- B. Project Closeout and Maintenance Material Submittals: See requirements in Section 017700 "Closeout Procedures."
- C. Approval Stamp: Stamp each submittal with a uniform, approval stamp. Include Project name and location, submittal number, Specification Section title and number, name of reviewer, date

of Contractor's approval, and statement certifying that submittal has been reviewed, checked, and approved for compliance with the Contract Documents.

3.2 ARCHITECT'S ACTION

- A. Action Submittals: Architect will review each submittal, make marks to indicate corrections or revisions required, and return it. Architect will stamp each submittal with an action stamp and will mark stamp appropriately to indicate action.

END OF SECTION 013300

SECTION 017300 - EXECUTION

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes general administrative and procedural requirements governing execution of the Work including, but not limited to, the following:

1. Construction layout.
2. Field engineering and surveying.
3. Installation of the Work.
4. Cutting and patching.
5. Coordination of Owner-installed products.
6. Progress cleaning.
7. Starting and adjusting.
8. Protection of installed construction.
9. Correction of the Work.

- B. Related Requirements:

1. Section 011000 "Summary" for limits on use of Project site.
2. Section 013300 "Submittal Procedures" for submitting surveys.
3. Section 017700 "Closeout Procedures" for submitting final property survey with Project Record Documents, recording of Owner-accepted deviations from indicated lines and levels, and final cleaning.

1.3 SUBMITTALS

- A. Landfill Receipts: Submit copy of receipts issued by a landfill facility, licensed to accept hazardous materials, for hazardous waste disposal.

PART 2 - PRODUCTS (Not used)

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Existing Conditions: The existence and location of underground and other utilities and construction indicated as existing are not guaranteed. Before beginning sitework, investigate and verify the existence and location of underground utilities, mechanical and electrical systems, and other construction affecting the Work.
 - 1. Before construction, verify the location and invert elevation at points of connection of sanitary sewer, storm sewer, and water-service piping; underground electrical services, and other utilities.
 - 2. Furnish location data for work related to Project that must be performed by public utilities serving Project site.
- B. Examination and Acceptance of Conditions: Before proceeding with each component of the Work, examine substrates, areas, and conditions, with Installer or Applicator present where indicated, for compliance with requirements for installation tolerances and other conditions affecting performance. Record observations.
 - 1. Examine roughing-in for mechanical and electrical systems to verify actual locations of connections before equipment and fixture installation.
 - 2. Examine walls, floors, and roofs for suitable conditions where products and systems are to be installed.
 - 3. Verify compatibility with and suitability of substrates, including compatibility with existing finishes or primers.

3.2 PREPARATION

- A. Existing Utility Information: Furnish information to local utility or Owner that is necessary to adjust, move, or relocate existing utility structures, utility poles, lines, services, or other utility appurtenances located in or affected by construction. Coordinate with authorities having jurisdiction.
- B. Field Measurements: Take field measurements as required to fit the Work properly. Recheck measurements before installing each product. Where portions of the Work are indicated to fit to other construction, verify dimensions of other construction by field measurements before fabrication. Coordinate fabrication schedule with construction progress to avoid delaying the Work.
- C. Space Requirements: Verify space requirements and dimensions of items shown diagrammatically on Drawings.
- D. Review of Contract Documents and Field Conditions: Immediately on discovery of the need for clarification of the Contract Documents caused by differing field conditions outside the control of Contractor, submit a request for information to Architect according to requirements in Section 013100 "Project Management and Coordination."

3.3 CONSTRUCTION LAYOUT

- A. Verification: Before proceeding to lay out the Work, verify layout information shown on Drawings, in relation to the existing separation walls to Emergency Center space. If discrepancies are discovered, notify Architect promptly.

3.4 INSTALLATION

- A. General: Locate the Work and components of the Work accurately, in correct alignment and elevation, as indicated.
 - 1. Make vertical work plumb and make horizontal work level.
 - 2. Where space is limited, install components to maximize space available for maintenance and ease of removal for replacement.
 - 3. Conceal pipes, ducts, and wiring in finished areas unless otherwise indicated.
 - 4. Maintain minimum headroom clearance of 96 inches in occupied spaces and 90 inches in unoccupied spaces to the extent possible.
- B. Comply with manufacturer's written instructions and recommendations for installing products in applications indicated.
- C. Install products at the time and under conditions that will ensure the best possible results. Maintain conditions required for product performance until Substantial Completion.
- D. Conduct construction operations so no part of the Work is subjected to damaging operations or loading in excess of that expected during normal conditions of occupancy.
- E. Sequence the Work and allow adequate clearances to accommodate movement of construction items on site and placement in permanent locations.
- F. Templates: Obtain and distribute to the parties involved templates for work specified to be factory prepared and field installed. Check Shop Drawings of other work to confirm that adequate provisions are made for locating and installing products to comply with indicated requirements.
- G. Attachment: Provide blocking and attachment plates and anchors and fasteners of adequate size and number to securely anchor each component in place, accurately located and aligned with other portions of the Work. Where size and type of attachments are not indicated, verify size and type required for load conditions.
 - 1. Mounting Heights: Where mounting heights are not indicated, mount components at heights directed by Architect.
 - 2. Allow for building movement, including thermal expansion and contraction.
 - 3. Coordinate installation of anchorages. Furnish setting drawings, templates, and directions for installing anchorages, including sleeves, concrete inserts, anchor bolts, and items with integral anchors, that are to be embedded in concrete or masonry. Deliver such items to Project site in time for installation.
- H. Joints: Make joints of uniform width. Where joint locations in exposed work are not indicated, arrange joints for the best visual effect. Fit exposed connections together to form hairline joints.

- I. Hazardous Materials: Use products, cleaners, and installation materials that are not considered hazardous.

3.5 CUTTING AND PATCHING

- A. Cutting and Patching, General: Employ skilled workers to perform cutting and patching. Proceed with cutting and patching at the earliest feasible time, and complete without delay.
 - 1. Cut in-place construction to provide for installation of other components or performance of other construction, and subsequently patch as required to restore surfaces to their original condition.
- B. Existing Warranties: Remove, replace, patch, and repair materials and surfaces cut or damaged during installation or cutting and patching operations, by methods and with materials so as not to void existing warranties.
- C. Temporary Support: Provide temporary support of work to be cut.
- D. Protection: Protect in-place construction during cutting and patching to prevent damage. Provide protection from adverse weather conditions for portions of Project that might be exposed during cutting and patching operations.

3.6 OWNER-INSTALLED PRODUCTS

- A. Project Access: Provide access to Project area for Owner's construction personnel.
- B. Coordination: Coordinate construction and operations of the Work with work performed by Owner's construction personnel.
 - 1. Construction Schedule: Inform Owner of Contractor's preferred construction schedule for Owner's portion of the Work. Adjust construction schedule based on a mutually agreeable timetable. Notify Owner if changes to schedule are required due to differences in actual construction progress.
 - 2. Preinstallation Conferences: Include Owner's construction personnel at preinstallation conferences covering portions of the Work that are to receive Owner's work. Attend preinstallation conferences conducted by Owner's construction personnel if portions of the Work depend on Owner's construction.

3.7 PROGRESS CLEANING

- A. General: Clean Project site and work areas daily, including common areas. Enforce requirements strictly. Dispose of materials lawfully.
 - 1. Comply with requirements in NFPA 241 for removal of combustible waste materials and debris.
 - 2. Do not hold waste materials more than seven days during normal weather or three days if the temperature is expected to rise above 80 deg F.
 - 3. Containerize hazardous and unsanitary waste materials separately from other waste. Mark containers appropriately and dispose of legally, according to regulations.

- a. Use containers intended for holding waste materials of type to be stored.
- 4. Coordinate progress cleaning for joint-use areas where Contractor and other contractors are working concurrently.
- B. Site: Maintain Project site free of waste materials and debris.
- C. Work Areas: Clean areas where work is in progress to the level of cleanliness necessary for proper execution of the Work.
 - 1. Remove liquid spills promptly.
 - 2. Where dust would impair proper execution of the Work, broom-clean or vacuum the entire work area, as appropriate.
- D. Installed Work: Keep installed work clean. Clean installed surfaces according to written instructions of manufacturer or fabricator of product installed, using only cleaning materials specifically recommended. If specific cleaning materials are not recommended, use cleaning materials that are not hazardous to health or property and that will not damage exposed surfaces.
- E. Concealed Spaces: Remove debris from concealed spaces before enclosing the space.
- F. Exposed Surfaces in Finished Areas: Clean exposed surfaces and protect as necessary to ensure freedom from damage and deterioration at time of Substantial Completion.
- G. Waste Disposal: Do not bury or burn waste materials on-site. Do not wash waste materials down sewers or into waterways.
- H. During handling and installation, clean and protect construction in progress and adjoining materials already in place. Apply protective covering where required to ensure protection from damage or deterioration at Substantial Completion.
- I. Clean and provide maintenance on completed construction as frequently as necessary through the remainder of the construction period. Adjust and lubricate operable components to ensure operability without damaging effects.
- J. Limiting Exposures: Supervise construction operations to assure that no part of the construction, completed or in progress, is subject to harmful, dangerous, damaging, or otherwise deleterious exposure during the construction period.

3.8 STARTING AND ADJUSTING

- A. Coordinate startup and adjusting of equipment and operating components with requirements in Section 019113 "General Commissioning Requirements."
- B. Start equipment and operating components to confirm proper operation. Remove malfunctioning units, replace with new units, and retest.
- C. Adjust equipment for proper operation. Adjust operating components for proper operation without binding.

- D. Test each piece of equipment to verify proper operation. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.
- E. Manufacturer's Field Service: Comply with qualification requirements in Section 014000 "Quality Requirements."

3.9 PROTECTION OF INSTALLED CONSTRUCTION

- A. Provide final protection and maintain conditions that ensure installed Work is without damage or deterioration at time of Substantial Completion.
- B. Comply with manufacturer's written instructions for temperature and relative humidity.

END OF SECTION 017300

SECTION 017700 - CLOSEOUT PROCEDURES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes administrative and procedural requirements for contract closeout, including, but not limited to, the following:
 - 1. Inspection procedures.
 - 2. Operation and maintenance manuals.
 - 3. Warranties.
 - 4. Instruction of Owner's personnel.
 - 5. Final cleaning.
- B. Related Requirements:
 - 1. Section 01 "Payment Procedures" for requirements for application for submitting final completion payment for Substantial to Final Completion.
 - 2. Section 01 "Execution" for progress cleaning of Project site.
 - 3. Section 01 "Project Record Documents" for submitting record Drawings, record Specifications, and record Product Data.
 - 4. Section 01 "Demonstration and Training" for requirements for instructing Owner's personnel.
 - 5. Divisions 02 through 33 Sections for specific closeout and special cleaning requirements for the Work in those Sections.

1.3 SUBSTANTIAL COMPLETION

- A. Preliminary Procedures: Before requesting inspection for determining date of Substantial Completion, complete the following. List items below that are incomplete in request.
 - 1. Prepare a list of items to be completed and corrected (punch list), the value of items on the list, and reasons why the Work is not complete.
 - 2. Advise Owner of pending insurance changeover requirements.
 - 3. Submit specific warranties, workmanship bonds, maintenance service agreements, final certifications, and similar documents.
 - 4. Obtain and submit releases permitting Owner unrestricted use of the work and access to services and utilities. Include occupancy permits, operating certificates, and similar releases.

5. Prepare and submit Project Record Documents, operation and maintenance manuals, completion construction photographs, damage or settlement surveys, property surveys, and similar final record information.
 6. Deliver tools, spare parts, extra materials, and similar items to location designated by Owner. Label with manufacturer's name and model number where applicable.
 7. Make final changeover of permanent locks and deliver keys to Owner. Advise Owner's personnel of changeover insecurity provisions.
 8. Complete startup testing of systems.
 9. Submit test/adjust/balance records.
 10. Terminate and remove temporary facilities from Project site, along with mockups, construction tools, and similar elements.
 11. Advise Owner of changeover in heat and other utilities.
 12. Submit changeover information related to Owner's occupancy, use, operation, and maintenance.
 13. Complete final cleaning requirements, including touchup painting.
 14. Touch up and otherwise repair and restore marred exposed finishes to eliminate visual defects.
- B. Inspection: Submit a written request for inspection to determine Substantial Completion. Architect will either proceed with inspection or notify Contractor of unfulfilled requirements. Architect will prepare the Certificate of Substantial Completion after inspection or will notify Contractor of items, either on Contractor's list or additional items identified by Architect, that must be completed or corrected before certificate will be issued.
1. Reinspection: Request reinspection when the Work identified in previous inspections as incomplete is completed or corrected.
 2. Results of completed inspection will form the basis of requirements for final completion.

1.4 FINAL COMPLETION PROCEDURES

- A. Submittals Prior to Final Completion: Before requesting final inspection for determining final completion, complete the following:
1. Submit a final Application for Payment according to Section 012900 "Payment Procedures."
 2. Submit certified copy of Architect's Substantial Completion inspection list of items to be completed or corrected (punch list), endorsed and dated by Architect. Certified copy of the list shall state that each item has been completed or otherwise resolved for acceptance.
 3. Instruct Owner's personnel in operation, adjustment and maintenance of products, equipment, and systems.
- B. Inspection: Submit a written request for final inspection to determine acceptance. Owner/Architect will either proceed with inspection or notify Contractor of unfulfilled requirements. Architect will prepare a final Certificate for Payment after inspection or will notify Contractor of construction that must be completed or corrected before certificate will be issued.
1. Reinspection: Request reinspection when the Work identified in previous inspections as incomplete is completed or corrected.

1.5 LIST OF INCOMPLETE ITEMS (PUNCH LIST)

- A. Organization of List: Include name and identification of each space and area affected by construction operations for incomplete items and items needing correction including, if necessary, areas disturbed by Contractor that are outside the limits of construction. Use CSI Form 14.1A or approved equivalent.
1. Organize list of spaces in sequential order, starting with exterior areas first and proceeding from lowest floor to highest floor.
 2. Organize items applying to each space by major element, including categories for ceiling, individual walls, floors, equipment, and building systems.
 3. Include the following information at the top of each page:
 - a. Project name.
 - b. Date.
 - c. Name of Architect.
 - d. Name of Contractor.
 - e. Page number.

1.6 SUBMITTAL OF PROJECT WARRANTIES

- A. Time of Submittal: Submit written warranties on request of Architect for designated portions of the Work where commencement of warranties other than date of Substantial Completion is indicated, or when delay in submittal of warranties might limit Owner's rights under warranty.
- B. Partial Occupancy: Submit properly executed warranties within 15 days of completion of designated portions of the Work that are completed and occupied or used by Owner during construction period by separate agreement with Contractor.
- C. Organize warranty documents into an orderly sequence based on the table of contents of Project Manual.
1. Bind warranties and bonds in heavy-duty, three-ring, vinyl-covered, loose-leaf binders, thickness as necessary to accommodate contents, and sized to receive 8-1/2-by-11-inch paper.
 2. Provide heavy paper dividers with plastic-covered tabs for each separate warranty. Mark tab to identify the product or installation. Provide a typed description of the product or installation, including the name of the product and the name, address, and telephone number of Installer.
 3. Identify each binder on the front and spine with the typed or printed title "WARRANTIES," Project name, and name of Contractor.
- D. Provide additional copies of each warranty to include in operation and maintenance manuals.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. Cleaning Agents: Use cleaning materials and agents recommended by manufacturer or fabricator of the surface to be cleaned. Do not use cleaning agents that are potentially hazardous to health or property or that might damage finished surfaces.

PART 3 - EXECUTION

3.1 FINAL CLEANING

- A. General: Perform final cleaning. Conduct cleaning and waste-removal operations to comply with local laws and ordinances and Federal and local environmental and antipollution regulations.
- B. Cleaning: Employ experienced workers or professional cleaners for final cleaning. Clean each surface or unit to condition expected in an average commercial building cleaning and maintenance program. Comply with manufacturer's written instructions.
 - 1. Complete the following cleaning operations before requesting inspection for certification of Substantial Completion for entire Project or for a designated portion of Project:
 - a. Clean Project site, yard, and grounds, in areas disturbed by construction activities, including landscape development areas, of rubbish, waste material, litter, and other foreign substances.
 - b. Sweep paved areas broom clean. Remove petrochemical spills, stains, and other foreign deposits.
 - c. Rake grounds that are neither planted nor paved to a smooth, even-textured surface.
 - d. Remove tools, construction equipment, machinery, and surplus material from Project site.
 - e. Remove snow and ice to provide safe access to building.
 - f. Clean exposed exterior and interior hard-surfaced finishes to a dirt-free condition, free of stains, films, and similar foreign substances. Avoid disturbing natural weathering of exterior surfaces. Restore reflective surfaces to their original condition.
 - g. Remove debris and surface dust from limited access spaces, including roofs, plenums, shafts, trenches, equipment vaults, manholes, attics, and similar spaces.
 - h. Sweep concrete floors broom clean in unoccupied spaces.
 - i. Vacuum carpet and similar soft surfaces, removing debris and excess nap; clean according to manufacturer's recommendations if visible soil or stains remain.
 - j. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compounds and other noticeable, vision-obscuring materials. Polish mirrors and glass, taking care not to scratch surfaces.
 - k. Remove labels that are not permanent.

- l. Wipe surfaces of mechanical and electrical equipment, elevator equipment, and similar equipment. Remove excess lubrication, paint and mortar droppings, and other foreign substances.
 - m. Clean plumbing fixtures to a sanitary condition, free of stains, including stains resulting from water exposure.
 - n. Replace disposable air filters and clean permanent air filters. Clean exposed surfaces of diffusers, registers, and grills.
 - o. Clean ducts, blowers, and coils, etc in the event that units were not operated with appropriate filtration prior to construction and the ductwork was not properly capped at all times including during shipment, storage and prior to final connection. Cleaning of ductwork, blower, coils, etc. shall be limited to the unit(s) where the above was not adhered and shall not include all air handling units.
 - p. Retain first subparagraph below in environments with demanding HVAC system cleaning standards or for special contamination issues. Below adds significantly to cleaning cost.
 - q. Clean light fixtures, lamps, globes, and reflectors to function with full efficiency.
 - r. Leave Project clean and ready for occupancy.
 - s. Touch up and otherwise repair and restore marred, exposed finishes and surfaces. Replace finishes and surfaces that cannot be satisfactorily repaired or restored or that already show evidence of repair or restoration.
 - 1) Do not paint over "UL" and similar labels, including mechanical and electrical nameplates.
 - t. Replace burned-out bulbs and those noticeably dimmed by hours of use, and defective and noisy starters in fluorescent and mercury vapor fixtures to comply with requirements for new fixtures.
- C. Comply with safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on Owner's property. Do not discharge volatile, harmful, or dangerous materials into drainage systems. Remove waste materials from Project site and dispose of lawfully.
 - D. After contractor's final cleaning, contractor to coordinate with owner's move-in cleaning. Coordinate materials, schedule and process.

3.2 CAMERA VIEWING/INSPECTION

- A. Contractor to provide a video of all underground plumbing lines and provide to owner at the end of construction.

END OF SECTION 017700

SECTION 07 84 00 - FIRESTOPPING

PART 1 - GENERAL

1.1 DESCRIPTION

- A. This section includes Through Penetration Firestop Systems for penetrations through the following fire-resistance rated assemblies, including both blank openings and openings containing penetrating items:
 - 1. Floor assemblies.
 - 2. Roof assemblies.
 - 3. Walls and partitions.
 - 4. Smoke barriers which also call for a fire rating.
 - 5. Construction enclosing compartmentalized areas.
 - 6. Existing, fire and smoke-rated elements.
 - 7. Not included: Non-rated walls and smoke-tight partitions which do not call for a fire rating): Do not require Through Penetration Firestop assemblies.

- B. This section includes Fire-Resistive Joint Assemblies for linear voids where fire-rated floor, roof, or wall assemblies abut one another, including the following types of joints:
 - 1. Head-of-Wall joint created where walls intersect with overhead roof or floor structure (slabs, decking, beams, etc).
 - a. Fire-rated Walls: Select agency-approved assemblies and employ materials specified in this section.
 - b. Non-fire rated partitions (including Smoke Partitions): Seal to structure with Acoustical Sealant specified in Section 092900 "Gypsum Drywall."
 - 2. Non-Fire Rated Expansion Joints: Specified in Section 079513 "Expansion Joint Cover Assemblies."

1.2 QUALITY ASSURANCE

- A. Provide Firestop Systems that comply with the following requirements and those specified in "Performance Requirements" Article:
 - 1. Firestopping tests, performed by a qualified, testing and inspection agency.
 - a. Qualified testing and inspection agency: UL, or another agency performing testing and follow-up inspection services for firestop systems acceptable to local authorities having jurisdiction.
 - 2. Firestop System products bear classification marking of qualified testing and inspection agency.
 - 3. Applications that exist for which no tested system is available through a manufacturer: Provide engineering judgment derived from similar UL system designs or other tests approved by local authorities having jurisdiction, prior to installation.
 - a. Engineering judgment drawings must follow requirements set forth by the International Firestop Council.

- B. Installer Qualifications:
 - 1. Licensed by the State or local authority, where applicable.

2. Shown to have successfully completed not less than 5 comparable scale projects.
 3. Certified Firestopping Contractors.
 - a. The work is to be installed by a contractor with at least one of the following qualifications:
 - 1) Manufacturer Accredited Fire Stop Specialty Contractor.
 - 2) UL Approved Contractor.
 - 3) FM 4991 Approved Contractors.
- C. Single-source: Obtain Firestop Systems for each type of penetration and construction condition indicated from a single manufacturer. A single source contract with one contractor is required for the installation of all firestopping and fire containments systems for the project. This also includes the installation of the Perimeter Fire Containment Systems as specified in Section 078400 "Firestopping."
- D. Fire Test Requirements:
1. Underwriters Laboratories, Inc. (UL):
 - a. UL 1479, "Fire Tests of Through Penetration Firestops."
 - b. UL 2079, "Tests for Fire Resistance of Building Joint Systems."
 - c. UL 263, "Fire Tests of Building Construction and Materials."
 - d. UL 723, "Surface Burning Characteristics of Building Materials."
 2. American Society of Testing and Materials (ASTM):
 - a. ASTM-E814, "Fire Tests of Through Penetration Fire Stops."
 - b. ASTM-E1966, "Test Method for Fire Resistive Joint Systems."
 - c. ASTM-E119, "Fire Tests of Building Construction and Materials."
 - d. ASTM-E84, "Surface Burning Characteristics of Building Materials."
 - e. ASTM-E1399, "Cyclic Movement and Measuring the Minimum and Maximum Joint Widths of Architectural Joint Systems."
 - f. ASTM E 2174, "Standard Practice for On-site Inspection of Installed Fire Resistive Joint Systems and Perimeter Fire Barriers."
- E. References:
1. Underwriters Laboratories (UL) "Fire Resistance Directory":
 - a. Through Penetration Firestop Systems (XHEZ).
 - b. Joint Systems (XHBN).
 - c. Fill, Void or Cavity Materials (XHHW).
 - d. Firestop Devices (XHJI).
 - e. Forming Materials (XHKU).
 - f. Wall Opening Protective Materials (CLIV).
 2. Building Code as locally adopted and amended.
 3. National Fire Protection Association (NFPA):
 - a. NFPA 101: "Life Safety Code."
 - b. NFPA 70: "National Electrical Code."
 4. Firestop Contractors International Association (FCIA):
 - a. Manual of Practice.
 5. International Firestop Council (IFC):
 - a. Ref. 1 Recommended IFC Guidelines for Evaluating Firestop Engineering Judgments (April 2001)
 - b. Ref. 2 Inspectors Field Pocket Guide
- F. Identification Labels for Firestop Assemblies:

1. Install labels which identify each Firestop installation.
2. Label shall be pre-printed by supplier and include the following:
 - a. Name of supplier of Firestopping system.
 - 1) Include manufacturer's representative and phone number.
 - b. UL Design Number or other approved testing agency.
 - c. Date of installation.
 - d. Name of firestopping installer.
3. Identification labels may be in the form of self-adhering stickers, tie-on ID tags, or combination of both as appropriate for permanent identification of firestop assemblies.

G. Environmental Reference Standards:

1. South Coast Air Quality Management District (SCAQMD), Rule #1168. b. Green Seal Standard GS-36.

H. Environmental Criteria:

1. South Coast Air Quality Management District (SCAQMD): Comply with requirements of Rule 1168 – Sealant Applications
2. South Coast Air Quality Management District (SCAQMD): Comply with requirements of Rule 1168 – Adhesive Applications.
 - a. Adhesive VOC Content: 40 CFR 59, Subpart D (EPA Method 24).
3. Green Seal: Comply with requirements of Standard GS-36 - Aerosol Adhesive Applications.
4. California OEHHA Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).
5. California Air Resources Board (ARB) list of Toxic Air Contaminants (California Air Toxics).
6. California's Special Environmental Requirements, specified in California Department of Health Services Standard Practice CA/DHS/EHLB/R-174.

1.3 PERFORMANCE REQUIREMENTS

- A. Provide products that upon curing, do not re-emulsify, dissolve, leach, breakdown or otherwise deteriorate over time from exposure to atmospheric moisture, sweating pipes, ponding water or other forms of moisture characteristic during and after construction.
- B. Provide firestop sealants sufficiently flexible to accommodate motion such as pipe vibration, water hammer, thermal expansion and other normal building movement without damage to the seal.
- C. Pipe insulation shall not be removed, cut away or otherwise interrupted through wall or floor openings.
 1. Provide products appropriately tested for the thickness and type of insulation utilized.
- D. Cabling (i.e. voice, data and video cabling, etc) where frequent cable moves, add-ons, and changes are likely to occur in future:
 1. Where Cable Trays are used to convey such cabling: Utilize re-enterable products (e.g. removable intumescent pillows) specifically designed for retrofit.
 2. Where Cable Trays are not used: Utilize Fire-rated Cable Pathway devices. Where not practical, re-enterable products specifically designed for retrofit may also be used.

- E. Penetrants passing through fire-resistance rated floor-ceiling assemblies contained within chase wall assemblies shall be protected with products tested by being fully exposed to the fire outside of the chase wall.
 - 1. Systems within the UL Fire Resistance Directory that meet this criterion are identified with the words “Chase Wall Optional.”
- F. Penetrants passing through smoke-barrier shall provide L-rating of 5/CFM per square foot or less as tested in accordance with UL-1479.
- G. Fire Resistive Joint Sealants:
 - 1. Provide fire-resistive joint sealants sufficiently flexible to accommodate movement such as thermal expansion and other normal building movement without damage to the seal.
 - 2. Provide fire-resistive joint sealants designed to accommodate a specific range of movement and tested for this purpose in accordance with a cyclic movement test criteria as outlined in Standards, ASTM-E1399, ASTM-E1966 or UL 2079.
 - 3. Provide fire-resistive joint systems subjected to an air leakage test conducted in accordance with Standard, UL 2079 with published L-Ratings for ambient and elevated temperatures as evidence of the ability of the fire-resistive joint system to restrict the movement of smoke.

1.4 SUBMITTALS

- A. Project Information:
 - 1. UL reports with illustration of systems and system numbers.
 - 2. 3M Accredited Fire Stop Specialty Contractor.
 - 3. Submittal of FM 4991 credentials.
- B. Contract Closeout Information:
 - 1. The fire stop contractor is to supply documentation in the form of the “Firestop Tracking Process” to include the following at a minimum:
 - a. Architectural Details.
 - b. Firestop Affidavit.
 - c. Firestop System Snapshot.
 - d. Installation log.
 - e. Firestop Systems.
 - f. IFC guidelines for Engineering Judgements.
 - g. Product Information of utilized Products.
 - h. All other relevant documentations. Building code excerpts.
 - i. Interactive Life Safety Floor Plan to include all firestop systems installed with links to the relevant Firestop system.
 - 2. Electronic file of all project Documentation provided to the General contractor, Architect, Inspector and Owner.
 - 3. Letter stating that installed Through Penetration Firestop Systems and Fire-Resistive Construction Joints have been labeled.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Deliver products to Project site in original, unopened containers.

- B. Store and handle materials to prevent their deterioration or damage due to moisture, temperature changes, contaminants or other causes to comply with manufacturer recommendations.

1.6 PROJECT CONDITIONS

- A. Do not install when ambient or substrate temperatures are outside limitations recommended by manufacturer.
- B. Do not install when substrates are wet due to rain, frost, condensation, or other causes.
- C. Do not use materials that contain flammable solvents.

1.7 COORDINATION

- A. Coordinate construction of openings and penetrating items to ensure that Firestopping Systems are installed according to specified requirements.
- B. Coordinate sizing of sleeves, openings, core-drilled holes or cut openings to accommodate through Penetration Firestop Systems.
- C. Schedule installation of firestopping after completion of penetrating item installation but prior to covering or concealing of openings.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. Acceptable manufacturers:
 - 1. Firestopping Materials (including fillers, sealants and other items):
 - a. Base:
 - 1) 3M.
 - b. Optional:
 - 1) BlazeFrame, Inc
 - 2) Specified Technologies, Inc (STI).
 - 3) Hilti.
 - 4) Tremco.
 - 2. Forming Materials:
 - a. Base:
 - 1) Thermafiber.
 - b. Optional:
 - 1) BlazeFrame, Inc
 - 2) Roxul Inc.
 - 3) IIG Minwool.
 - 4) Rock Wool Manufacturing.

2.2 FIRESTOPPING – GENERAL REQUIREMENTS

- A. Selection Responsibility:
 - 1. Contractor is responsible to select systems which are approved for conditions encountered and when installed, will maintain required fire separations.
- B. Provide firestopping systems and materials that are compatible with one another, with the substrates forming openings, and with penetrating items, under conditions of service and application.
- C. Provide components for each firestopping system that are needed to install fill materials.
- D. Materials shall be provided by a single firestopping products manufacturer as far a possible.
- E. All materials used shall be the specific items named in the UL assemblies being installed.
- F. All materials must be UL or other approved third party testing agency-listed for the designated for the designated fire-resistance-rated systems.
- G. Use only products that have been tested for specific fire-resistance-rated construction conditions conforming to construction assembly type, penetrating item type, annular space requirements, void width, movement capabilities, and fire-rating involved for each separate instance.
- H. Joints at exterior curtain- wall/ floor intersection. Perimeter Fire Barrier System shall be: Hilti: System No. CEJ 127 P (HI/JS 120-05). Perimeter Fire Barrier System-ASTM E 23-7. F Rating.

2.3 MATERIALS

- A. Latex Sealants:
 - 1. Single component latex formulations that upon cure do not re-emulsify during exposure to moisture.
 - a. Through Penetration Firestop Systems:
 - 1) Base Products: “IC15WB+”, “CP25WB+”, “FireDam 150+” by 3M.
 - 2) Optional Products:
 - a) “SpecSeal Series SSS and LCI Intumescent Sealants,” “SpecSeal Series LC Endothermic Sealant,” and “SpecSeal Series AS Elastomeric Spray” by STI.
 - b) “FS-ONE,” and “CP606” by Hilti.
 - b. Fire-resistive Joints:
 - 1) Base Products: “FireDam 150+”, “Fire Barrier 1000NS”, “Fire Barrier 1003SL”, “Fire Barrier 2000NS”, “FireDam Spray 200” by 3M.
 - 2) Optional Products:
 - a) “SpecSeal Series ES and AS Elastomeric Sealants” by STI.
 - b) “CP606”, “CP601S”, “CP604” and “CP672” by Hilti.
- B. Firestop Devices:
 - 1. Factory-assembled steel collars lined with intumescent material sized to fit specific outside diameter of penetrating item.
 - 2. Base Products: “Fire Barrier Ultra Plastic Pipe Device” by 3M.

3. Optional Products:
 - a. "SpecSeal Series SSC and LLC Firestop Collars" by STI.
 - b. "CP643N" and "CP644" by Hilti.
- C. Intumescent Pads (Wall Opening Protective Materials):
1. Intumescent, non-curing pads or inserts for protection of electrical switch and receptacle boxes, medical gas outlets, and other items recessed in to face of fire rated walls.
 2. Base Products: "Interam Ultra GS Wrap Strip", "3M Fire Barrier Moldable Putty+ pads", "3M Fire Barrier Moldable Putty Stix" by 3M.
 3. Optional Products:
 - a. "SpecSeal Series SSP Firestop Putty Pads" and "SpecSeal Series EP PowerShield Insert Pads" by STI.
 - b. "CP617" by Hilti.
- D. Fire-rated Cable Pathways:
1. Usage:
 - a. Cables passing through fire-rated floors or walls shall pass through Fire-rated Cable Pathway devices made from an intumescent material that adjusts automatically to cable additions or subtractions.
 2. Product Description and Requirements:
 - a. Pathway device modules comprised of steel raceway and intumescent foam pads.
 - b. F-Rating equal to the rating of the barrier in which the device penetrates.
 - c. Pathway devices shall be capable of allowing a 0 to 100% fill of cables.
 - d. Size to accommodate the quantity and size of electrical wires and data cables indicated plus 100% expansion.
 - e. Wire devices to be provided with steel wall plates allowing for single or multiple devices to be ganged together.
 3. Base Product: "3M Fire Barrier Pass-Through Devices" by 3M;
 4. Optional Products:
 - a. "3M Fire Barrier Pass-Through Devices" by 3M;
 - b. "CP653 Speed Sleeve" by Hilti.
- E. Firestop Putty:
1. Intumescent, non-hardening, water resistant putties containing no solvents, inorganic fibers or silicone compounds.
 2. Base Product: "3M Fire Barrier Moldable Putty+ pads", "3M Fire Barrier Moldable Putty Stix" by 3M.
 3. Optional Products:
 - a. "SpecSeal Series SSP Firestop Putty" by STI.
 - b. "CP618" and "CP619" by Hilti.
- F. Wrap Strips:
1. Single component intumescent elastomeric strips faced on both sides with a plastic film:
 2. Base Products: "Interam Ultra GS Wrap Strip", "3M Fire Barrier FS 195+ Wrap Strip" by 3M.
 3. Optional Products:
 - a. "SpecSeal Series RED Wrap Strip" and "SpecSeal Series BLU Wrap Strip" by STI.

- b. “CP648E” and “CP648S” by Hilti.

G. Firestop Pillows:

- 1. Re-enterable, non-curing, mineral fiber core encapsulated with an intumescent coating contained in a flame retardant poly bag.
- 2. Base Product: “3M Fire Barrier Pillows”, “3M Fire Barrier Self-Locking Pillows”, by 3M.
- 3. Optional Products:
 - a. “SpecSeal Series SSB Firestop Pillows” by STI.
 - b. “CP657 FireBlock” by Hilti.

H. Mortar:

- 1. Portland cement based dry-mix product formulated for mixing with water at Project site to form a non-shrinking, water-resistant, homogenous mortar.
- 2. Base Product: “3M Fire Barrier Mortar” by 3M.
- 3. Optional Products:
 - a. “SpecSeal Series SSM Firestop Mortar” by STI.
 - b. “CP637” by Hilti.

I. Silicone Sealants:

- 1. Moisture curing, single component, silicone elastomeric sealant for horizontal surfaces (pourable or nonsag) or vertical surface (nonsag).
- 2. Base Products: “Fire Barrier 3000WT Water Tight Silicone”, “3M Fire Barrier 1000NS and 1003 SL Silicone”, “3M Fire Barrier 2000+”, “Fire Barrier 2000NS” by 3M.
- 3. Optional Products:
 - a. “Pensil 300 Silicone Sealant” and “Pensil 300 SL Self-Leveling Silicone Sealant” by STI.
 - b. “CP601S,” and “CP604” by Hilti.

J. Foam:

- 1. Multi-component, silicone-based, liquid elastomers, that when mixed, expand and cure in place to produce a flexible, non-shrinking foam.
- 2. Base Product: “3M Fire Barrier 2001 RTV Foam” by 3M.
- 3. Optional Products:
 - a. “Pensil 200 Silicone Foam” by STI.
 - b. “CP620” by Hilti.

K. Forming Materials:

- 1. Materials listed as components in laboratory-approved designs.
- 2. Mineral Wool:
 - a. Base Products: “3M Fire Barrier Packing Material PM4” by 3M.
 - b. Optional Product: “Type SAF” by Thermafiber or similar products specifically named as components in laboratory-approved designs.

L. Perimeter Fire Containment: Specified in Section 078400 “Firestopping.”

2.4 THROUGH PENETRATION FIRESTOP SYSTEMS

A. General:

1. The schedules below identify requirements for acceptable Through Penetration Firestop Systems based on barrier type, fire-resistive rating, and penetrant type. It is a guide. Ultimately each system must comply with Building Code and Fire Code as locally adopted and amended.
 2. Requirements for “single-membrane” penetrations and Through Penetration Firestops are Identical. (Unless otherwise noted, penetrants which pass through a single membrane, shall be treated the same as if it passed through the entire fire-resistive assembly.)
 3. Select each Firestop System based on actual field conditions, including penetration type, shape, size(s), quantities and physical position within opening.
 4. Refer to Plans for indication of the required ratings of Fire-resistive wall, floor, and roof assemblies.
 5. Indicated ratings are minimum and may be exceeded.
 6. Firestop Assemblies at Fire-Rated Walls:
 - a. The minimum Fire (F) Rating for Firestop assemblies in walls shall equal that of the wall, but not less than 1-HR.
 - b. The minimum Temperature (T) Rating of Firestop assemblies in walls may equal zero.
 - c. Smoke Barrier: In addition to (F) Rating, (L) Rating of maximum 5 CFM/SF.
 - d. Non-rated walls and Smoke-Partitions with no fire-resistive requirement: Assembly with (L) rating.
 7. Firestop Assemblies at Fire-Rated Floors and Roofs:
 - a. The minimum Fire (F) and Temperature (T) Ratings of Firestop assemblies used in floors (or roofs) shall equal the hourly rating of the floor (or roof) being penetrated, but not less than 1-HR.
 - 1) Exception 1: The T-rating may equal zero when the portion of the penetrant which is above or below the floor is contained within a wall.)
 - 2) Exception 2: Firestops are not required for floor penetrations that are within a 2- hour rated shaft enclosure.
- B. Joints at Exterior Curtain-Wall/Floor Intersections: Provide fire-resistive joint systems with rating determined by ASTM E 119 based on testing at a positive pressure differential of 0.01-inch wg (2.49 Pa) or ASTM E 2307.
- C. Voids in wall (no penetrating items):
1. Fill with approved Through Penetration Firestopping System.
 2. Contractors Option: Patch void in wall with like construction.
- D. Penetrating Ducts with Dampers:
1. Utilize only firestop materials which are included in the damper’s classification.
 2. Do not install Firestop Systems that might hamper the performance of fire dampers.
- E. Cable Trays and similar devices:
1. Openings within walls and floors designed to accommodate voice, data and video cabling shall be provided with re-enterable products (e.g. Firestop Pillows) specifically designed for removal and re-installation.
- F. Electrical and Electrical Devices recessed in to face of rated walls:
1. Items included: Switches, receptacles, J-boxes, medical gas outlets, and similar items recessed in to the face(s) of fire rated walls.

2. Where such devices are placed in approved manner or maintain continuity of rated barrier with wall cavity surrounding the recessed item or on opposite sides of wall, and are less than 24 IN apart measured horizontally: Install Intumescent Pads over back of devices in approved manner.

2.5 FIRE-RESISTIVE JOINT ASSEMBLIES – GENERAL

A. General:

1. Where joint will be exposed to the elements, fire-resistive joint sealant must be approved by manufacturer for use in exterior applications and shall comply with ASTM-C920.

B. Head-of-Wall Assemblies:

1. General:

- a. Use at top of fire-rated and smoke-barrier walls and partitions where they abut floor and roof structures above.
- b. Select systems with “D” designation (rated for dynamic movement capability.)
- c. Select systems that can accommodate deflection of structure above.
- d. Maximum Leakage for Fire-resistive Joints in Smoke Barriers: 5 CFM or less per linear foot as tested in accordance with UL 2079.
- e. Sound-control walls and Smoke Partitions which are not stipulated to include fire-resistance rating. Seal with Acoustical Sealant, specified in Section 092900 “Gypsum Drywall.”

2. Minimum F- and T-ratings:

- a. The minimum Fire (F) Rating for Firestop assemblies in walls shall equal that of the wall, but not less than 1-HR.
- b. The minimum Temperature (T) Rating of Firestop assemblies in walls may equal zero.

3. Acceptable Systems:

- a. Metal Stud and Drywall Walls: Select system from UL HW-D-0000 Series.

4. Concrete and Masonry Walls: Select system from UL HW-D-1000 Series.

Penetrant Description		Criteria	Metal Stud & GWB	CIP Concrete & Masonry
			UL U-400 Series	UL U-900 Series
No Penetrating Items		Single Penetrant	W-L-0000 Series ⁵	W-J-0000 Series ⁵
		Multiple Penetrants		
Metallic, Un-Insulated Pipe, Conduit, or Tubing ¹² (i.e. Multiple Penetrations)		Single Penetrant	W-L-1000 Series	C-AJ-1000 or W-J-1000 Series
		Multiple Penetrants	W-L-8000 Series ⁶	C-AJ-8000 or W-J-8000 Series ⁶
		Remarks	<Note 11>	<Note 9 & 11>
Non-Metallic, Un-Insulated Pipe, Conduit, or Tubing (i.e. PVC, CPVC, Glass)		Single Penetrant	W-L-2000 Series	C-AJ-2000 or W-J-2000 Series
		Multiple Penetrants	W-L-8000 Series ⁶	C-AJ-8000 or W-J-8000 Series ⁶
		Remarks	<Note 11>	<Note 11>
Electrical Cables		Single Penetrant	W-L-3000 Series	C-AJ-3000 or W-J-3000 Series
		Multiple Penetrants	W-L-8000 Series ⁶	C-AJ-8000 or W-J-8000 Series ⁶
Cable Trays w/cablings		Single Penetrant	W-L-4000 Series	C-AJ-4000 or W-J-4000 Series
		Multiple Penetrants		
Insulated Pipes (i.e. Copper, Glass, Steel, Iron, Plastic, Steel)	Systems operating between 32 to 122 DegF ¹	Single Penetrant	W-L-5000 Series	C-AJ-5000 or W-J-5000 Series
		Multiple Penetrants	W-L-8000 Series ⁶	C-AJ-8000 or W-J-8000 Series ⁶
	Systems operating below 32 DegF or above 122 DegF ²	Single Penetrant	W-L-5000 Series	C-AJ-5000 or W-J-5000 Series
		Multiple Penetrants	W-L-8000 Series ⁶	C-AJ-8000 or W-J-8000 Series ⁶
	Remarks	<Note 7>	<Note 7>	
Miscellaneous Electrical Penetrations (i.e. Bus Ducts)		Single Penetrant	W-L-6000 Series	C-AJ-6000 or W-J-6000 Series
		Multiple Penetrants	N/A	
Metal Duct ³		Single Penetrant	W-L-7000 Series	C-AJ-7000 or W-J-7000 Series
		Multiple Penetrants	N/A	N/A
Electrical Boxes		Single Penetrant	CEYY or CLIV Series	CEYY Series
		Multiple Penetrants	N/A	N/A
		Remarks	<Notes 10 & 11>	<Notes 9>
Other Recessed Devices ⁴		Single Penetrant	W-L-7000 Series ⁸	<Note 8>
		Multiple Penetrants		

Guide to Through Penetration Firestop Systems - FLOORS AND ROOFS					
Penetrant Description		Criteria	Framed Structure	Cast-in-Place Concrete (Maximum thickness less than or equal to 5 IN)	Cast-in-Place Concrete (Min thickness > 5 IN)
No Penetrating Items		Single Penetrant	<F-C-0000, Note 5>	C-AJ-0000 or F-A-0000 Series ⁵	C-BJ-0000 Series ⁵
		Multiple Penetrants			
Metallic, Un-Insulated Pipe, Conduit, or Tubing ¹² (i.e. Copper, Iron, Steel)		Single Penetrant	F-C-1000 Series	C-AJ-1000 or F-A-1000 Series	C-BJ-1000 or F-B-1000 Series
		Multiple Penetrants	F-C-8000 Series ⁶	C-AJ-8000 or F-A-8000 Series ⁶	C-BJ-8000 or F-B-8000 Series ⁶
		Remarks	--	<Note 9>	<Note 9>
Non-Metallic, Un-Insulated Pipe, Conduit, or Tubing (i.e. PVC, CPVC, Glass)		Single Penetrant	F-C-2000 Series	C-AJ-2000 or F-A-2000 Series	C-BJ-2000 or F-B-2000 Series
		Multiple Penetrants	F-C-8000 Series ⁶	C-AJ-8000 or F-A-8000 Series	C-BJ-8000 or F-B-8000 Series ⁶
Electrical Cables		Single Penetrant	F-C-3000 Series	C-AJ-3000 or F-A-3000 Series	C-BJ-3000 or F-B-3000 Series
		Multiple Penetrants	F-C-8000 Series ⁶	C-AJ-8000 or F-A-8000 Series	C-BJ-8000 or F-B-8000 Series ⁶
Cable Trays w/cabling		Single Penetrant	N/A	C-AJ-4000 or F-A-4000 Series	C-BJ-4000 or F-B-4000 Series
		Multiple Penetrants			
Insulated Pipes (i.e. Copper, Glass, Steel, Iron, Plastic, Steel)	Systems operating between 32 to 122 DegF ¹	Single Penetrant	F-C-5000 Series	C-AJ-5000 or F-A-5000 Series	C-BJ-5000 or F-B-5000 Series
		Multiple Penetrants	F-C-8000 Series ⁶	C-AJ-8000 or F-A-8000 Series	C-BJ-8000 or F-B-8000 Series ⁶
	Systems operating below 32 DegF or above 122 DegF ²	Single Penetrant	F-C-5000 Series	C-AJ-5000 or F-A-5000 Series	C-BJ-5000 or F-B-5000 Series
		Multiple Penetrants	F-C-8000 Series ⁶	C-AJ-8000 or F-A-8000 Series ⁶	C-BJ-8000 or F-B-8000 Series ⁶
	Remarks	<Note 7>	<Note 7>	<Note 7>	
Miscellaneous Electrical Penetrations (i.e. Bus Ducts)		Single Penetrant	N/A	C-AJ-6000 Series	C-BJ-6000 Series
		Multiple Penetrants			
Metal Duct ³		Single Penetrant	F-C-7000 Series	C-AJ-7000 or F-A-Series	C-BJ-7000 Series or F-B-7000 Series
		Multiple Penetrants	N/A	N/A	N/A
Electrical Boxes		Single Penetrant	CEYY Series	CEYY Series	CEYY Series
		Multiple Penetrants	N/A	N/A	N/A
Other Recessed Devices ⁴		Single Penetrant	<Note 8>	<Note 8>	--
		Multiple Penetrants			

PART 3 - EXECUTION

3.1 PREPARATION

- A. Examination of Conditions: Examine areas and conditions under which work is to be performed and identify conditions detrimental to proper or timely completion.
- B. Surfaces to which fire stop materials will be applied shall be free of dirt, grease, oil, scale, laitance, rust, release agents, water repellents, and any other substances that may inhibit optimum adhesion.
- C. Provide masking and temporary covering to prevent soiling of adjacent surfaces by firestopping materials.
- D. Do not proceed until unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. General:
 - 1. Install fire stop systems in accordance with “PERFORMANCE REQUIREMENTS” Article and in accordance with the conditions of testing and classification as specified in the published design.
 - 2. Penetrations through fire-resistive floor assemblies shall be sealed with a fire stop system which provides a minimum Class 1 W-rating as tested in accordance with UL 1479. Seal openings or voids made by penetrations to ensure an air and water resistant seal.
 - 3. Install per UL or other acceptable 3rd party testing agency and in accordance with manufacturer’s instructions, to maintain fire separations per UL listing.
 - 4. Protect materials from damage on surfaces subjected to traffic.
- B. Identification Labels.
 - 1. General:
 - a. Identify each Firestop Assembly as defined in “Quality Assurance.”
 - b. Do not locate ID labels/tags on finished surfaces or where they will be exposed to view by public occupants.

3.3 FIELD QUALITY CONTROL

- A. Keep areas of work accessible until inspection by authorities having jurisdiction.
- B. Where deficiencies are found, repair or replace assemblies so they comply with requirements.
- C. Construct mock-up on-site to include the typical through penetrations and fire-resistive joint applications for the project.

3.4 ADJUSTING AND CLEANING

- A. Remove equipment, materials and debris, leaving area in undamaged, clean condition.
- B. Clean surfaces adjacent to sealed openings to be free of excess materials and soiling as work progresses.
- C. Perform patching and repair of fire stopping systems damaged by other trades.

END OF SECTION 07 84 00

SECTION 081113 - HOLLOW METAL DOORS AND FRAMES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes:
 - 1. Interior standard steel doors and frames.
 - 2. Exterior standard steel doors and frames.
- B. Related Requirements:
 - 1. Section 087100 "Door Hardware" for door hardware for hollow-metal doors.

1.3 DEFINITIONS

- A. Minimum Thickness: Minimum thickness of base metal without coatings according to NAAMM-HMMA 803 or ANSI/SDI A250.8.

1.4 COORDINATION

- A. Coordinate anchorage installation for hollow-metal frames. Furnish setting drawings, templates, and directions for installing anchorages, including sleeves, concrete inserts, anchor bolts, and items with integral anchors. Deliver such items to Project site in time for installation.
- B. Coordinate requirements for installation of door hardware, electrified door hardware, and access control and security systems.

1.5 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

1.6 ACTION SUBMITTALS

- A. Product Data: For each type of product.

1.7 CLOSEOUT SUBMITTALS

- A. Record Documents: For fire-rated doors, list of door numbers and applicable room name and number to which door accesses.

1.8 DELIVERY, STORAGE, AND HANDLING

- A. Deliver hollow-metal doors and frames palletized, packaged, or crated to provide protection during transit and Project-site storage. Do not use nonvented plastic.
 - 1. Provide additional protection to prevent damage to factory-finished units.
- B. Deliver welded frames with two removable spreader bars across bottom of frames, tack welded to jambs and mullions.
- C. Store hollow-metal doors and frames vertically under cover at Project site with head up. Place on minimum 4-inch-high wood blocking. Provide minimum 1/4-inch space between each stacked door to permit air circulation.

1.9 PERFORMANCE REQUIREMENTS

- A. Fire-Rated Door Assemblies: Assemblies complying with NFPA 80 that are listed and labeled by a qualified testing agency acceptable to authorities having jurisdiction for fire-protection ratings indicated on Drawings, based on testing at positive pressure according to NFPA 252 or UL 10C.
 - 1. Smoke- and Draft-Control Door Assemblies: Listed and labeled for smoke and draft control by a qualified testing agency acceptable to authorities having jurisdiction, based on testing according to UL 1784 and installed in compliance with NFPA 105.

1.10 INTERIOR STANDARD STEEL DOORS AND FRAMES

- A. Construct hollow-metal doors and frames to comply with standards indicated for materials, fabrication, hardware locations, hardware reinforcement, tolerances, and clearances, and as specified.
- B. Standard-Duty Doors and Frames: ANSI/SDI A250.8, Level 1; ANSI/SDI A250.4, Level C. At locations indicated in the Door and Frame Schedule.
 - 1. Doors:
 - a. Type: As indicated in the Door and Frame Schedule.
 - b. Thickness: 1-3/4 inches.
 - c. Fire-Rated Core: Manufacturer's standard core for fire-rated doors.
 - 2. Frames:
 - a. Materials: steel sheet, minimum thickness of 0.042 inch.
 - b. Frames: Fabricated from same thickness material as adjacent door frame.
 - 3. Exposed Finish: Prime.

1.11 EXTERIOR STANDARD STEEL DOORS AND FRAMES

- A. Construct hollow-metal doors and frames to comply with standards indicated for materials, fabrication, hardware locations, hardware reinforcement, tolerances, and clearances, and as specified.
- B. Heavy-Duty Doors and Frames: ANSI/SDI A250.8, Level 2; ANSI/SDI A250.4, Level B. At exterior doors.
 - 1. Doors:

- a. Type: As indicated in the Door and Frame Schedule.
 - b. Thickness: 1-3/4 inches.
 - c. Face: Metallic-coated steel sheet, minimum thickness of 0.042 inch, with minimum A40 coating.
 - d. Edge Construction: Model 1, Full Flush.
 - e. Edge Bevel: Provide manufacturer's standard beveled or square edges.
 - f. Top Edge Closures: Close top edges of doors with flush closures of same material as face sheets. Seal joints against water penetration.
 - g. Bottom Edges: Close bottom edges of doors with end closures or channels of same material as face sheets. Provide weep-hole openings in bottoms of exterior doors to permit moisture to escape.
 - h. Core: Manufacturer's standard.
 - i. Fire-Rated Core: Manufacturer's standard core for fire-rated doors.
2. Frames:
- a. Materials: Metallic-coated steel sheet, minimum thickness of 0.053 inch, with minimum A40 coating.

1.12 MATERIALS

- A. Cold-Rolled Steel Sheet: ASTM A1008/A1008M, Commercial Steel (CS), Type B; suitable for exposed applications.
- B. Hot-Rolled Steel Sheet: ASTM A1011/A1011M, Commercial Steel (CS), Type B; free of scale, pitting, or surface defects; pickled and oiled.
- C. Metallic-Coated Steel Sheet: ASTM A653/A653M, Commercial Steel (CS), Type B.
- D. Inserts, Bolts, and Fasteners: Hot-dip galvanized according to ASTM A153/A153M.
- E. Power-Actuated Fasteners in Concrete: Fastener system of type suitable for application indicated, fabricated from corrosion-resistant materials, with clips or other accessory devices for attaching hollow-metal frames of type indicated.
- F. Mineral-Fiber Insulation: ASTM C665, Type I (blankets without membrane facing); consisting of fibers manufactured from slag or rock wool; with maximum flame-spread and smoke-developed indexes of 25 and 50, respectively; passing ASTM E136 for combustion characteristics.
- G. Glazing: Comply with requirements in Section 088000 "Glazing."

1.13 FABRICATION

- A. Door Astragals: Provide overlapping astragal on one leaf of pairs of doors where required by NFPA 80 for fire-performance rating or where indicated. Extend minimum 3/4 inch beyond edge of door on which astragal is mounted or as required to comply with published listing of qualified testing agency.

- B. Hollow-Metal Frames: Fabricate in one piece except where handling and shipping limitations require multiple sections. Where frames are fabricated in sections, provide alignment plates or angles at each joint, fabricated of metal of same or greater thickness as frames.
 - 1. Frames: Provide closed tubular members with no visible face seams or joints, fabricated from same material as door frame. Fasten members at crossings and to jambs by welding.
 - 2. Provide countersunk, flat- or oval-head exposed screws and bolts for exposed fasteners unless otherwise indicated.
 - 3. Door Silencers: Except on weather-stripped frames, drill stops to receive door silencers as follows. Keep holes clear during construction.
 - a. Single-Door Frames: Drill stop in strike jamb to receive three door silencers.
 - b. Double-Door Frames: Drill stop in head jamb to receive two door silencers.
 - 4. Terminated Stops (Hospital Stops): Terminate stops above finish floor with a-degree angle cut, and close open end of stop with steel sheet closure. Cover opening in extension of frame with welded-steel filler plate, with welds ground smooth and flush with frame.
- C. Hardware Preparation: Factory prepare hollow-metal doors and frames to receive templated mortised hardware, and electrical wiring; include cutouts, reinforcement, mortising, drilling, and tapping according to ANSI/SDI A250.6, the Door Hardware Schedule, and templates.
 - 1. Reinforce doors and frames to receive nontemplated, mortised, and surface-mounted door hardware.
 - 2. Comply with BHMA A156.115 for preparing hollow-metal doors and frames for hardware.

1.14 STEEL FINISHES

- A. Prime Finish: Clean, pretreat, and apply manufacturer's standard primer.
 - 1. Shop Primer: Manufacturer's standard, fast-curing, lead- and chromate-free primer complying with ANSI/SDI A250.10; recommended by primer manufacturer for substrate; compatible with substrate and field-applied coatings despite prolonged exposure.

1.15 LOUVERS

- A. Provide louvers for interior doors, where indicated, which comply with SDI 111, with blades or baffles formed of 0.020-inch- thick, cold-rolled steel sheet set into 0.032-inch- thick steel frame.
 - 1. Sightproof Louver: Stationary louvers constructed with inverted-V or inverted-Y blades.

1.16 INSTALLATION

- A. Install hollow-metal doors and frames plumb, rigid, properly aligned, and securely fastened in place. Comply with approved Shop Drawings and with manufacturer's written instructions.
- B. Hollow-Metal Frames: Comply with ANSI/SDI A250.11.
 - 1. Set frames accurately in position; plumbed, aligned, and braced securely until permanent anchors are set. After wall construction is complete, remove temporary braces without damage to completed Work.
 - a. Where frames are fabricated in sections, field splice at approved locations by welding face joint continuously; grind, fill, dress, and make splice smooth, flush, and invisible on exposed faces. Touch-up finishes.
 - b. Install frames with removable stops located on secure side of opening.

2. Fire-Rated Openings: Install frames according to NFPA 80.
 3. Floor Anchors: Secure with postinstalled expansion anchors.
 - a. Floor anchors may be set with power-actuated fasteners instead of postinstalled expansion anchors if so indicated and approved on Shop Drawings.
 4. Solidly pack mineral-fiber insulation inside frames.
 5. Masonry Walls: Coordinate installation of frames to allow for solidly filling space between frames and masonry with grout or mortar.
 6. In-Place Concrete or Masonry Construction: Secure frames in place with postinstalled expansion anchors. Countersink anchors, and fill and make smooth, flush, and invisible on exposed faces.
 7. Installation Tolerances: Adjust hollow-metal frames to the following tolerances:
 - a. Squareness: Plus or minus 1/16 inch, measured at door rabbet on a line 90 degrees from jamb perpendicular to frame head.
 - b. Alignment: Plus or minus 1/16 inch, measured at jambs on a horizontal line parallel to plane of wall.
 - c. Twist: Plus or minus 1/16 inch, measured at opposite face corners of jambs on parallel lines, and perpendicular to plane of wall.
 - d. Plumbness: Plus or minus 1/16 inch, measured at jambs at floor.
- C. Hollow-Metal Doors: Fit and adjust hollow-metal doors accurately in frames, within clearances specified below.
1. Non-Fire-Rated Steel Doors: Comply with ANSI/SDI A250.8.
 2. Fire-Rated Doors: Install doors with clearances according to NFPA 80.
 3. Smoke-Control Doors: Install doors according to NFPA 105.
- D. Glazing: Comply with installation requirements in Section 088000 "Glazing" and with hollow-metal manufacturer's written instructions.

1.17 REPAIR

- A. Prime-Coat Touchup: Immediately after erection, sand smooth rusted or damaged areas of prime coat and apply touchup of compatible air-drying, rust-inhibitive primer.
- B. Metallic-Coated Surface Touchup: Clean abraded areas and repair with galvanizing repair paint according to manufacturer's written instructions.
- C. Factory-Finish Touchup: Clean abraded areas and repair with same material used for factory finish according to manufacturer's written instructions.
- D. Touchup Painting: Cleaning and touchup painting of abraded areas of paint are specified in painting Sections.

END OF SECTION 081113

SECTION 087100 - FINISH HARDWARE

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes: Provide all items of finish hardware required to adequately trim, hang, and operate all doors, as is hereinafter specified and listed in the Hardware Schedule.
 - 1. Provide hardware for doors and frames of unusual profile or shape or other special conditions.
 - 2. Provide all necessary standard and special fasteners, screws, bolts, expansion shields or anchors to properly secure hardware to its intended door, frame, or other surface.

1.2 REFERENCES

- A. The following reference standards and model code documents shall be used in estimating and detailing door hardware, and shall be considered as a standard of quality, function, and performance, as applicable:
 - 1. I.B.C. International Building Code (current year adopted).
 - 2. NFPA-80 Fire Doors & Windows (current year adopted).
 - 3. NFPA-101 Life Safety Code (current year adopted).
 - 4. NFPA-105 Smoke Control Door Assembly. (current year adopted)
 - 5. ANSI-117.1 1992 Edition Providing Accessibility and Usability for Physically Handicapped People.
 - 6. A.D.A.A.G Americans with Disabilities Act Accessibility Guidelines.
 - 7. T.A.S. Texas Accessibility Standards.

1.3 ACTION SUBMITTALS

- A. General: Submit the following in accordance with Section 01 33 00.
- B. Product Data: Provide a catalog cut sheet, clearly marked and identified, illustrating and describing each product included in the Hardware Schedule.
 - 1. Include construction and installation details, material descriptions, dimensions of individual components and profiles, and finishes.
 - 2. Formulate catalog cut sheets into sets and include a set with each copy of the Hardware Schedule submitted.
- C. Door Hardware Schedule: Prepared by or under the supervision of Architectural Hardware Consultant, detailing fabrication and assembly of door hardware, as well as procedures and diagrams. Coordinate the final Door Hardware Schedule with doors, frames, and related work to ensure proper size, thickness, hand, function, and finish of door hardware.
 - 1. Format: Comply with scheduling sequence and vertical format in DHI's "Sequence and Format for the Hardware Schedule."
 - 2. Organization: Organize the Door Hardware Schedule into door hardware sets indicating complete designations of every item required for each door or opening.
 - 3. Content: Include the following information:

- a. Type, style, function, size, label, hand, and finish of each door hardware item.
 - b. Complete designations of every item required for each door or opening including name and manufacturer.
 - c. Fastenings and other pertinent information.
 - d. Location of each door hardware set, cross-referenced to Drawings, both on floor plans and in door and frame schedule. Use same scheduling sequence and format and use same door numbers and hardware set numbers as in the Contract Documents.
 - e. Explanation of abbreviations, symbols, and codes contained in schedule.
 - f. Mounting locations for door hardware.
 - g. Door and frame sizes and materials.
 - h. Description of each electrified door hardware function, including location, sequence of operation, and interface with other building control systems.
4. Submittal Sequence: Submit the final Door Hardware Schedule at earliest possible date, particularly where approval of the Door Hardware Schedule must precede fabrication of other Work that is critical in the Project construction schedule. Include Product Data, Samples, Shop Drawings of other work affected by door hardware, and other information essential to the coordinated review of the Door Hardware Schedule.
- D. Samples for Verification: If so requested by the Architect, provide a sample of any product or item requested, properly marked and tagged, for the opening for which it is intended.
- E. Keying: Provide a keying schedule, listing the levels of keying, (GGMK, GKD, MKD or KA) as well as an explanation of the key system's function, the key symbols used and the numbers of the doors controlled. Provide in conjunction with the Door Index/Keying Schedule (which lists the door number, schedule heading, lock type and individual key symbol and remarks or special instructions) mentioned in above. Project shall be Masterkeyed and/or Grand Masterkeyed and provide two (2) keys per lockset or cylinder.

1.4 INFORMATIONAL SUBMITTALS

- A. Operation and Maintenance Data: For each type of door hardware to include in maintenance manuals. Provide latest, revised and updated schedule of finish hardware, complete with catalog cuts and keying schedule. In addition, furnish one (1) copy of maintenance and parts manuals for those items for which they are readily available and normally provided.
1. Submit in accordance with provisions of Section 01 78 23.

1.5 QUALITY ASSURANCE

- A. Substitutions: Request for substitutions for alternative hardware items will not be accepted on this Project unless specifically indicated. Specification indicates one (1) specified product, listed hereinafter in the Hardware Schedule, and two (2) acceptable alternative manufacturers for that product. If any specified product is listed as a "No Substitution" product, only that specified product shall be provided as indicated.
- B. Installer Qualifications: An experienced installer who has completed door hardware similar in material, design, and extent to that indicated for this Project and whose work has resulted in construction with a record of successful in-service performance.

- C. **Supplier Qualifications:** Door hardware supplier with warehousing facilities in Project's vicinity and who is or employs a qualified Architectural Hardware Consultant, available during the course of the Work to consult with Contractor, Architect, and Owner about door hardware and keying.
 - 1. The hardware supplier shall be engaged regularly in the furnishing, delivery and servicing of contract builder's hardware and must be experienced and knowledgeable in all phases of estimating, detailing, scheduling, masterkeying, shipping and installation practices.
 - 2. When electro-mechanical or electronic hardware is supplied, a qualified individual with a minimum five- (5) year's experience shall be available for assistance.
- D. **Architectural Hardware Consultant Qualifications:** A person who is currently certified by the Door and Hardware Institute as an Architectural Hardware Consultant and who is experienced in providing consulting services for door hardware installations that are comparable in material, design, and extent to that indicated for this Project.
- E. **Source Limitations:** Obtain each type and variety of door hardware from a single manufacturer, unless otherwise indicated.
- F. **Regulatory Requirements:** Comply with provisions of the following:
 - 1. Provide hardware that complies with Americans with Disabilities Act (ADA), "Accessibility Guidelines for Buildings and Facilities (ADAAG)," and ANSI A117.1.
- G. **Fire-Rated Door Assemblies:** Provide door hardware for assemblies complying with NFPA 80 that are listed and labeled by a testing and inspecting agency acceptable to authorities having jurisdiction, for fire ratings indicated, based on testing according to NFPA 252.
- H. **Electrified Door Hardware:** Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- I. **Keying Conference:** Conduct conference at Project site to comply with requirements in Division 01 Section "Project Management and Coordination." Incorporate keying conference decisions into final keying schedule after reviewing door hardware keying system including, but not limited to, the following:
 - 1. Function of building, flow of traffic, purpose of each area, degree of security required, and plans for future expansion.
 - 2. Preliminary key system schematic diagram.
 - 3. Requirements for key control system.
 - 4. Address for delivery of keys.
 - 5. Location of Key Cabinet.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. **Marking and Packaging:** All items of hardware shall be delivered to the site in manufacturer's original cartons or boxes. Each item of hardware shall be marked with the abbreviation set forth on the Shop Drawings to ensure that the product reaches its installation destination without needing specific hardware product number knowledge.
- B. **Inventory door hardware on receipt and provide secure lock-up for door hardware delivered to Project site.**

- C. Tag each item or package separately with identification related to the final Door Hardware Schedule, and include basic installation instructions with each item or package.

1.7 COORDINATION

- A. Templates: Obtain and distribute to the parties involved templates for doors, frames, and other work specified to be factory prepared for installing door hardware. Check Shop Drawings of other work to confirm that adequate provisions are made for locating and installing door hardware to comply with indicated requirements.

1.8 MAINTENANCE

- A. Maintenance Tools and Instructions: Furnish a complete set of specialized tools and maintenance instructions as needed for Owner's continued adjustment, maintenance, and removal and replacement of door hardware.
- B. Maintenance Service: If there are any products listed hereinafter that normally require a maintenance or service contract, provide the Owner and Architect with details and costs of standard maintenance or service contract.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Designations: Requirements for design, grade, function, finish, size, and other distinctive qualities of each type of door hardware are indicated in Part 3 "Hardware Schedule" Article. Products are identified by using door hardware designations, as follows:
 - 1. Named Manufacturers' Products: Manufacturer and product designation are listed for each door hardware type required for the purpose of establishing minimum requirements. Manufacturers' names are abbreviated in Part 3 "Hardware Schedule" Article.
- B. Product manufacturers listed with an asterisk (*) denote the specified manufacturers listed in the Hardware Schedule. The remaining two (2) listed manufacturers will be acceptable substitutions. If only one manufacturer is listed this shall be considered a "No Substitution" specification as set forth in "Quality Assurance" Article, for that particular item.

2.2 MATERIALS

- A. Screws and Fasteners: Provide all screws and fasteners of the proper size and type to properly anchor or attach the item of hardware scheduled. Provide all fasteners with Phillips heads, unless security type screws (spanner-head or torx-head) are hereinafter specified.
- B. Hinges: Provide as follows:
 - 1. On doors to exterior openings and main corridor doors, and other doors of high frequency use, provide a continuous, gear type hinge of appropriate weight.
 - 2. Where regular ball bearing hinges are listed for other doors, provide one hinge for each 30-inch of door height.

3. The width of the hinges shall be sufficient to clear all trim that is mounted to the doorframe.
4. Acceptable Manufacturers:
 - a. Hager* No Substitution
- C. Locks: All locks shall incorporate a six pin tumbler system and be keyed to a existing GRANDMASTER SYSTEM as not to breach security of system in place. Keying system must be guaranteed of no duplication of existing change keys, master keys or grandmaster keys located in this Project. All keying shall be coordinated with Owner. Locks shall be Grade 1 mortise and/or cylindrical as hereinafter listed in the Hardware Schedule.
 1. Acceptable Manufacturers:
 - a. Schlage* No Substitution
- D. Lock Trim: Cylindrical/mortise locks are to be furnished with lever handle trim, as is hereinafter listed in the Hardware Schedule.
- E. Flush Bolts: Manual flush bolts to have 12-inch rods for doors 7'-6". Doors over 7'-6" high shall have bolts with top rods of 18 inch or 24 inch to allow ease of access to bolt lever. Furnish dust proof strikes for all bottom bolts.
 1. Acceptable Manufacturers:
 - a. Ives* No Substitution
- F. Exit Devices: Exit Devices shall be rim, mortise or vertical rod type as called for in the Hardware Schedule. Devices shall be of the touch-pad type as is hereinafter specified in the Hardware Schedule. Exit devices shall be constructed to allow cylinder to be removed and rekeyed without removing the device from the door either by removable core cylinders or construction of exit device. Exit devices shall be constructed to allow the conversion from one function to another simply within lock stile case and selecting proper outside trim as specified hereinafter in the Hardware Schedule. Devices shall be furnished with outside trim lever handles matching locks.
 1. Acceptable Manufacturers:
 - a. Von Duprin* No Substitution
- G. Door Closers: Door closers shall be of cast iron and rectangular design, furnished with a full cover. Provide complete with backcheck, delayed action and hold-open as indicated. Closers shall be mounted out of the line of sight wherever possible (i.e., room side of corridor doors, etc.) with parallel arm mounting on out-swinging doors. Mount closers to jamb or on brackets and/or drop plates, where special conditions require.
 1. Acceptable Manufacturers:
 - a. LCN* No Substitution
- H. Push Plates: Push plates are to be .050 brass, bronze or stainless steel with four (4) beveled edges, drilled and countersunk for screws, as is hereinafter specified in the Hardware Schedule.
 1. Acceptable Manufacturers:
 - a. Ives* No Substitution
- I. Door Pulls: Door pulls shall be ADA compliant with a 2 1/2 inch projection from back of pull to face of door. All door pulls shall be thru-bolted or back-to-back mounted.
 1. Acceptable Manufacturers:
 - a. Ives* No Substitution

b. Hager* No Substitution

- J. Protective Plates: Protective plates shall be mop (6”), kick (10”) or armor (34”) and shall be minimum .050 thick brass, bronze, or stainless steel, with three (3) beveled edges, drilled and countersunk for screws. Plates shall be mounted to avoid louvers and/or glass kits.
1. Acceptable Manufacturers:
 - a. Ives* No Substitution
- K. Door Stops and Holders: Where a door strikes a wall at approximately 90 degrees, a suitable door stop shall be provided, either a wall bumper or floor stop. Where doors are undercut, provide floor stops with adequate height to properly stop the door. If door would not otherwise strike a wall, an overhead stop shall be provided. In-wall blocking for wall bumpers at stud walls shall be provided in accordance with Section 06 10 53. Provide reinforcing in frame and door for overhead stops.
1. Acceptable Manufacturers:
 - a. Glynn-Johnson* No Substitution
- L. Thresholds and Weatherstrip: Weatherstripping to have aluminum housing, specified insert, and elongated mounting holes. Door sweeps shall be surface mounted, of aluminum/stainless steel housing with specified insert. Overhead drip caps to be of aluminum, have a 2 1/2-inch projection and be 4 inches wider than the door opening. Thresholds shall be of saddle type with no more than 1/2 inch rise. Weatherstripping and smoke seals shall be surface-mounted on doorstop and have 1/4" adjustment slots.
1. Acceptable Manufacturers:
 - a. Zero* No Substitution
- M. Smoke Gasket: Smoke gasket shall comply with door and frame manufacturers for positive pressure tests for fire and smoke. (UBC 7-2, Parts 1 & 2/UL10C).
1. Acceptable Manufacturers:
 - a. Zero*

2.3 FINISHES

- A. Hardware finishes shall match and be maintained to BHMA symbols, as indicated in the Hardware Schedule. Strict adherence to base metals and finish is required.
- B. Provide Anti-Microbial finish for all lever sets, electronic lever sets, exit device trim and door push/pulls.
- C. Protect mechanical finishes on exposed surfaces from damage by applying a strippable, temporary protective covering before shipping.

2.4 KEYING

- A. Keying of locks and cylinders throughout project shall be scheduled through a key meeting with Architect, Owner, and hardware supplier. Key schedule shall be prepared and submitted to the Owner for approval. Copies of final key schedule with the bitting instructions shall be submitted as part of the Project Record Documents.

2.5 KEY CONTROL

- A. Provide key cabinet(s) manufactured by of sufficient capacity to handle all keys, plus 50 percent expansion. Provide key control cross-reference chart and accountability (sign-out) tags.
 - 1. Acceptable Manufacturers:
 - a. Telkee*
 - b. Lund.
 - c. Key Control Systems.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine doors and frames, with Installer present, for compliance with requirements for installation tolerances, labeled fire door assembly construction, wall and floor construction, and other conditions affecting performance.
- B. Examine roughing-in for electrical power systems to verify actual locations of wiring connections before electrified door hardware installation.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Steel Doors and Frames: Comply with DHI A115 series.
 - 1. Surface-Applied Door Hardware: Drill and tap doors and frames according to SDI 107 or ANSI A250.6, whichever is more stringent.
- B. Wood Doors: Comply with DHI A115-W series.

3.3 INSTALLATION

- A. Installation shall be by a qualified installer with a minimum five (5) year's experience in the installation of commercial grade hardware. Manufacturer's instructions shall dictate templating and installation.
- B. Mounting Heights: Mount door hardware units at heights indicated in following applicable publications, unless specifically indicated or required to comply with governing regulations:
 - 1. Standard Steel Doors and Frames: DHI's "Recommended Locations for Architectural Hardware for Standard Steel Doors and Frames."
 - 2. Wood Doors: DHI WDHS.3, "Recommended Locations for Architectural Hardware for Wood Flush Doors."
- C. Install each door hardware item to comply with manufacturer's written instructions. Where cutting and fitting are required to install door hardware onto or into surfaces that are later to be painted or finished in another way, coordinate removal, storage, and reinstallation of surface protective trim units with finishing work specified in Division 09 Sections. Do not install surface-mounted items until finishes have been completed on substrates involved.

1. Set units level, plumb, and true to line and location. Adjust and reinforce attachment substrates as necessary for proper installation and operation.
 2. Drill and countersink units that are not factory prepared for anchorage fasteners. Space fasteners and anchors according to industry standards.
- D. Key Control System: Place keys on markers and hooks in key control system cabinet, as determined by final keying schedule.
- E. Boxed Power Supplies: Locate power supplies as indicated or, if not indicated, above accessible ceilings. Verify location with Architect prior to installation.
- F. Thresholds: Set thresholds for exterior and acoustical doors in full bed of sealant complying with requirements specified in Division 07 Section "Joint Sealants."

3.4 FIELD QUALITY CONTROL

- A. Perform final inspection with hardware installer and hardware supplier present to ensure correct installation and operation, and check for any damaged or defective items. Observe and inspect that all hardware has been installed to its correct destination in proper working order.
- B. Independent Architectural Hardware Consultant: Owner reserves the right to engage a qualified independent Architectural Hardware Consultant to perform a separate independent inspection and to prepare an inspection report.

3.5 ADJUSTING

- A. Initial Adjustment: Adjust and check each operating item of door hardware and each door to ensure proper operation or function of every unit. Replace units that cannot be adjusted to operate as intended.
1. Adjust door control devices to compensate for final operation of heating and ventilating equipment and to comply with referenced accessibility requirements.
 2. Electric Strikes: Adjust horizontal and vertical alignment of keeper to properly engage lock bolt.
 3. Door Closers: Adjust sweep period so that, from an open position of 70 degrees, the door will take at least 3 seconds to move to a point 3 inches(75 mm) from the latch, measured to the leading edge of the door.
- B. At completion of the installation and prior to Substantial Completion, make final adjustments to door closures and other items of hardware. Leave all hardware clean and fully operable. Should any item be found to be defective, it shall be repaired or replaced as directed.
- C. Occupancy Adjustment: Approximately three months after date of Substantial Completion, Installer's Architectural Hardware Consultant shall examine and readjust, including adjusting operating forces, each item of door hardware as necessary to ensure function of doors, door hardware, and electrified door hardware.

3.6 CLEANING AND PROTECTION

- A. Clean adjacent surfaces soiled by door hardware installation.

- B. Clean operating items as necessary to restore proper function and finish.
- C. Provide final protection and maintain conditions that ensure door hardware is without damage or deterioration at time of Substantial Completion.

3.7 DEMONSTRATION

- A. Engage a factory-authorized service representative to train Owner's maintenance personnel to adjust, operate, and maintain door hardware and door hardware finishes. Refer to Division 01 Section "Demonstration and Training."

3.8 HARDWARE SCHEDULE

- A. All products below to be Buy America compliant. Confirm with CRL and Hager that specified product is Buy America compliant and have proper documentation.

OPT0183055

HARDWARE GROUP NO. 103S

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	ENTRANCE LOCK	ND53TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 201CL

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN

-CLOSER ONLY REQUIRED. EXISTING DOOR REMAINING.

HARDWARE GROUP NO. 203

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	STOREROOM LOCK	ND80TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. 203S

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	STOREROOM LOCK	ND80TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 207

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	STOREROOM LOCK	ND80TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040 BAA REG OR PA AS REQ.	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 210

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
6	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	SET	CONST LATCHING BOLT	FB51P/FB61P AS REQ BAA	630	IVE
1	EA	STOREROOM LOCK	ND80TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA SCUSH X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
2	EA	KICK PLATE	8400 10" X 1" LDW B-CS	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER
1	EA	MEETING STILE	326AA BAA (2 PCS - 1 SET) HEIGHT AS REQUIRED (OMIT @ NON-RATED DOORS)	AA	ZER

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. 216
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
6	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	SET	CONST LATCHING BOLT	FB51P/FB61P AS REQ BAA	630	IVE
1	EA	STOREROOM LOCK	ND80TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
2	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
2	EA	KICK PLATE	8400 10" X 1" LDW B-CS	630	IVE
1	EA	GASKETING	488S BAA PSA H & J (USE SILENCERS @ NON-RATED DOORS)	BK	ZER
1	EA	MEETING STILE	326AA BAA (2 PCS - 1 SET) HEIGHT AS REQUIRED (OMIT @ NON-RATED DOORS)	AA	ZER

HARDWARE GROUP NO. 303
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	PRIVACY LOCK	ND40S RHO BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 341
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	PRIVACY LOCK	ND40S RHO BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

-INDICATOR ON OUTSIDE OF DOOR.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. 401
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	PASSAGE SET	ND10S RHO BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 403
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	PASSAGE SET	ND10S RHO BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 407
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	PASSAGE SET	ND10S RHO BAA	626	SCH
1	EA	OH STOP	100S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 507
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	STOREROOM LOCK	ND80TD RHO BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040 BAA REG OR PA AS REQ.	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J (USE SILENCERS @ NON-RATED DOORS)	BK	ZER

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. 700CR
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
6	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" CONFIRM BAA	652	HAG
2	EA	FIRE EXIT HARDWARE	9947-L-F-LBR-17 (WDC @ WD) BAA LENGTH & HEIGHT AS REQ	626	VON
2	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE BAA	626	SCH
2	EA	FSIC CORE	23-030 BAA	626	SCH
2	EA	SURFACE CLOSER	4040XP BAA SCUSH X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
2	EA	KICK PLATE	8400 10" X 1" LDW B-CS	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER
1	EA	MEETING STILE	326AA BAA(2 PCS - 1 SET) HEIGHT AS REQUIRED	AA	ZER

HARDWARE GROUP NO. 701CR
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" CONFIRM BAA W/ MFR.	652	HAG
1	EA	FIRE EXIT HARDWARE	99-L-F-17 BAA LENGTH AS REQ	626	VON
1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	SURFACE CLOSER	4040XP BAA SCUSH X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

HARDWARE GROUP NO. 701X
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" CONFIRM BAA W/ MFR.	652	HAG
1	EA	PANIC HARDWARE	LD-99-L-17 BAA LENGTH AS REQ	626	VON
1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. 801
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	PUSH PLATE	8200 4" X 16" BAA	630	IVE
1	EA	PULL PLATE	8302 10" 4" X 16" BAA	630	IVE
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. C200C
EACH TO HAVE:

QTY	EA	DESCRIPTION	CATALOG NUMBER	FINISH	MFR
5	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	ELEC. HINGE	BB1279 4.5" X 4.5" ETW-8	652	HAG
1	SET	AUTO FLUSH BOLT	FB31P/FB41P AS REQ BAA	630	IVE
1	EA	EU STOREROOM LOCK	ND80TDEU RHO RX CON 12V/24V DC	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	COORDINATOR	COR -BAA X FL X MB X HW PREPS X LENGTH AS REQUIRED	628	IVE
2	EA	SURFACE CLOSER	4040XP BAA SCUSH X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
2	EA	KICK PLATE	8400 10" X 1" LDW B-CS	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER
1	EA	MEETING STILE	326AA BAA (2 PCS - 1 SET) HEIGHT AS REQUIRED (OMIT @ NON-RATED DOORS)	AA	ZER
2	EA	HARNES (1 IN DOOR & 1 IN FRAME)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	HARNES (TO POWER SUPPLY)	CON-6W - CONNECTION LEADS		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION 1		
2	EA	DOOR CONTACT	679-05 TYPE AS REQ (COORDINATE FINAL LOCATIONS WITH SECURITY PRIOR TO SUBMITTAL)	WHT	SCE
1	EA	POWER SUPPLY	POWER SUPPLY FOR CREDENTIAL READER BY ANOTHER SECTION		
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE PS WITH SECURITY CONTRACTOR PRIOR TO SUBMITTALS)	LGR	SCE

-INGRESS BY THE CARD READER OR KEY OVERRIDE.
-FREE EGRESS BY LEVER.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. C201
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
2	EA	HINGE	BB1279 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	ELEC. HINGE	BB1279 4.5" X 4.5" ETW-8	652	HAG
1	EA	EU STOREROOM LOCK	ND80TDEU RHO RX CON 12V/24V DC	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER
2	EA	HARNESS (1 IN DOOR & 1 IN FRAME)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	HARNESS (TO POWER SUPPLY)	CON-6W - CONNECTION LEADS		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION 1		
1	EA	DOOR CONTACT	679-05 TYPE AS REQ (COORDINATE FINAL LOCATIONS WITH SECURITY PRIOR TO SUBMITTAL)	WHT	SCE
1	EA	POWER SUPPLY	POWER SUPPLY FOR CREDENTIAL READER BY ANOTHER SECTION		
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE PS WITH SECURITY CONTRACTOR PRIOR TO SUBMITTALS)	LGR	SCE

-INGRESS BY THE CARD READER OR KEY OVERRIDE.

-FREE EGRESS BY LEVER.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. C701
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
2	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	ELEC. HINGE	BB1168 4.5" X 4.5" ETW-8 CONFIRM BAA W/MFR.	652	HAG
1	EA	ELEC PANIC HARDWARE	RX-99-L-M996-17-FSE-CON BAA(FAIL SECURE) LENGTH AS REQ	626	VON
1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	OH STOP	900S SERIES BAA X SIZE & MOUNTING AS REQ	630	GLY
1	EA	SURFACE CLOSER	4040XP BAA RW/PA X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER
2	EA	HARNESS (1 IN DOOR & 1 IN FRAME)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	HARNESS (TO POWER SUPPLY)	CON-6W - CONNECTION LEADS		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION 1		
1	EA	DOOR CONTACT	679-05 TYPE AS REQ (COORDINATE FINAL LOCATIONS WITH SECURITY PRIOR TO SUBMITTAL)	WHT	SCE
1	EA	POWER SUPPLY	POWER SUPPLY FOR CREDENTIAL READER BY ANOTHER SECTION		
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE PS WITH SECURITY CONTRACTOR PRIOR TO SUBMITTALS)	LGR	SCE

-INGRESS BY THE CARD READER OR KEY OVERRIDE.
-FREE EGRESS BY THE PUSH PAD.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. C701C
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
2	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" CONFIRM BAA W/MFR.	652	HAG
1	EA	ELEC. HINGE	BB1168 4.5" X 4.5" ETW-8 CONFIRM BAA W/MFR.	652	HAG
1	EA	ELEC PANIC HARDWARE	RX-99-L-M996-17-FSE-CON BAA(FAIL SECURE) LENGTH AS REQ	626	VON
1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	SURFACE CLOSER	4040XP BAA SCUSH X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	488S BAA PSA H & J	BK	ZER
2	EA	HARNESS (1 IN DOOR & 1 IN FRAME)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	HARNESS (TO POWER SUPPLY)	CON-6W - CONNECTION LEADS		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION 1		
1	EA	DOOR CONTACT	679-05 TYPE AS REQ (COORDINATE FINAL LOCATIONS WITH SECURITY PRIOR TO SUBMITTAL)	WHT	SCE
1	EA	POWER SUPPLY	POWER SUPPLY FOR CREDENTIAL READER BY ANOTHER SECTION		
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE PS WITH SECURITY CONTRACTOR PRIOR TO SUBMITTALS)	LGR	SCE

-INGRESS BY THE CARD READER OR KEY OVERRIDE.
-FREE EGRESS BY THE PUSH PAD.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. C715
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	H. WGT. HINGE	BB1168 4.5" X 4.5" NRP CONFIRM BAA W/ MFR.	652	HAG
1	EA	POWER TRANSFER	EPT10-BAA- CON	689	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-99-NL-CON BAA LENGTH AS REQ	626	VON
1	EA	RIM CYLINDER	20-057 ICX W/CONST. CORE BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	SURFACE CLOSER	4040XP BAA SCUSH X MTG BRKT, SPCR & PLATE AS REQ	689	LCN
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS BAA	630	IVE
1	EA	GASKETING	328AA BAA H & J	AA	ZER
1	EA	DOOR SWEEP	8198AA BAA LENGTH AS REQ	AA	ZER
1	EA	THRESHOLD	65A BAA LENGTH AS REQ	A	ZER
2	EA	HARNESS (1 IN DOOR & 1 IN FRAME)	ALLEGION CONNECT TYPE & LENGTH AS REQ		SCH
1	EA	HARNESS (TO POWER SUPPLY)	CON-6W - CONNECTION LEADS		SCH
1	EA	CREDENTIAL READER	CREDENTIAL READER BY ANOTHER SECTION 1		
1	EA	DOOR CONTACT	679-05 TYPE AS REQ (COORDINATE FINAL LOCATIONS WITH SECURITY PRIOR TO SUBMITTAL)	WHT	SCE
1	EA	POWER SUPPLY	POWER SUPPLY FOR CREDENTIAL READER BY ANOTHER SECTION		
1	EA	POWER SUPPLY	PS902 120/240 VAC (COORDINATE PS WITH SECURITY CONTRACTOR PRIOR TO SUBMITTALS)	LGR	SCE

- INGRESS BY THE CARD READER OR KEY OVERRIDE.
- FREE EGRESS BY THE PUSH PAD.
- STEEL CONTRACTOR TO PROVIDE OVERHEAD RAIN DRIP AS REQ.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. G811CC
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	PIVOT SET	7255 SET BAA	626	IVE
1	EA	DOOR PULL	#20 (18 CTC) BTB MOUNTING GLASS DOOR- CONFIRM BAA W/ MFR. PUSH/PULL SET	630	HAG
1	EA	CONCEALED CLOSER	6031 BAA BUMP WMS -REQUIRES MINIMUM 1-3/4" HEADER	689	LCN
1	EA	APPLIED STOP	BY FRAME MFR.		
1	SET	SEAL	PERIMETER SEAL BY FRAME MFR.		

- TRACK BUMPER TO ASSIST BACKCHECK
- NO AUXILIARY DEAD STOP SCHEDULED.
- NON LOCKING.
- GLASS DOOR TO HAVE TAPERED TOP/BOTTOM RAILS.
- MINIMUM 1-3/4" HEADER REQUIRED FOR CONCEALED CLOSER.
- COORDINATE ALL HARDWARE WITH GLASS DOOR MFR. PRIOR TO SUBMITTALS.

HARDWARE GROUP NO. G811CCNS
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	PIVOT SET	7255 SET BAA	626	IVE
1	EA	DOOR PULL	#20 (18 CTC) BTB MOUNTING GLASS DOOR- CONFIRM BAA W/ MFR. PUSH/PULL SET	630	HAG
1	EA	CONCEALED CLOSER	6031 BAA BUMP WMS -REQUIRES MINIMUM 1-3/4" HEADER	689	LCN
1	EA	APPLIED STOP	BY FRAME MFR.		
1	SET	SEAL	PERIMETER SEAL BY FRAME MFR.		

- TRACK BUMPER TO ASSIST BACKCHECK
- NO AUXILIARY DEAD STOP SCHEDULED.
- NON LOCKING.
- GLASS DOOR TO HAVE TAPERED TOP/BOTTOM RAILS.
- MINIMUM 1-3/4" HEADER REQUIRED FOR CONCEALED CLOSER.
- COORDINATE ALL HARDWARE WITH GLASS DOOR MFR. PRIOR TO SUBMITTALS.

TRINITY METRO - HRP FACILITY
COUNTING ROOM REMODEL
FORT WORTH, TEXAS

TECHNICAL SPECIFICATIONS

HARDWARE GROUP NO. G871CCL
EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	PIVOT SET	7255 SET BAA	626	IVE
1	EA	PUSH/PULL LATCH	LLPUA48BS X STRIKE AS REQ. (LOCKING LADDER PULL SET) -LOCKING DEADBOLT THROWS INTO HEADER. CONFIRM BAA W/ MFR.	626	CRL
1	EA	MORTISE CYLINDER	20-061 ICX W/CONST. CORE BAA	626	SCH
1	EA	FSIC CORE	23-030 BAA	626	SCH
1	EA	CONCEALED CLOSER	6031 BAA BUMP WMS -REQUIRES MINIMUM 1-3/4" HEADER	689	LCN
1	EA	APPLIED STOP	BY FRAME MFR.		
1	SET	SEAL	PERIMETER SEAL BY FRAME MFR.		
1	EA	HARDWARE	REMAINDER OF HARDWARE BY DOOR MFG	FBO	UNK

- GLASS DOOR TO HAVE TAPERED TOP/BOTTOM RAILS.
- MINIMUM 1-3/4" HEADER REQUIRED FOR CONCEALED CLOSER.
- COORDINATE ALL HARDWARE WITH GLASS DOOR MFR. PRIOR TO SUBMITTALS.

END OF SECTION 087100

SECTION 092900 - GYPSUM BOARD

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Interior gypsum board.
 - 2. Tile backing panels.
- B. Related Requirements:
 - 1. Section 061600 "Sheathing" for gypsum sheathing for exterior walls.
 - 2. Section 079219 "Acoustical Joint Sealants" for acoustical joint sealants installed in gypsum board assemblies.
 - 3. Section 092216 "Non-Structural Metal Framing" for non-structural steel framing and suspension systems that support gypsum board panels.
 - 4. Section 093013 "Ceramic Tiling" for cementitious backer units installed as substrates for ceramic tile.

1.3 DELIVERY, STORAGE AND HANDLING

- A. Store materials inside under cover and keep them dry and protected against weather, condensation, direct sunlight, construction traffic, and other potential causes of damage. Stack panels flat and supported on risers on a flat platform to prevent sagging.

1.4 FIELD CONDITIONS

- A. Environmental Limitations: Comply with ASTM C840 requirements or gypsum board manufacturer's written instructions, whichever are more stringent.
- B. Do not install paper-faced gypsum panels until installation areas are enclosed and conditioned.
- C. Do not install panels that are wet, moisture damaged, and mold damaged.
 - 1. Indications that panels are wet or moisture damaged include, but are not limited to, discoloration, sagging, or irregular shape.
 - 2. Indications that panels are mold damaged include, but are not limited to, fuzzy or splotchy surface contamination and discoloration.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Fire-Resistance-Rated Assemblies: For fire-resistance-rated assemblies, provide materials and construction identical to those tested in assembly indicated according to ASTM E119 by an independent testing agency.
- B. STC-Rated Assemblies: For STC-rated assemblies, provide materials and construction identical to those tested in assembly indicated according to ASTM E90 and classified according to ASTM E413 by an independent testing agency.

2.2 GYPSUM BOARD, GENERAL

- A. Size: Provide maximum lengths and widths available that will minimize joints in each area and that correspond with support system indicated.

2.3 INTERIOR GYPSUM BOARD

- A. Gypsum Board, Type X: ASTM C1396/C1396M.
 - 1. Thickness: 5/8 inch.
 - 2. Long Edges: Tapered.
- B. Gypsum Ceiling Board: ASTM C1396/C1396M.
 - 1. Thickness: 1/2 inch.
 - 2. Long Edges: Tapered.
- C. Mold-Resistant Gypsum Board: ASTM C1396/C1396M. With moisture- and mold-resistant core and paper surfaces.
 - 1. Core: 5/8 inch, Type X.
 - 2. Long Edges: Tapered.
 - 3. Mold Resistance: ASTM D3273, score of 10 as rated according to ASTM D3274.

2.4 SPECIALTY GYPSUM BOARD

- A. Gypsum Board, Type C: ASTM C1396/C1396M. Manufactured to have increased fire-resistive capability.
 - 1. Thickness: As required by fire-resistance-rated assembly indicated on Drawings.
 - 2. Long Edges: Tapered.

2.5 TILE BACKING PANELS

- A. Glass-Mat, Water-Resistant Backing Board: ASTM C1178/C1178M, with manufacturer's standard edges.
 - 1. Core: 5/8 inch, Type X.
 - 2. Mold Resistance: ASTM D3273, score of 10 as rated according to ASTM D3274.

- B. Cementitious Backer Units: ANSI A118.9 and ASTM C1288 or ASTM C1325, with manufacturer's standard edges.
 - 1. Thickness: 5/8 inch.
 - 2. Mold Resistance: ASTM D3273, score of 10 as rated according to ASTM D3274.
- C. Water-Resistant Gypsum Backing Board: ASTM C1396/C1396M, with manufacturer's standard edges.
 - 1. Core: 5/8 inch, Type X.

2.6 JOINT TREATMENT MATERIALS

- A. General: Comply with ASTM C475/C475M.
- B. Joint Tape:
 - 1. Interior Gypsum Board: Paper.
 - 2. Exterior Gypsum Soffit Board: Paper.
 - 3. Glass-Mat Gypsum Sheathing Board: 10-by-10 glass mesh.
 - 4. Tile Backing Panels: As recommended by panel manufacturer.
- C. Joint Compound for Interior Gypsum Board: For each coat, use formulation that is compatible with other compounds applied on previous or for successive coats.
 - 1. Prefilling: At open joints and damaged surface areas, use setting-type taping compound.
 - 2. Embedding and First Coat: For embedding tape and first coat on joints, fasteners, and trim flanges, use setting-type taping drying-type, all-purpose compound.
 - a. Use setting-type compound for installing paper-faced metal trim accessories.
 - 3. Fill Coat: For second coat, use setting-type, sandable topping compound.
 - 4. Finish Coat: For third coat, use setting-type, sandable topping compound.
 - 5. Skim Coat: For final coat of Level 5 finish, use setting-type, sandable topping compound.
- D. Joint Compound for Exterior Applications:
 - 1. Exterior Gypsum Soffit Board: Use setting-type taping compound and setting-type, sandable topping compound.
 - 2. Glass-Mat Gypsum Sheathing Board: As recommended by sheathing board manufacturer.
- E. Joint Compound for Tile Backing Panels:
 - 1. Glass-Mat, Water-Resistant Backing Panel: As recommended by backing panel manufacturer.
 - 2. Cementitious Backer Units: As recommended by backer unit manufacturer.
 - 3. Water-Resistant Gypsum Backing Board: Use setting-type taping compound and setting-type, sandable topping compound.

2.7 AUXILIARY MATERIALS

- A. Provide auxiliary materials that comply with referenced installation standards and manufacturer's written instructions.
- B. Laminating Adhesive: Adhesive or joint compound recommended for directly adhering gypsum panels to continuous substrate.

- C. Steel Drill Screws: ASTM C1002 unless otherwise indicated.
 - 1. Use screws complying with ASTM C954 for fastening panels to steel members from 0.033 to 0.112 inch thick.
 - 2. For fastening cementitious backer units, use screws of type and size recommended by panel manufacturer.
- D. Sound-Attenuation Blankets: ASTM C665, Type I (blankets without membrane facing) produced by combining thermosetting resins with mineral fibers manufactured from glass, slag wool, or rock wool.
 - 1. Fire-Resistance-Rated Assemblies: Comply with mineral-fiber requirements of assembly.
- E. Acoustical Sealant: As specified in Section 079219 "Acoustical Joint Sealants."
- F. Thermal Insulation: As specified in Section 072100 "Thermal Insulation."
- G. Vapor Retarder: As specified in Section 072600 "Vapor Retarders."

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine areas and substrates including welded hollow-metal frames and support framing, with Installer present, for compliance with requirements and other conditions affecting performance of the Work.
- B. Examine panels before installation. Reject panels that are wet, moisture damaged, and mold damaged.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION AND FINISHING OF PANELS, GENERAL

- A. Comply with ASTM C840.
- B. Install ceiling panels across framing to minimize the number of abutting end joints and to avoid abutting end joints in central area of each ceiling. Stagger abutting end joints of adjacent panels not less than one framing member.
- C. Install panels with face side out. Butt panels together for a light contact at edges and ends with not more than 1/16 inch of open space between panels. Do not force into place.
- D. Locate edge and end joints over supports, except in ceiling applications where intermediate supports or gypsum board back-blocking is provided behind end joints. Do not place tapered edges against cut edges or ends. Stagger vertical joints on opposite sides of partitions. Do not make joints other than control joints at corners of framed openings.
- E. Form control and expansion joints with space between edges of adjoining gypsum panels.

- F. Cover both faces of support framing with gypsum panels in concealed spaces (above ceilings, etc.), except in chases braced internally.
 - 1. Unless concealed application is indicated or required for sound, fire, air, or smoke ratings, coverage may be accomplished with scraps of not less than 8 sq. ft. in area.
 - 2. Fit gypsum panels around ducts, pipes, and conduits.
 - 3. Where partitions intersect structural members projecting below underside of floor/roof slabs and decks, cut gypsum panels to fit profile formed by structural members; allow 1/4- to 3/8-inch- wide joints to install sealant.
- G. Isolate perimeter of gypsum board applied to non-load-bearing partitions at structural abutments. Provide 1/4- to 1/2-inch- wide spaces at these locations and trim edges with edge trim where edges of panels are exposed. Seal joints between edges and abutting structural surfaces with acoustical sealant.
- H. Attachment to Steel Framing: Attach panels so leading edge or end of each panel is attached to open (unsupported) edges of stud flanges first.
- I. Wood Framing: Install gypsum panels over wood framing, with floating internal corner construction. Do not attach gypsum panels across the flat grain of wide-dimension lumber, including floor joists and headers. Float gypsum panels over these members or provide control joints to counteract wood shrinkage.
- J. STC-Rated Assemblies: Seal construction at perimeters, behind control joints, and at openings and penetrations with a continuous bead of acoustical sealant. Install acoustical sealant at both faces of partitions at perimeters and through penetrations. Comply with ASTM C919 and with manufacturer's written instructions for locating edge trim and closing off sound-flanking paths around or through assemblies, including sealing partitions above acoustical ceilings.
- K. Install sound attenuation blankets before installing gypsum panels unless blankets are readily installed after panels have been installed on one side.

3.3 INSTALLATION OF INTERIOR GYPSUM BOARD

- A. Install interior gypsum board in the following locations:
 - 1. Wallboard Type: Vertical surfaces unless otherwise indicated.
 - 2. Type X: Where required for fire-resistance-rated assembly.
 - 3. Ceiling Type: As indicated on Drawings.
 - 4. Mold-Resistant Type: As indicated on Drawings.
- B. Single-Layer Application:
 - 1. On ceilings, apply gypsum panels before wall/partition board application to greatest extent possible and at right angles to framing unless otherwise indicated.
 - 2. On partitions/walls, apply gypsum panels vertically (parallel to framing) horizontally (perpendicular to framing) unless otherwise indicated or required by fire-resistance-rated assembly, and minimize end joints.
 - a. Stagger abutting end joints not less than one framing member in alternate courses of panels.
 - b. At stairwells and other high walls, install panels horizontally unless otherwise indicated or required by fire-resistance-rated assembly.

3. On Z-shaped furring members, apply gypsum panels vertically (parallel to framing) with no end joints. Locate edge joints over furring members.
 4. Fastening Methods: Apply gypsum panels to supports with steel drill screws.
- C. Multilayer Application:
1. On ceilings, apply gypsum board indicated for base layers before applying base layers on walls/partitions; apply face layers in same sequence. Apply base layers at right angles to framing members and offset face-layer joints one framing member, 16 inches minimum, from parallel base-layer joints, unless otherwise indicated or required by fire-resistance-rated assembly.
 2. On partitions/walls, apply gypsum board indicated for base layers and face layers vertically (parallel to framing) with joints of base layers located over stud or furring member and face-layer joints offset at least one stud or furring member with base-layer joints unless otherwise indicated or required by fire-resistance-rated assembly. Stagger joints on opposite sides of partitions.
 3. On Z-shaped furring members, apply base layer vertically (parallel to framing) and face layer either vertically (parallel to framing) or horizontally (perpendicular to framing) with vertical joints offset at least one furring member. Locate edge joints of base layer over furring members.
 4. Fastening Methods: Fasten base layers and face layers separately to supports with screws.
- D. Laminating to Substrate: Where gypsum panels are indicated as directly adhered to a substrate (other than studs, joists, furring members, or base layer of gypsum board), comply with gypsum board manufacturer's written instructions and temporarily brace or fasten gypsum panels until fastening adhesive has set.
- E. Curved Surfaces:
1. Install panels horizontally (perpendicular to supports) and unbroken, to extent possible, across curved surface plus 12-inch- long straight sections at ends of curves and tangent to them.
 2. For double-layer construction, fasten base layer to studs with screws 16 inches o.c. Center gypsum board face layer over joints in base layer, and fasten to studs with screws spaced 12 inches o.c.
- 3.4 INSTALLATION OF EXTERIOR GYPSUM PANELS FOR CEILINGS AND SOFFITS
- A. Apply panels perpendicular to supports, with end joints staggered and located over supports.
1. Install with 1/4-inch open space where panels abut other construction or structural penetrations.
 2. Fasten with corrosion-resistant screws.
- 3.5 INSTALLATION OF TILE BACKING PANELS
- A. Glass-Mat, Water-Resistant Backing Panels: Comply with manufacturer's written installation instructions and install at locations indicated to receive tile. Install with 1/4-inch gap where panels abut other construction or penetrations.
- B. Cementitious Backer Units: ANSI A108.11, at locations indicated to receive tile.

- C. Water-Resistant Backing Board: Install where indicated with 1/4-inch gap where panels abut other construction or penetrations.
- D. Where tile backing panels abut other types of panels in same plane, shim surfaces to produce a uniform plane across panel surfaces.

3.6 INSTALLATION OF TRIM ACCESSORIES

- A. General: For trim with back flanges intended for fasteners, attach to framing with same fasteners used for panels. Otherwise, attach trim according to manufacturer's written instructions.
- B. Control Joints: Install control joints at locations indicated on Drawings.
- C. Interior Trim: Install in the following locations:
 - 1. Cornerbead: Use at outside corners unless otherwise indicated.
 - 2. Bullnose Bead: Use at outside corners.
 - 3. LC-Bead: Use at exposed panel edges.
 - 4. L-Bead: Use where indicated.
 - 5. U-Bead: Use at exposed panel edges.
 - 6. Curved-Edge Cornerbead: Use at curved openings.
- D. Aluminum Trim: Install in locations indicated on Drawings.

3.7 FINISHING GYPSUM BOARD

- A. General: Treat gypsum board joints, interior angles, edge trim, control joints, penetrations, fastener heads, surface defects, and elsewhere as required to prepare gypsum board surfaces for decoration. Promptly remove residual joint compound from adjacent surfaces.
- B. Prefill open joints and damaged surface areas.
- C. Apply joint tape over gypsum board joints, except for trim products specifically indicated as not intended to receive tape.
- D. Gypsum Board Finish Levels: Finish panels to levels indicated below and according to ASTM C840:
 - 1. Level 1: Ceiling plenum areas, concealed areas, and where indicated.
 - 2. Level 2: Panels that are substrate for tile.
 - 3. Level 3: Where indicated on Drawings.
 - 4. Level 4: At panel surfaces that will be exposed to view unless otherwise indicated.
 - a. Primer and its application to surfaces are specified in Section 099123 "Interior Painting."
 - 5. Level 5: Where indicated on Drawings.
 - a. Primer and its application to surfaces are specified in Section 099123 "Interior Painting."
- E. Glass-Mat Gypsum Sheathing Board: Finish according to manufacturer's written instructions for use as exposed soffit board.

- F. Glass-Mat Faced Panels: Finish according to manufacturer's written instructions.
- G. Cementitious Backer Units: Finish according to manufacturer's written instructions.

3.8 PROTECTION

- A. Protect adjacent surfaces from drywall compound and promptly remove from floors and other non-drywall surfaces. Repair surfaces stained, marred, or otherwise damaged during drywall application.
- B. Protect installed products from damage from weather, condensation, direct sunlight, construction, and other causes during remainder of the construction period.
- C. Remove and replace panels that are wet, moisture damaged, and mold damaged.
 - 1. Indications that panels are wet or moisture damaged include, but are not limited to, discoloration, sagging, or irregular shape.
 - 2. Indications that panels are mold damaged include, but are not limited to, fuzzy or splotchy surface contamination and discoloration.

END OF SECTION 092900

SECTION 095123 - ACOUSTICAL TILE CEILINGS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Acoustical tiles for interior ceilings.
 - 2. Fully concealed, direct-hung, suspension systems.
- B. Related Requirements:
- C. Products furnished, but not installed under this Section, include anchors, clips, and other ceiling attachment devices to be cast in concrete.

1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

1.4 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples: For each exposed product and for each color and texture specified, 6 inches in size.

1.5 INFORMATIONAL SUBMITTALS

1.6 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials, from the same product run, that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Acoustical Ceiling Units: Full-size tiles equal to 2 percent of quantity installed.
 - 2. Suspension-System Components: Quantity of each concealed grid and exposed component equal to 2 percent of quantity installed.

1.7 QUALITY ASSURANCE

1.8 DELIVERY, STORAGE, AND HANDLING

- A. Deliver acoustical tiles, suspension-system components, and accessories to Project site and store them in a fully enclosed, conditioned space where they will be protected against damage from moisture, humidity, temperature extremes, direct sunlight, surface contamination, and other causes.
- B. Before installing acoustical tiles, permit them to reach room temperature and a stabilized moisture content.

1.9 FIELD CONDITIONS

- A. Environmental Limitations: Do not install acoustical tile ceilings until spaces are enclosed and weathertight, wet-work in spaces is complete and dry, work above ceilings is complete, and ambient temperature and humidity conditions are maintained at the levels indicated for Project when occupied for its intended use.
 - 1. Pressurized Plenums: Operate ventilation system for not less than 48 hours before beginning acoustical tile ceiling installation.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Source Limitations:
 - 1. Suspended Acoustical Tile Ceilings: Obtain each type of acoustical ceiling tile and its suspension system from single source from single manufacturer.
 - 2. Directly Attached Acoustical Tile Ceilings: Obtain each type of acoustical ceiling tile from single source from single manufacturer.
- B. ACOUSTICAL TILES Acoustical Tile Standard: Provide manufacturer's standard tegular edge tiles of configuration indicated that comply with ASTM E1264 classifications as designated by type, form, pattern, acoustical rating, and light reflectance unless otherwise indicated.

2.2 METAL SUSPENSION SYSTEM

- A. Metal Suspension-System Standard: Provide manufacturer's standard, direct-hung, fully concealed, metal suspension system and accessories of type, structural classification, and finish indicated that complies with applicable requirements in ASTM C635/C635M.

2.3 ACCESSORIES

- A. Attachment Devices: Size for five times the design load indicated in ASTM C635/C635M, Table 1, "Direct Hung," unless otherwise indicated. Comply with seismic design requirements.
- B. Wire Hangers, Braces, and Ties: Provide wires as follows:

1. Zinc-Coated, Carbon-Steel Wire: ASTM A641/A641M, Class 1 zinc coating, soft temper.

2.4 METAL EDGE MOLDINGS AND TRIM <Insert drawing designation>

- A. Roll-Formed, Sheet-Metal Edge Moldings and Trim: Type and profile indicated or, if not indicated, manufacturer's standard moldings for edges and penetrations complying with seismic design requirements; formed from sheet metal of same material, finish, and color as that used for of suspension-system runners.
 1. For circular penetrations of ceiling, provide edge moldings fabricated to diameter required to fit penetration exactly.
 2. Finish: Painted white.

2.5 ACOUSTICAL SEALANT

- A. Acoustical Sealant: As specified in Section 079219 "Acoustical Joint Sealants."

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, including structural framing and substrates to which acoustical tile ceilings attach or abut, with Installer present, for compliance with requirements specified in this and other Sections that affect ceiling installation and anchorage and for compliance with requirements for installation tolerances and other conditions affecting performance of the Work.
- B. Examine acoustical tiles before installation. Reject acoustical tiles that are wet, moisture damaged, or mold damaged.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Testing Substrates: Before adhesively bonding tiles to wet-placed substrates such as cast-in-place concrete or plaster, test and verify that moisture level is below tile manufacturer's recommended limits.
- B. Measure each ceiling area and establish layout of acoustical tiles to balance border widths at opposite edges of each ceiling. Avoid using less-than-half-width tiles at borders unless otherwise indicated, and comply with layout shown on reflected ceiling plans.
- C. Layout openings for penetrations centered on the penetrating items.

3.3 INSTALLATION OF SUSPENDED ACOUSTICAL TILE CEILINGS

- A. Install suspended acoustical tile ceilings according to ASTM C636/C636M and manufacturer's written instructions.

1. Fire-Rated Assembly: Install fire-rated ceiling systems according to tested fire-rated design.
- B. Suspend ceiling hangers from building's structural members and as follows:
1. Install hangers plumb and free from contact with insulation or other objects within ceiling plenum that are not part of supporting structure or of ceiling suspension system.
 2. Splay hangers only where required to miss obstructions; offset resulting horizontal forces by bracing, countersplaying, or other equally effective means.
 3. Where width of ducts and other construction within ceiling plenum produces hanger spacings that interfere with location of hangers at spacings required to support standard suspension-system members, install supplemental suspension members and hangers in form of trapezes or equivalent devices.
 4. Secure wire hangers to ceiling suspension members and to supports above with a minimum of three tight turns. Connect hangers directly to structure or to inserts, eye screws, or other devices that are secure and appropriate for substrate and that will not deteriorate or otherwise fail due to age, corrosion, or elevated temperatures.
 5. Secure flat, angle, channel, and rod hangers to structure, including intermediate framing members, by attaching to inserts, eye screws, or other devices that are secure and appropriate for both the structure to which hangers are attached and the type of hanger involved. Install hangers in a manner that will not cause them to deteriorate or fail due to age, corrosion, or elevated temperatures.
 6. Do not support ceilings directly from permanent metal forms or floor deck. Fasten hangers to cast-in-place hanger inserts, postinstalled mechanical or adhesive anchors, or power-actuated fasteners that extend through forms into concrete.
 7. When steel framing does not permit installation of hanger wires at spacing required, install carrying channels or other supplemental support for attachment of hanger wires.
 8. Do not attach hangers to steel deck tabs.
 9. Do not attach hangers to steel roof deck. Attach hangers to structural members.
 10. Space hangers not more than 48 inches o.c. along each member supported directly from hangers unless otherwise indicated; provide hangers not more than 8 inches from ends of each member.
 11. Size supplemental suspension members and hangers to support ceiling loads within performance limits established by referenced standards.
- C. Secure bracing wires to ceiling suspension members and to supports with a minimum of four tight turns. Suspend bracing from building's structural members as required for hangers without attaching to permanent metal forms, steel deck, or steel deck tabs. Fasten bracing wires into concrete with cast-in-place or postinstalled anchors.
- D. Install edge moldings and trim of type indicated at perimeter of acoustical ceiling area and where necessary to conceal edges of acoustical tiles.
1. Apply acoustical sealant in a continuous ribbon concealed on back of vertical legs of moldings before they are installed.
 2. Screw attach moldings to substrate at intervals not more than 16 inches o.c. and not more than 3 inches from ends. Miter corners accurately and connect securely.
 3. Do not use exposed fasteners, including pop rivets, on moldings and trim.
- E. Install suspension-system runners so they are square and securely interlocked with one another. Remove and replace dented, bent, or kinked members.

- F. Arrange directionally patterned acoustical tiles as follows:
 - 1. As indicated on reflected ceiling plans.
 - 2. Install tiles with pattern running in one direction parallel to long axis of space.
 - 3. Install tiles in a basket-weave pattern.

- G. Install acoustical tiles in coordination with suspension system and exposed moldings and trim. Place splines or suspension-system flanges into kerfed edges of tiles so tile-to-tile joints are interlocked.
 - 1. Fit adjoining tiles to form flush, tight joints. Scribe and cut tiles for accurate fit at borders and around penetrations through ceiling.
 - 2. Hold tile field in compression by inserting leaf-type, spring-steel spacers between tiles and moldings, spaced 12 inches o.c.
 - 3. Protect lighting fixtures and air ducts according to requirements indicated for fire-resistance-rated assembly.

3.4 INSTALLATION OF DIRECTLY ATTACHED ACOUSTICAL TILE CEILINGS

- A. Adhesive Installation: Install acoustical tile by bonding to substrate, using acoustical tile adhesive and procedure recommended in writing by tile manufacturer and as follows:
 - 1. Wipe and prime ceiling.
 - 2. Remove loose dust from backs of tiles by brushing.
 - 3. Install splines in joints between tiles and maintain bottom surface to a uniform level. Shim tile or correct substrate as required to maintain levelness.
 - 4. Maintain tight butt joints, aligned in both directions and coordinated with ceiling fixtures.

- B. Stapled Installation: Fasten acoustical tile to substrate using a minimum of two staples per tile that are installed in flanges of tile and as follows:
 - 1. Form double-lapped joint between tiles by securely pressing tile tongues into corresponding tile grooves.
 - 2. Maintain bottom surface of tiles to a uniform level. Shim tile or correct substrate as required to maintain levelness.
 - 3. Maintain tight butt joints, aligned in both directions and coordinated with ceiling fixtures.

- C. Install edge moldings and trim of type indicated at perimeter of acoustical tile ceiling area and where necessary to conceal edges of acoustical units.

3.5 ERECTION TOLERANCES

- A. Suspended Ceilings: Install main and cross runners level to a tolerance of 1/8 inch in 12 feet, non-cumulative.

- B. Directly Attached Ceilings: Install bottom surface of tiles to a tolerance of 1/8 inch in 12 feet and not exceeding 1/4 inch cumulatively.

- C. Moldings and Trim: Install moldings and trim to substrate and level with ceiling suspension system to a tolerance of 1/8 inch in 12 feet, non-cumulative.

3.6 FIELD QUALITY CONTROL

3.7 ADJUSTING

- A. Clean exposed surfaces of acoustical tile ceilings, including trim and edge moldings. Comply with manufacturer's written instructions for cleaning and touchup of minor finish damage.
- B. Remove and replace tiles and other ceiling components that cannot be successfully cleaned and repaired to permanently eliminate evidence of damage.

END OF SECTION 095123

SECTION 096513 - RESILIENT BASE AND ACCESSORIES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 1. Thermoset-rubber base.
 2. Thermoplastic-rubber base.
 3. Vinyl base.
 4. Rubber stair accessories.
 5. Vinyl stair accessories.
 6. Rubber molding accessories.
 7. Vinyl molding accessories.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples: For each exposed product and for each color and texture specified, not less than 12 inches long.

1.4 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 1. Furnish not less than 10 linear feet for every or fraction thereof, of each type, color, pattern, and size of resilient product installed.

1.5 QUALITY ASSURANCE

- A. Mockups: Build mockups to verify selections made under Sample submittals, to demonstrate aesthetic effects, and to set quality standards for materials and execution.
 1. Coordinate mockups in this Section with mockups specified in other Sections.
 2. Approval of mockups does not constitute approval of deviations from the Contract Documents contained in mockups unless Architect specifically approves such deviations in writing.
 3. Subject to compliance with requirements, approved mockups may become part of the completed Work if undisturbed at time of Substantial Completion.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Store resilient products and installation materials in dry spaces protected from the weather, with ambient temperatures maintained within range recommended by manufacturer, but not less than 50 deg F or more than 90 deg F.

PART 2 - PRODUCTS

2.1 THERMOSET-RUBBER BASE

- A. Product Standard: ASTM F1861, Type TS (rubber, vulcanized thermoset), Group I (solid, homogeneous).
 - 1. Style and Location:
 - a. Style A, Straight: Provide in areas with carpet.
 - b. Style B, Cove: Provide in areas with resilient floor coverings.
- B. Thickness: 0.125 inch.
- C. Height: 4 inches.
- D. Lengths: Coils in manufacturer's standard length.
- E. Outside Corners: Preformed.
- F. Inside Corners: Preformed.
- G. Colors: As indicated by manufacturer's designations.

2.2 INSTALLATION MATERIALS

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland-cement-based or blended hydraulic-cement-based formulation provided or approved by resilient-product manufacturer for applications indicated.
- B. Adhesives: Water-resistant type recommended by resilient-product manufacturer for resilient products and substrate conditions indicated.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, with Installer present, for compliance with requirements for maximum moisture content and other conditions affecting performance of the Work.
 - 1. Verify that finishes of substrates comply with tolerances and other requirements specified in other Sections and that substrates are free of cracks, ridges, depressions, scale, and foreign deposits that might interfere with adhesion of resilient products.

- B. Proceed with installation only after unsatisfactory conditions have been corrected.
 - 1. Installation of resilient products indicates acceptance of surfaces and conditions.

3.2 PREPARATION

- A. Prepare substrates according to manufacturer's written instructions to ensure adhesion of resilient products.
- B. Fill cracks, holes, and depressions in substrates with trowelable leveling and patching compound; remove bumps and ridges to produce a uniform and smooth substrate.
- C. Do not install resilient products until materials are the same temperature as space where they are to be installed.
 - 1. At least 48 hours in advance of installation, move resilient products and installation materials into spaces where they will be installed.
- D. Immediately before installation, sweep and vacuum clean substrates to be covered by resilient products.

3.3 RESILIENT BASE INSTALLATION

- A. Comply with manufacturer's written instructions for installing resilient base.
- B. Apply resilient base to walls, columns, pilasters, casework and cabinets in toe spaces, and other permanent fixtures in rooms and areas where base is required.
- C. Install resilient base in lengths as long as practical without gaps at seams and with tops of adjacent pieces aligned.
- D. Tightly adhere resilient base to substrate throughout length of each piece, with base in continuous contact with horizontal and vertical substrates.
- E. Do not stretch resilient base during installation.
- F. On masonry surfaces or other similar irregular substrates, fill voids along top edge of resilient base with manufacturer's recommended adhesive filler material.
- G. Preformed Corners: Install preformed corners before installing straight pieces.

3.4 CLEANING AND PROTECTION

- A. Comply with manufacturer's written instructions for cleaning and protecting resilient products.
- B. Perform the following operations immediately after completing resilient-product installation:
 - 1. Remove adhesive and other blemishes from surfaces.
 - 2. Sweep and vacuum horizontal surfaces thoroughly.
 - 3. Damp-mop horizontal surfaces to remove marks and soil.

- C. Protect resilient products from mars, marks, indentations, and other damage from construction operations and placement of equipment and fixtures during remainder of construction period.

END OF SECTION 096513

SECTION 099123 - INTERIOR PAINTING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Primers.
 - 2. Water-based finish coatings.
 - 3. Solvent-based finish coatings.
 - 4. Floor sealers and paints.
 - 5. Dry fall coatings.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product. Include preparation requirements and application instructions.
 - 1. Include preparation requirements and application instructions.
 - 2. Indicate VOC content.
- B. Samples: For each type of topcoat product.
- C. Samples for Initial Selection: For each type of topcoat product.
- D. Samples for Verification: For each type of paint system and each color and gloss of topcoat.
 - 1. Submit Samples on rigid backing, 8 inches square.
 - 2. Apply coats on Samples in steps to show each coat required for system.
 - 3. Label each coat of each Sample.
 - 4. Label each Sample for location and application area.
- E. Product Schedule: Use same designations indicated on Drawings and in the Interior Painting Schedule to cross-reference paint systems specified in this Section. Include color designations.

1.4 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Paint Products: 5 percent, but not less than 1 gal. of each material and color applied.

1.5 QUALITY ASSURANCE

- A. Mockups: Apply mockups of each paint system indicated and each color and finish selected to verify preliminary selections made under Sample submittals and to demonstrate aesthetic effects and set quality standards for materials and execution.
 - 1. Architect will select one surface to represent surfaces and conditions for application of each paint system.
 - a. Vertical and Horizontal Surfaces: Provide samples of at least 100 sq. ft..
 - b. Other Items: Architect will designate items or areas required.
 - 2. Final approval of color selections will be based on mockups.
 - a. If preliminary color selections are not approved, apply additional mockups of additional colors selected by Architect at no added cost to Owner.
 - 3. Approval of mockups does not constitute approval of deviations from the Contract Documents contained in mockups unless Architect specifically approves such deviations in writing.
 - 4. Subject to compliance with requirements, approved mockups may become part of the completed Work if undisturbed at time of Substantial Completion.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Store materials not in use in tightly covered containers in well-ventilated areas with ambient temperatures continuously maintained at not less than 45 deg F.
 - 1. Maintain containers in clean condition, free of foreign materials and residue.
 - 2. Remove rags and waste from storage areas daily.

1.7 FIELD CONDITIONS

- A. Apply paints only when temperature of surfaces to be painted and ambient air temperatures are between 50 and 95 deg F.
- B. Do not apply paints when relative humidity exceeds 85 percent; at temperatures of less than 5 deg F above the dew point; or to damp or wet surfaces.

PART 2 - PRODUCTS

2.1 PAINT PRODUCTS, GENERAL

- A. Material Compatibility:
 - 1. Materials for use within each paint system shall be compatible with one another and substrates indicated, under conditions of service and application as demonstrated by manufacturer, based on testing and field experience.
- B. Colors: As selected by Architect from manufacturer's full range Match Architect's samples As indicated in a color schedule.

2.2 PRIMERS

- A. Interior Latex Primer Sealer: Water-based latex sealer used on new interior plaster, concrete, and gypsum wallboard surfaces.
- B. Interior Latex Primer for Wood: Waterborne-emulsion primer formulated for resistance to extractive bleeding, mold, and microbials; for hiding stains; and for use on interior wood subject to extractive bleeding.
- C. Water-Based Rust-Inhibitive Primer: Corrosion-resistant, water-based-emulsion primer formulated for resistance to flash rusting when applied to cleaned, interior ferrous metals subject to mildly corrosive environments.
- D. Water-Based Galvanized-Metal Primer: Corrosion-resistant, acrylic primer; formulated for use on cleaned/etched, exterior, galvanized metal to prepare it for subsequent water-based coatings.

2.3 WATER-BASED FINISH COATS

- A. Interior, Latex, Eggshell: Pigmented, water-based paint for use on primed/sealed interior plaster and gypsum board, and on primed wood and metals.
 - 1. Gloss and Sheen Level: Manufacturer's standard eggshell finish.

2.4 EXAMINATION

- A. Examine substrates and conditions, with Applicator present, for compliance with requirements for maximum moisture content and other conditions affecting performance of the Work.
- B. Maximum Moisture Content of Substrates: When measured with an electronic moisture meter as follows:
 - 1. Concrete: 12 percent.
 - 2. Fiber-Cement Board: 12 percent.
 - 3. Masonry (Clay and CMUs): 12 percent.
 - 4. Wood: 15 percent.
 - 5. Gypsum Board: 12 percent.
 - 6. Plaster: 12 percent.
- C. Gypsum Board Substrates: Verify that finishing compound is sanded smooth.
- D. Plaster Substrates: Verify that plaster is fully cured.
- E. Spray-Textured Ceiling Substrates: Verify that surfaces are dry.
- F. Verify suitability of substrates, including surface conditions and compatibility, with existing finishes and primers.
- G. Proceed with coating application only after unsatisfactory conditions have been corrected.
 - 1. Application of coating indicates acceptance of surfaces and conditions.

2.5 PREPARATION

- A. Comply with manufacturer's written instructions and recommendations applicable to substrates and paint systems indicated.
- B. Remove hardware, covers, plates, and similar items already in place that are removable and are not to be painted. If removal is impractical or impossible because of size or weight of item, provide surface-applied protection before surface preparation and painting.
 - 1. After completing painting operations, use workers skilled in the trades involved to reinstall items that were removed. Remove surface-applied protection if any.
- C. Clean substrates of substances that could impair bond of paints, including dust, dirt, oil, grease, and incompatible paints and encapsulants.
 - 1. Remove incompatible primers and reprime substrate with compatible primers or apply tie coat as required to produce paint systems indicated.
- D. Concrete Substrates: Remove release agents, curing compounds, efflorescence, and chalk. Do not paint surfaces if moisture content or alkalinity of surfaces to be painted exceeds that permitted in manufacturer's written instructions.
- E. Masonry Substrates: Remove efflorescence and chalk. Do not paint surfaces if moisture content or alkalinity of surfaces or mortar joints exceeds that permitted in manufacturer's written instructions.
- F. Steel Substrates: Remove rust, loose mill scale, and shop primer, if any. Clean using methods recommended in writing by paint manufacturer.
 - 1. SSPC-SP 2.
 - 2. SSPC-SP 3.
 - 3. SSPC-SP 7/NACE No. 4.
 - 4. SSPC-SP 11.
- G. Shop-Primed Steel Substrates: Clean field welds, bolted connections, and areas where shop paint is abraded. Paint exposed areas with the same material as used for shop priming to comply with SSPC-PA 1 for touching up shop-primed surfaces.
- H. Galvanized-Metal Substrates: Remove grease and oil residue from galvanized sheet metal by mechanical methods to produce clean, lightly etched surfaces that promote adhesion of subsequently applied paints.
- I. Aluminum Substrates: Remove loose surface oxidation.
- J. Wood Substrates:
 - 1. Scrape and clean knots, and apply coat of knot sealer before applying primer.
 - 2. Sand surfaces that will be exposed to view, and dust off.
 - 3. Prime edges, ends, faces, undersides, and backsides of wood.
 - 4. After priming, fill holes and imperfections in the finish surfaces with putty or plastic wood filler. Sand smooth when dried.
- K. Cotton or Canvas Insulation Covering Substrates: Remove dust, dirt, and other foreign material that might impair bond of paints to substrates.

2.6 INSTALLATION

- A. Apply paints according to manufacturer's written instructions.
 - 1. Use applicators and techniques suited for paint and substrate indicated.
 - 2. Paint surfaces behind movable equipment and furniture same as similar exposed surfaces. Before final installation, paint surfaces behind permanently fixed equipment or furniture with prime coat only.
 - 3. Paint front and backsides of access panels, removable or hinged covers, and similar hinged items to match exposed surfaces.
 - 4. Do not paint over labels of independent testing agencies or equipment name, identification, performance rating, or nomenclature plates.
 - 5. Primers specified in painting schedules may be omitted on items that are factory primed or factory finished if acceptable to topcoat manufacturers.

- B. Tint each undercoat a lighter shade to facilitate identification of each coat if multiple coats of same material are to be applied. Tint undercoats to match color of topcoat, but provide sufficient difference in shade of undercoats to distinguish each separate coat.

- C. If undercoats or other conditions show through topcoat, apply additional coats until cured film has a uniform paint finish, color, and appearance.

- D. Apply paints to produce surface films without cloudiness, spotting, holidays, laps, brush marks, roller tracking, runs, sags, ropiness, or other surface imperfections. Cut in sharp lines and color breaks.

- E. Painting Fire-Suppression, Plumbing, HVAC, Electrical, Communication, and Electronic Safety and Security Work:
 - 1. Paint the following work where exposed in equipment rooms:
 - a. Equipment, including panelboards.
 - b. Uninsulated metal piping.
 - c. Uninsulated plastic piping.
 - d. Pipe hangers and supports.
 - e. Metal conduit.
 - f. Plastic conduit.
 - g. Tanks that do not have factory-applied final finishes.
 - h. Duct, equipment, and pipe insulation having cotton or canvas insulation covering or other paintable jacket material.
 - 2. Paint the following work where exposed in occupied spaces:
 - a. Equipment, including panelboards.
 - b. Uninsulated metal piping.
 - c. Uninsulated plastic piping.
 - d. Pipe hangers and supports.
 - e. Metal conduit.
 - f. Plastic conduit.
 - g. Duct, equipment, and pipe insulation having cotton or canvas insulation covering or other paintable jacket material.
 - h. Other items as directed by Architect.
 - 3. Paint portions of internal surfaces of metal ducts, without liner, behind air inlets and outlets that are visible from occupied spaces.

2.7 FIELD QUALITY CONTROL

- A. Dry-Film Thickness Testing: Owner may engage the services of a qualified testing and inspecting agency to inspect and test paint for dry-film thickness.
 - 1. Contractor shall touch up and restore painted surfaces damaged by testing.
 - 2. If test results show that dry-film thickness of applied paint does not comply with paint manufacturer's written recommendations, Contractor shall pay for testing and apply additional coats as needed to provide dry-film thickness that complies with paint manufacturer's written recommendations.

2.8 CLEANING AND PROTECTION

- A. At end of each workday, remove rubbish, empty cans, rags, and other discarded materials from Project site.
 - 1. Do not clean equipment with free-draining water and prevent solvents, thinners, cleaners, and other contaminants from entering into waterways, sanitary and storm drain systems, and ground.
 - 2. Dispose of contaminants in accordance with requirements of authorities having jurisdiction.
 - 3. Allow empty paint cans to dry before disposal.
 - 4. Collect waste paint by type and deliver to recycling or collection facility.
- B. After completing paint application, clean spattered surfaces. Remove spattered paints by washing, scraping, or other methods. Do not scratch or damage adjacent finished surfaces.
- C. Protect work of other trades against damage from paint application. Correct damage to work of other trades by cleaning, repairing, replacing, and refinishing, as approved by Architect, and leave in an undamaged condition.
- D. At completion of construction activities of other trades, touch up and restore damaged or defaced painted surfaces.

2.9 INTERIOR PAINTING SCHEDULE

- A. Exposed Wood Framing:
 - 1. Latex over Latex Primer System:
 - a. Prime Coat: Interior latex primer for wood.
 - b. Intermediate Coat: Matching topcoat.
 - c. Topcoat: Interior, latex, gloss.
- B. Gypsum Board Substrates:
 - 1. Latex over Latex Sealer System:
 - a. Prime Coat: Interior latex primer sealer.
 - b. Intermediate Coat: Matching topcoat.
 - c. Topcoat: Interior, latex, eggshell .

END OF SECTION 099123



ArmorSeal Heavy Duty Floor Coatings

ARMORSEAL® 1000 HS

PART A
PART B

B67-2000
B67V2002

SERIES
HARDENER

Revised: August 10, 2021

PRODUCT INFORMATION

8.22

PRODUCT DESCRIPTION

ARMORSEAL 1000 HS is a high solids, heavy duty, two-component, catalyzed, polyamide epoxy coating formulated for demanding marine and industrial requirements. Dries rapidly to a tough, high gloss finish with excellent resistance to alkalis, abrasion, corrosion, and chemical attack.

- Chemical Resistant
- Impact Resistant
- Abrasion Resistant
- Outstanding application properties

PRODUCT CHARACTERISTICS

Finish:	Gloss
Color:	Clear, Haze Gray, Deck Gray, White, Sandstone, Tile Red, Safety Yellow, and a wide range of tinted colors
Volume Solids, mixed:	colors - 65% ± 2% may vary by color clear - 61% ± 2%
Weight Solids, mixed:	74% ± 2%, may vary by color
VOC (EPA Method 24):	Unreduced (mixed): <340 g/L; 2.8 lb/gal
Mix Ratio:	1:1 by volume

Recommended Spreading Rate per coat:

	Minimum	Maximum
Wet mils (microns)	5.0 (125)	8.0 (200)
Dry mils (microns)	3.0 (75)	5.0 (125)
~Coverage sq ft/gal (m ² /L)	206 (5.0)	350 (8.6)
Theoretical coverage sq ft/gal (m ² /L) @ 1 mil / 25 microns dft	1040 (25.5)	

NOTE: Brush or roll application may require multiple coats to achieve maximum film thickness and uniformity of appearance.

Drying Schedule @ 6.0 mils (150 microns):

	@ 50°F/10°C	@ 77°F/25°C 50% RH	@ 120°F/49°C
To touch:	4 hours	2 hours	30 minutes
To recoat:			
minimum:	24 hours	8 hours	4 hours
maximum:	7 days	7 days	7 days
Foot traffic:	48 hours	24 hours	12 hours
Heavy traffic:	4-5 days	48-72 hours	24-36 hours
To cure:	10 days	7 days	4 days

*If maximum recoat time is exceeded, abrade surface before topcoating.
Drying time is temperature, humidity, and film thickness dependent.*

Pot Life:	6 hours	4 hours	2 hours
Sweat-in-Time:	2 hours	30 minutes	10 minutes

PRODUCT CHARACTERISTICS (CONT'D)

Shelf Life:	36 months, unopened Store indoors at 40°F (4.5°C) to 100°F (38°C)
Flash Point:	>105°F (41°C), Seta, mixed
Reducer*:	VOC Restricted Areas (≤340 g/L): Not recommended
Clean Up:	Reducer #54 (R7K54)

*In other VOC areas (>340 g/L): use Reducer #54 (R7K54). Confirm compliance with state and local air quality rules before use.

RECOMMENDED USES

- For industrial, commercial, or marine applications where a heavy duty epoxy coating is required.
- Superior resistance to chemicals, moisture, abrasion, and impact
- Excellent resistance to alkalis, dilute acids, spillage of solvents, chemicals, jet fuel, grease, etc.
- Clear finish for interior use only
- Suitable for use in USDA inspected facilities

PERFORMANCE CHARACTERISTICS

Substrate*: Concrete
Surface Preparation*: Clean, dry, sound
System Tested*:
 1 ct. ArmorSeal 1000 HS (reduced)
 1 ct. ArmorSeal 1000 HS @ 3.0-5.0 mils (75-125 microns) dft
 *unless otherwise noted below

Test Name	Test Method	Results
Abrasion Resistance	ASTM D4060, CS17 wheel, 1000 cycles, 1 Kg load	64.8 mg loss
Adhesion, over concrete	ASTM D4541	350 psi, 100% concrete failure
Direct Impact Resistance (steel)	ASTM D2794	58 in. lbs
Dry Heat Resistance	ASTM D2485	180°F (82°C)
Flexibility (steel)	ASTM D522, 180° bend, 1/8" mandrel	Passes
Pencil Hardness	ASTM D3363	HB
Slip Resistance, Floors	ASTM C1028**, .60 minimum Static Coefficient of Friction	Passes wet and dry, with and without SharkGrip Additive

**Test method withdrawn in 2014 without replacement

Epoxy coatings may darken or yellow following application and curing.



ArmorSeal Heavy Duty Floor Coatings

ARMORSEAL® 1000 HS

PART A
PART B

B67-2000
B67V2002

SERIES
HARDENER

PRODUCT INFORMATION

Revised: August 10, 2021

8.22

RECOMMENDED SYSTEMS

Dry Film Thickness / ct.

Mils (Microns)

Concrete/Wood:

1 ct. ArmorSeal 1000 HS*	2.5-4.0 (63-100)
1-2 cts. ArmorSeal 1000 HS (with anti-slip aggregate if required)	3.0-5.0 (75-125)

Concrete:

1 ct. ArmorSeal 33 Epoxy Primer/Sealer	8.0 (200)
1-2 cts. ArmorSeal 1000 HS (with anti-slip aggregate if required)	3.0-5.0 (75-125)

Steel:

1 ct. Recoatable Epoxy Primer	4.0-5.0 (100-125)
1-2 cts. ArmorSeal 1000 HS	3.0-5.0 (75-125)

Painted Surfaces in Sound Condition:

1-2 cts. ArmorSeal 1000 HS	3.0-5.0 (75-125)
----------------------------	------------------

*In VOC Restricted Areas (≤ 340 g/L), reduction is not recommended. In other areas (>340 g/L), Reducer #54 (R7K54) may be used as necessary up to 1 pt/gal. Confirm compliance with state and local air quality rules before use.

The systems listed above are representative of the product's use, other systems may be appropriate.

SURFACE PREPARATION

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

Refer to product Application Bulletin for detailed surface preparation information.

Minimum recommended surface preparation:

* Iron & Steel:	SSPC-SP6/NACE 3
Concrete & Masonry:	SSPC-SP13/NACE 6, or ICRI No. 310.2R, CSP 1-3
Wood, interior:	Clean, smooth, dust free
*Primer Required	

Surface Preparation Standards

Condition of Surface	ISO 8501-1 BS7079:A1	Swedish Std. SIS055900	SSPC	NACE
White Metal	Sa 3	Sa 3	SP 5	1
Near White Metal	Sa 2.5	Sa 2.5	SP 10	2
Commercial Blast	Sa 2	Sa 2	SP 6	3
Brush-Off Blast	Sa 1	Sa 1	SP 7	4
Hand Tool Cleaning	C St 2	C St 2	SP 2	-
Pitted & Rusted	D St 2	D St 2	SP 2	-
Power Tool Cleaning	C St 3	C St 3	SP 3	-
Rusted	C St 3	C St 3	SP 3	-
Pitted & Rusted	D St 3	D St 3	SP 3	-

TINTING

White and Ultradeep may be tinted with Maxitoner Colorants at 200% tinting strength into Part A. Five minutes minimum mixing on a mechanical shaker is required for complete mixing of color.

APPLICATION CONDITIONS

Temperature:	50°F (10°C) minimum, 120°F (49°C) maximum (air, surface, and material) At least 5°F (2.8°C) above dew point
Relative humidity:	85% maximum

Refer to product Application Bulletin for detailed application information.

ORDERING INFORMATION

Packaging:	1 gallon (3.78L) containers
Part A:	1 gallon (3.78L) containers
Part B:	(clear available in 5 gallon /18.9L containers)
Weight:	12.51 ± 0.2 lb/gal ; 1.5 Kg/L mixed, may vary by color

SAFETY PRECAUTIONS

Refer to the SDS sheet before use.

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.

WARRANTY

The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin.



ArmorSeal Heavy Duty Floor Coatings

ARMORSEAL® 1000 HS

PART A
PART B

B67-2000
B67V2002

SERIES
HARDENER

Revised: August 10, 2021

APPLICATION BULLETIN

8.22

SURFACE PREPARATIONS

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

Iron & Steel (atmospheric service)

Remove all oil and grease from surface by Solvent Cleaning per SSPC-SP1. Minimum surface preparation is Commercial Blast Cleaning per SSPC-SP6/NACE 3. For better performance, use Near White Metal Blast Cleaning per SSPC-SP10/NACE 2. Blast clean all surfaces using a sharp, angular abrasive for optimum surface profile (2 mils / 50 microns). Prime any bare steel the same day as it is cleaned or before flash rusting occurs.

Concrete and Masonry

For surface preparation, refer to SSPC-SP13/NACE 6, or ICRI No. 310.2R, CSP 1-3. Surfaces should be thoroughly clean and dry. Concrete and mortar must be cured at least 28 days @ 75°F (24°C). Remove all loose mortar and foreign material. Surface must be free of laitance, concrete dust, dirt, form release agents, moisture curing membranes, loose cement and hardeners. Fill bug holes, air pockets and other voids with Steel-Seam FT910. Primer required.

Follow the standard methods listed below when applicable:

ASTM D4258 Standard Practice for Cleaning Concrete.
ASTM D4259 Standard Practice for Abrading Concrete.
ASTM D4260 Standard Practice for Etching Concrete.
ASTM F1869 Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete.
SSPC-SP 13/Nace 6 Surface Preparation of Concrete.
ICRI No. 310.2R Concrete Surface Preparation.

Previously Painted Surfaces

If in sound condition, clean the surface of all foreign material. Smooth, hard or glossy coatings and surfaces should be dulled by abrading the surface. Apply a test area, allowing paint to dry one week before testing adhesion. If adhesion is poor, or if this product attacks the previous finish, removal of the previous coating may be necessary. If paint is peeling or badly weathered, clean surface to sound substrate and treat as a new surface as above.

APPLICATION CONDITIONS

Temperature: 50°F (10°C) minimum, 120°F (49°C) maximum (air, surface, and material)
At least 5°F (2.8°C) above dew point

Relative humidity: 85% maximum

APPLICATION EQUIPMENT

The following is a guide. Changes in pressures and tip sizes may be needed for proper spray characteristics. Always purge spray equipment before use with listed reducer. Any reduction must be compliant with existing VOC regulations and compatible with the existing environmental and application conditions.

Reducer* VOC Restricted Areas (≤340 g/L): Not recommended
Clean Up Reducer #54 (R7K54)

Airless Spray

Pressure..... 2500 psi
Hose..... 3/8" ID
Tip015" - .021"
Filter 60 mesh
Reduction* Not recommended

Brush

Nylon/Polyester or Natural Bristle
Reduction* Not recommended

Roller

Cover 3/8" woven with solvent resistant core
Reduction* Not recommended

*In other VOC areas (>340 g/L): Reducer #54 (R7K54) may be used up to 10% by volume. Confirm compliance with state and local air quality rules before use.

If specific application equipment is not listed above, equivalent equipment may be substituted.

Surface Preparation Standards

Condition of Surface	ISO 8501-1 BS7079:A1	Swedish Std. SIS055900	SSPC	NACE
White Metal	Sa 3	Sa 3	SP 5	1
Near White Metal	Sa 2.5	Sa 2.5	SP 10	2
Commercial Blast	Sa 2	Sa 2	SP 6	3
Brush-Off Blast	Sa 1	Sa 1	SP 7	4
Hand Tool Cleaning	Rusted C.St 2	C.St 2	SP 2	-
Pitted & Rusted	D.St 2	D.St 2	SP 2	-
Power Tool Cleaning	Rusted C.St 3	C.St 3	SP 3	-
Pitted & Rusted	D.St 3	D.St 3	SP 3	-



ArmorSeal Heavy Duty Floor Coatings

ARMORSEAL® 1000 HS

PART A
PART B

B67-2000
B67V2002

SERIES
HARDENER

Revised: August 10, 2021

APPLICATION BULLETIN

8.22

APPLICATION PROCEDURES

Surface preparation must be completed as indicated.

Mix contents of each component thoroughly with low speed power agitation. Combine one Part A with one Part B by volume and mix for 3 minutes and until uniform. Allow the material to sweat-in as indicated. Re-stir before using.

Apply paint at the recommended film thickness and spreading rate as indicated below:

Recommended Spreading Rate per coat:

	Minimum	Maximum
Wet mils (microns)	5.0 (125)	8.0 (200)
Dry mils (microns)	3.0 (75)	5.0 (125)
~Coverage sq ft/gal (m ² /L)	206 (5.0)	350 (8.6)
Theoretical coverage sq ft/gal (m ² /L) @ 1 mil / 25 microns dft	1040 (25.5)	

NOTE: Brush or roll application may require multiple coats to achieve maximum film thickness and uniformity of appearance.

Drying Schedule @ 6.0 mils (150 microns):

	@ 50°F/10°C	@ 77°F/25°C 50% RH	@ 120°F/49°C
To touch:	4 hours	2 hours	30 minutes
To recoat:			
minimum:	24 hours	8 hours	4 hours
maximum:	7 days	7 days	7 days
Foot traffic:	48 hours	24 hours	12 hours
Heavy traffic:	4-5 days	48-72 hours	24-36 hours
To cure:	10 days	7 days	4 days

If maximum recoat time is exceeded, abrade surface before topcoating.
Drying time is temperature, humidity, and film thickness dependent.

Pot Life:	6 hours	4 hours	2 hours
Sweat-in-Time:	2 hours	30 minutes	10 minutes

Application of coating above maximum or below minimum recommended spreading rate may adversely affect coating performance.

CLEAN UP INSTRUCTIONS

Clean spills and spatters immediately with Reducer #54 (R7K54). Clean tools immediately after use with Reducer #54 (R7K54). Follow manufacturer's safety recommendations when using any solvent.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin.

PERFORMANCE TIPS

Stripe coat all crevices, welds, and sharp angles to prevent early failure in these areas.

When using spray application, use a 50% overlap with each pass of the gun to avoid holidays, bare areas, and pinholes. If necessary, cross spray at a right angle.

Spreading rates are calculated on volume solids and do not include an application loss factor due to surface profile, roughness or porosity of the surface, skill and technique of the applicator, method of application, various surface irregularities, material lost during mixing, spillage, overthinning, climatic conditions, and excessive film build.

No reduction of material is recommended as it can affect film build, appearance, and adhesion.

Do not apply the material beyond recommended pot life.

Do not mix previously catalyzed material with new.

In order to avoid blockage of spray equipment, clean equipment before use or before periods of extended downtime with Reducer #54 (R7K54).

Material can not be sprayed if anti-slip aggregate is use.

Anti-slip additives, such as H&C SharkGrip®, may be added to the coating to provide some slip resistance. This product should not be used in place of a non-skid finish.

Anti-slip additive may be mixed into the final coat just prior to application. Exception: if anti-slip is desired with Clear finish, it should be hand broadcast.

In VOC Restricted Areas (≤340 g/L), reduction is not recommended. In other areas (>340 g/L), the prime coat for concrete may be reduced with Reducer #54 (R7K54) up to 1 pt/gal. Confirm compliance with state and local air quality rules before use.

Clear is for interior use only.

Refer to Product Information sheet for additional performance characteristics and properties.

SAFETY PRECAUTIONS

Refer to the SDS sheet before use.

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.

WARRANTY

The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

SECTION 102600 - WALL AND DOOR PROTECTION

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 1. Door Protectors & Frame Guards
 2. Corner guards.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
 1. Include construction details, material descriptions, impact strength, dimensions of individual components and profiles, and finishes.
 2. Include fire ratings of units recessed in fire-rated walls and listings for door-protection items attached to fire-rated doors.
- B. Shop Drawings: For each type of wall and door protection showing locations and extent.
 1. Include plans, elevations, sections, and attachment details. Show design and support spacing required to withstand structural loads.
- C. Samples for Initial Selection: For each type of impact-resistant wall-protection unit indicated, in each color and texture specified.
 1. Include Samples of accent strips and accessories to verify color selection.
- D. Samples for Verification: For each type of exposed finish on the following products, prepared on Samples of size indicated below:
 1. Wall Guards: 12 inches long. Include examples of joinery, corners, end caps, top caps, and field splices.
 2. Door Protector and Frame Guard: include examples
 3. Corner Guards: 12 inches long. Include example top caps.

1.4 INFORMATIONAL SUBMITTALS

- A. Product Certificates: For each type of product.

- B. Material Certificates: For each type of exposed material.
- C. Sample Warranty: For special warranty.

1.5 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For each type of wall and door protection product to include in maintenance manuals.
 - 1. Include recommended methods and frequency of maintenance for maintaining best condition of plastic covers under anticipated traffic and use conditions. Include precautions against using cleaning materials and methods that may be detrimental to finishes and performance.

1.6 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials, from the same product run, that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Wall-Guard and Handrail Covers: Full-size plastic covers of maximum length equal to 2 percent of each type, color, and texture of cover installed, but no fewer than two, 96-inch long units.
 - 2. Corner-Guard Covers: Full-size plastic covers of maximum length equal to 2 percent of each type, color, and texture of cover installed, but no fewer than two, 48-inch-long units.
 - 3. Mounting and Accessory Components: Amounts proportional to the quantities of extra materials. Package mounting and accessory components with each extra material.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Store wall and door protection in original undamaged packages and containers inside well-ventilated area protected from weather, moisture, soiling, extreme temperatures, and humidity.
 - 1. Maintain room temperature within storage area at not less than 70 deg F during the period plastic materials are stored.
 - 2. Keep plastic materials out of direct sunlight.
 - 3. Store plastic wall- and door-protection components for a minimum of 72 hours, or until plastic material attains a minimum room temperature of 70 deg F
 - a. Store corner-guard covers in a vertical position.
 - b. Store wall-guard and handrail covers in a horizontal position.

1.8 WARRANTY

- A. Special Warranty: Manufacturer agrees to repair or replace components of wall- and door-protection units that fail in materials or workmanship within specified warranty period.
 - 1. Failures include, but are not limited to, the following:

- a. Structural failures including detachment of components from each other or from the substrates, delamination, and permanent deformation beyond normal use.
 - b. Deterioration of metals, metal finishes, plastics, and other materials beyond normal use.
2. Warranty Period: Five years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Source Limitations: Obtain wall- and door-protection products of each type from single source from single manufacturer.

2.2 PERFORMANCE REQUIREMENTS

- A. Surface Burning Characteristics: Comply with ASTM E 84 or UL 723; testing by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.
 1. Flame-Spread Index: 25 or less.
 2. Smoke-Developed Index: 450 or less.
- B. Regulatory Requirements: Comply with applicable provisions in the U.S. Architectural & Transportation Barriers Compliance Board's ADA-ABA Accessibility Guidelines for Buildings and Facilities.

2.3 IMPACT-RESISTANT PRODUCTS

- A. Structural Performance: Products, including attachment to building construction, shall withstand the effects of gravity loads and the following loads and stresses within limits and under conditions indicated:
 1. Uniform load of 50 lbf/ft. applied in any direction.
 2. Concentrated load of 200 lbf applied in any direction.
 3. Uniform and concentrated loads need not be assumed to act concurrently.
- B. Heavy Duty, Rubber, Impact-Resistant Corner Guards: Manufacturer's standard assembly.
 1. Manufacturers: Subject to compliance with requirements, provide product indicated on Finish Schedule

2.4 CORNER GUARDS

- A. Surface-Mounted, Opaque-Plastic Corner Guards Fabricated as one piece from acrylic-modified vinyl sheet; with formed edges; fabricated with 90- or 135-degree turn to match wall condition.

1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Construction Specialties, Inc / Acrovyn
 - b. WallGuard.com.
 - c. Inpro
2. Wing Size: Nominal 2 by 2 inches.
3. Mounting: Countersunk screws through factory-drilled mounting holes.
4. Color and Texture: As selected by Architect from manufacturer's full range.

2.5 MATERIALS

- A. Rubber Materials: Chemical- and stain-resistant, heavy duty, high-impact-resistant rubber with integral color throughout; extruded and sheet material as required, thickness as indicated.
- B. Fasteners: Aluminum, nonmagnetic stainless-steel, or other noncorrosive metal screws, bolts, and other fasteners compatible with items being fastened. Use security-type fasteners where exposed to view.

2.6 FABRICATION

- A. Fabricate wall protection according to requirements indicated for design, performance, dimensions, and member sizes, including thicknesses of components.
- B. Factory Assembly: Assemble components in factory to greatest extent possible to minimize field assembly. Disassemble only as necessary for shipping and handling.
- C. Quality: Fabricate components with uniformly tight seams and joints and with exposed edges rolled. Provide surfaces free of wrinkles, chips, dents, uneven coloration, and other imperfections. Fabricate members and fittings to produce flush, smooth, and rigid hairline joints.

2.7 FINISHES

- A. Protect finishes on exposed surfaces from damage by applying a strippable, temporary protective covering before shipping.
- B. Appearance of Finished Work: Noticeable variations in same piece are not acceptable. Variations in appearance of adjoining components are acceptable if they are within the range of approved Samples and are assembled or installed to minimize contrast.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates and wall areas, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Complete finishing operations, including painting, before installing wall and door protection.
- B. Before installation, clean substrate to remove dust, debris, and loose particles.

3.3 INSTALLATION

- A. Installation Quality: Install wall and door protection according to manufacturer's written instructions, level, plumb, and true to line without distortions. Do not use materials with chips, cracks, voids, stains, or other defects that might be visible in the finished Work.
- B. Mounting Heights: Install wall and door protection in locations and at mounting heights indicated on Drawings.
- C. Accessories: Provide splices, mounting hardware, anchors, trim, joint moldings, and other accessories required for a complete installation.
 - 1. Provide anchoring devices and suitable locations to withstand imposed loads.
 - 2. Where splices occur in horizontal runs of more than 20 feet, splice aluminum retainers and plastic covers at different locations along the run, but no closer than 12 inches apart.
 - 3. Adjust end and top caps as required to ensure tight seams.

3.4 CLEANING

- A. Immediately after completion of installation, clean plastic covers and accessories using a standard ammonia-based household cleaning agent.
- B. Remove excess adhesive using methods and materials recommended in writing by manufacturer.

END OF SECTION 102600

SECTION 104416 - FIRE EXTINGUISHERS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes portable, hand-carried fire extinguishers and mounting brackets for fire extinguishers.
- B. Related Requirements:
 - 1. Section 104413 "Fire Protection Cabinets."

1.3 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.
 - 1. Review methods and procedures related to fire extinguishers including, but not limited to, the following:
 - a. Schedules and coordination requirements.

1.4 ACTION SUBMITTALS

- A. Product Data: For each type of product. Include rating and classification, material descriptions, dimensions of individual components and profiles, and finishes for fire extinguisher and mounting brackets.
- B. Product Schedule: For fire extinguishers. Coordinate final fire-extinguisher schedule with fire-protection cabinet schedule to ensure proper fit and function. Use same designations indicated on Drawings.

1.5 INFORMATIONAL SUBMITTALS

- A. Warranty: Sample of special warranty.

1.6 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For fire extinguishers to include in maintenance manuals.

1.7 COORDINATION

- A. Coordinate type and capacity of fire extinguishers with fire-protection cabinets to ensure fit and function.

1.8 WARRANTY

- A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace fire extinguishers that fail in materials or workmanship within specified warranty period.
 - 1. Failures include, but are not limited to, the following:
 - a. Failure of hydrostatic test according to NFPA 10.
 - b. Faulty operation of valves or release levers.
 - 2. Warranty Period: Six years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. NFPA Compliance: Fabricate and label fire extinguishers to comply with NFPA 10, "Portable Fire Extinguishers."
- B. Fire Extinguishers: Listed and labeled for type, rating, and classification by an independent testing agency acceptable to authorities having jurisdiction.
 - 1. Provide fire extinguishers approved, listed

2.2 PORTABLE, HAND-CARRIED FIRE EXTINGUISHERS

- A. Fire Extinguishers: Type, size, and capacity for each fire-protection cabinet and mounting bracket indicated.
 - 1. Valves: Manufacturer's standard.
 - 2. Handles and Levers: Manufacturer's standard.
 - 3. Instruction Labels: Include pictorial marking system complying with NFPA 10, Appendix B, and bar coding for documenting fire-extinguisher location, inspections, maintenance, and recharging.
- B. Multipurpose Dry-Chemical Type in Steel Container: UL-rated 4-A:60-B:C, 10-lb nominal capacity, with monoammonium phosphate-based dry chemical in enameled-steel container.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine fire extinguishers for proper charging and tagging.
 - 1. Remove and replace damaged, defective, or undercharged fire extinguishers.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. General: Install fire extinguishers and mounting brackets in locations indicated and in compliance with requirements of authorities having jurisdiction.
 - 1. Mounting Brackets: 54 inches above finished floor to top of fire extinguisher.
- B. Mounting Brackets: Fasten mounting brackets to surfaces, square and plumb, at locations indicated.

END OF SECTION 104416

SECTION 270528 - PATHWAYS FOR COMMUNICATIONS SYSTEMS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Metal conduits and fittings.
 - 2. Metal wireways and auxiliary gutters.
 - 3. Metallic surface pathways.
 - 4. Tele-power poles.
 - 5. Boxes, enclosures, and cabinets.

1.3 DEFINITIONS

- A. GRC: Galvanized rigid conduit.
- B. IMC: Intermediate metal conduit.

1.4 ACTION SUBMITTALS

- A. Product data for the following:
 - 1. Surface pathways
 - 2. Wireways and fittings.
 - 3. Tele-power poles.
 - 4. Boxes, enclosures, and cabinets.
- B. Shop Drawings: For custom enclosures and cabinets. Include plans, elevations, sections, and attachment details.

1.5 INFORMATIONAL SUBMITTALS

- A. Coordination Drawings: Pathway routing plans, drawn to scale, on which the following items are shown and coordinated with each other, using input from installers of items involved:
 - 1. Structural members in paths of pathway groups with common supports.
 - 2. HVAC and plumbing items and architectural features in paths of conduit groups with common supports.
- B. Qualification Data: For professional engineer.

- C. Seismic Qualification Data: Provide seismic bracing for all pathway racks, enclosures, cabinets, equipment racks, and their mounting provisions, including those for internal components, from manufacturer.
 - 1. Basis for Certification: Indicate whether withstand certification is based on actual test of assembled components or on calculation.
 - 2. Dimensioned Outline Drawings of Equipment Unit: Identify center of gravity and locate and describe mounting and anchorage provisions.
 - 3. Detailed description of equipment anchorage devices on which certification is based and their installation requirements.
 - 4. Detailed description of conduit support devices and interconnections on which certification is based and their installation requirements.
- D. Source quality-control reports.

PART 2 - PRODUCTS

2.1 METAL CONDUITS AND FITTINGS

- A. Description: Metal raceway of circular cross section with manufacturer-fabricated fittings.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 - 1. ABB, Electrification Products Division.
 - 2. AFC Cable Systems; Atkore International.
 - 3. Allied Tube & Conduit; Atkore International.
 - 4. Alpha Wire.
 - 5. Anaconda Sealtite; Anamet Electrical, Inc.
 - 6. Electri-Flex Company.
 - 7. O-Z/Gedney; Emerson Electric Co., Automation Solutions, Appleton Group.
 - 8. Picoma; Zekelman Industries.
 - 9. Plasti-Bond; Robroy Industries.
 - 10. Republic Conduit; Nucor Corporation, Nucor Tubular Products.
 - 11. Southwire Company.
 - 12. Western Tube; Zekelman Industries.
 - 13. Wheatland Tube; Zekelman Industries.
- C. General Requirements for Metal Conduits and Fittings:
 - 1. Listed and labeled as defined in NFPA 70, by a nationally recognized testing laboratory, and marked for intended location and application.
 - 2. Comply with TIA-569-D.
- D. GRC: Comply with ANSI C80.1 and UL 6.
- E. IMC: Comply with ANSI C80.6 and UL 1242.
- F. PVC-Coated Steel Conduit: PVC-coated GRC .
 - 1. Comply with NEMA RN 1.
 - 2. Coating Thickness: 0.040 inch, minimum.

- G. EMT: Comply with ANSI C80.3 and UL 797.
- H. Fittings for Metal Conduit: Comply with NEMA FB 1 and UL 514B.
 - 1. Conduit Fittings for Hazardous (Classified) Locations: Comply with UL 1203 and NFPA 70.
 - 2. Fittings for EMT:
 - a. Material: Steel or die cast.
 - b. Type: Set screw or compression.
 - 3. Expansion Fittings: PVC or steel to match conduit type, complying with UL-467, rated for environmental conditions where installed, and including flexible external bonding jumper.
 - 4. Coating for Fittings for PVC-Coated Conduit: Minimum thickness of 0.040 inch, with overlapping sleeves protecting threaded joints.
- I. Joint Compound for IMC, GRC, or ARC: Approved, as defined in NFPA 70, by authorities having jurisdiction for use in conduit assemblies, and compounded for use to lubricate and protect threaded conduit joints from corrosion and to enhance their conductivity.

2.2 OPTICAL-FIBER-CABLE PATHWAYS AND FITTINGS

- A. Description: Comply with UL 2024; flexible-type pathway with a circular cross section, approved for plenum riser or general-use installation unless otherwise indicated.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 - 1. ABB, Electrification Products Division.
 - 2. Alpha Wire.
 - 3. Dura-Line.
 - 4. Endot Industries Inc.
 - 5. IPEX USA LLC.
- C. Listed and labeled as defined in NFPA 70, by an NRTL, and marked for intended location and application.
- D. Comply with TIA-569-D.

2.3 METAL WIREWAYS AND AUXILIARY GUTTERS

- A. Description: Sheet metal trough of rectangular cross section fabricated to required size and shape, without holes or knockouts, and with hinged or removable covers.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 - 1. B-line; Eaton, Electrical Sector.
 - 2. Hoffman; nVent.
 - 3. MonoSystems, Inc.
 - 4. Square D; Schneider Electric USA.
- C. General Requirements for Metal Wireways and Auxiliary Gutters:

1. Comply with UL 870 and NEMA 250, Type 1 unless otherwise indicated, and sized according to NFPA 70.
 2. Metal wireways installed outdoors shall be listed and labeled as defined in NFPA 70, by an NRTL, and marked for intended location and application.
 3. Comply with TIA-569-D.
- D. Fittings and Accessories: Include covers, couplings, offsets, elbows, expansion joints, adapters, hold-down straps, end caps, and other fittings to match and mate with wireways as required for complete system.
- E. Finish: Manufacturer's standard enamel finish.

2.4 SURFACE METAL PATHWAYS

- A. Description: Galvanized steel with snap-on covers, complying with UL 5.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
1. MonoSystems, Inc.
 2. Niedax Inc.
 3. Panduit Corp.
 4. Wiremold; Legrand North America, LLC.
- C. Finish: Manufacturer's standard enamel finish in color selected by Architect.
- D. Listed and labeled as defined in NFPA 70, by an NRTL, and marked for intended location and application.
- E. Comply with TIA-569-D.

2.5 TELE-POWER POLES:

- A. Description: Prefabricated, finished metal pole with prewired power and communications outlets.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
1. MonoSystems, Inc.
 2. Panduit Corp.
 3. Wiremold; Legrand North America, LLC.
- C. Material: Galvanized steel with ivory baked-enamel finish or aluminum with clear anodized finish.
- D. Fittings and Accessories: Dividers, end caps, covers, cutouts, wiring harnesses, devices, mounting materials, and other fittings shall match and mate with tele-power pole as required for complete system.

- E. Listed and labeled as defined in NFPA 70, by an NRTL, and marked for intended location and application.
- F. Comply with TIA-569-D.

2.6 HOOKS

- A. Description: Prefabricated sheet metal cable supports for telecommunications cable.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 - 1. MonoSystems, Inc.
 - 2. Panduit Corp.
 - 3. Wiremold; Legrand North America, LLC.
- C. Listed and labeled as defined in NFPA 70, by an NRTL, and marked for intended location and application.
- D. Comply with TIA-569-D.
- E. Galvanized steel.
- F. J shape.

2.7 BOXES, ENCLOSURES, AND CABINETS

- A. Description: Enclosures for communications.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 - 1. ABB, Electrification Products Division.
 - 2. Adalet.
 - 3. Crouse-Hinds; Eaton, Electrical Sector.
 - 4. EGS; Emerson Electric Co., Automation Solutions, Appleton Group.
 - 5. Erickson Electrical Equipment Company.
 - 6. FSR Inc.
 - 7. Hoffman; nVent.
 - 8. Milbank Manufacturing Co.
 - 9. Molex Industrial Products Group; Woodhead Brand.
 - 10. MonoSystems, Inc.
 - 11. Oldcastle Infrastructure Inc.; CRH Americas.
 - 12. O-Z/Gedney; Emerson Electric Co., Automation Solutions, Appleton Group.
 - 13. Plasti-Bond; Robroy Industries.
 - 14. Quazite; Hubbell Incorporated, Power Systems.
 - 15. Racco Taymac Bell; Hubbell Incorporated, Commercial and Industrial.
 - 16. Spring City Electrical Manufacturing Company.
 - 17. Stahlin Non-Metallic Enclosures.
 - 18. Wiremold; Legrand North America, LLC.

- C. General Requirements for Boxes, Enclosures, and Cabinets:
 - 1. Comply with TIA-569-D.
 - 2. Boxes, enclosures, and cabinets installed in wet locations shall be listed and labeled as defined in NFPA 70, by an NRTL, and marked for use in wet locations.
 - 3. Box extensions used to accommodate new building finishes shall be of same material as recessed box.
 - 4. Device Box Dimensions: 4 inches square by 2-1/8 inches deep.
 - 5. Gangable boxes are prohibited.
- D. Sheet Metal Outlet and Device Boxes: Comply with NEMA OS 1 and UL 514A.
- E. Cast-Metal Outlet and Device Boxes: Comply with NEMA FB 1, ferrous alloy, Type FD, with gasketed cover.
- F. Metal Floor Boxes:
 - 1. Material: Cast metal.
 - 2. Type: Fully adjustable.
 - 3. Shape: Rectangular.
 - 4. Metal floor boxes shall be listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- G. Small Sheet Metal Pull and Junction Boxes: NEMA OS 1.
- H. Cast-Metal Access, Pull, and Junction Boxes: Comply with NEMA FB 1 and UL 1773, galvanized, cast iron with gasketed cover.
- I. Hinged-Cover Enclosures: Comply with UL 50 and NEMA 250, Type 12, with continuous-hinge cover with flush latch unless otherwise indicated.
 - 1. Metal Enclosures: Steel, finished inside and out with manufacturer's standard enamel.
 - 2. Interior Panels: Steel; all sides finished with manufacturer's standard enamel.
- J. Cabinets:
 - 1. NEMA 250, Type 12 galvanized-steel box with removable interior panel and removable front, finished inside and out with manufacturer's standard enamel.
 - 2. Hinged door in front cover with flush latch and concealed hinge.
 - 3. Key latch to match panelboards.
 - 4. Metal barriers to separate wiring of different systems and voltage.
 - 5. Accessory feet where required for freestanding equipment.
 - 6. Nonmetallic cabinets shall be listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.

PART 3 - EXECUTION

3.1 PATHWAY APPLICATION

- A. Outdoors: Apply pathway products as specified below unless otherwise indicated:
 - 1. Exposed Conduit: GRC or IMC.
 - 2. Concealed Conduit, Aboveground: GRC, IMC or EMT.
 - 3. Underground Conduit: RNC, Type EPC-40-PVC, direct buried.

4. Boxes and Enclosures, Aboveground: NEMA 250, Type 4.
- B. Indoors: Apply pathway products as specified below unless otherwise indicated:
1. Exposed, Not Subject to Physical Damage: EMT.
 2. Exposed, Not Subject to Severe Physical Damage: EMT.
 3. Exposed and Subject to Severe Physical Damage: GRC or IMC. Pathway locations include the following:
 - a. Loading dock.
 - b. Corridors used for traffic of mechanized carts, forklifts, and pallet-handling units.
 - c. Mechanical rooms.
 4. Concealed in Ceilings and Interior Walls and Partitions: EMT.
 5. Damp or Wet Locations: GRC or IMC.
 6. Pathways for Optical-Fiber or Communications Cable in Spaces Used for Environmental Air: Plenum-type, optical-fiber-cable pathway Plenum-type, communications-cable pathway or EMT.
 7. Pathways for Optical-Fiber or Communications-Cable Risers in Vertical Shafts: Riser-type, optical-fiber-cable pathway Riser-type, communications-cable pathway or EMT.
 8. Pathways for Concealed General-Purpose Distribution of Optical-Fiber or Communications Cable: General-use, optical-fiber-cable pathway Riser-type, optical-fiber-cable pathway Plenum-type, optical-fiber-cable pathway Riser-type, communications-cable pathway Plenum-type, communications-cable pathway or EMT.
 9. Boxes and Enclosures: NEMA 250, Type 1, except use NEMA 250, Type 4 stainless steel units in institutional and commercial kitchens and damp or wet locations.
- C. Minimum Pathway Size: 3/4-inch trade size for copper and aluminum cables, and 1 inch for optical-fiber cables.
- D. Pathway Fittings: Compatible with pathways and suitable for use and location.
1. Rigid and Intermediate Steel Conduit: Use threaded rigid steel conduit fittings unless otherwise indicated. Comply with NEMA FB 2.10.
 2. PVC Externally Coated, Rigid Steel Conduits: Use only fittings listed for use with this type of conduit. Patch and seal all joints, nicks, and scrapes in PVC coating after installing conduits and fittings. Use sealant recommended by fitting manufacturer and apply in thickness and number of coats recommended by manufacturer.
 3. EMT: Use compression, steel fittings. Comply with NEMA FB 2.10.
- E. Do not install aluminum conduits, boxes, or fittings in contact with concrete or earth.
- F. Install surface pathways only where indicated on Drawings.
- G. Do not install nonmetallic conduit where ambient temperature exceeds 120 deg F.

3.2 INSTALLATION

- A. Comply with the following standards for installation requirements except where requirements on Drawings or in this Section are stricter:
1. NECA 1.
 2. NECA/BICSI 568.
 3. TIA-569-D.
 4. NECA 101

5. NECA 102.
 6. NECA 105.
 7. NECA 111.
- B. Comply with NFPA 70 limitations for types of pathways allowed in specific occupancies and number of floors.
 - C. Comply with requirements in Section 260529 "Hangers and Supports for Electrical Systems" for hangers and supports.
 - D. Comply with requirements in Section 260544 "Sleeves and Sleeve Seals for Electrical Raceways and Cabling" for sleeves and sleeve seals for communications.
 - E. Keep pathways at least 6 inches away from parallel runs of flues and steam or hot-water pipes. Install horizontal pathway runs above water and steam piping.
 - F. Complete pathway installation before starting conductor installation.
 - G. Arrange stub-ups so curved portions of bends are not visible above finished slab.
 - H. Install no more than the equivalent of two 90-degree bends in any pathway run. Support within 12 inches of changes in direction. Utilize long radius ells for all optical-fiber cables.
 - I. Conceal rigid conduit within finished walls, ceilings, and floors unless otherwise indicated. Install conduits parallel or perpendicular to building lines.
 - J. Support conduit within 12 inches of enclosures to which attached.
 - K. Pathways Embedded in Slabs:
 1. Run conduit larger than 1-inch trade size, parallel or at right angles to main reinforcement. Where at right angles to reinforcement, place conduit close to slab support. Secure pathways to reinforcement at maximum 10-foot intervals.
 2. Arrange pathways to cross building expansion joints at right angles with expansion fittings. Comply with requirements for expansion joints specified in this article.
 3. Arrange pathways to keep a minimum of 2 inches of concrete cover in all directions.
 4. Do not embed threadless fittings in concrete unless specifically approved by Architect for each specific location.
 5. Change from nonmetallic conduit and fittings to GRC or IMC and fittings before rising above floor.
 - L. Stub-ups to Above Recessed Ceilings:
 1. Use EMT, IMC, or RMC for pathways.
 2. Use a conduit bushing or insulated fitting to terminate stub-ups not terminated in hubs or in an enclosure.
 - M. Threaded Conduit Joints, Exposed to Wet, Damp, Corrosive, or Outdoor Conditions: Apply listed compound to threads of pathway and fittings before making up joints. Follow compound manufacturer's written instructions.

- N. Coat field-cut threads on PVC-coated pathway with a corrosion-preventing conductive compound prior to assembly.
- O. Terminate threaded conduits into threaded hubs or with locknuts on inside and outside of boxes or cabinets. Install insulated bushings on conduits terminated with locknuts.
- P. Install pathways square to the enclosure and terminate at enclosures with locknuts. Install locknuts hand tight plus one additional quarter-turn.
- Q. Do not rely on locknuts to penetrate nonconductive coatings on enclosures. Remove coatings in the locknut area prior to assembling conduit to enclosure, to assure a continuous ground path.
- R. Cut conduit perpendicular to the length. For conduits of 2-inch trade size and larger, use roll cutter or a guide to ensure cut is straight and perpendicular to the length.
- S. Install pull wires in empty pathways. Use polypropylene or monofilament plastic line with not less than 200-lb tensile strength. Leave at least 12 inches of slack at each end of pull wire. Secure pull wire, so it cannot fall into conduit. Cap pathways designated as spare alongside pathways in use.
- T. Surface Pathways:
 - 1. Install surface pathway for surface telecommunications outlet boxes only where indicated on Drawings.
 - 2. Install surface pathway with a minimum 2-inch radius control at bend points.
 - 3. Secure surface pathway with screws or other anchor-type devices at intervals not exceeding 48 inches and with no less than two supports per straight pathway section. Support surface pathway according to manufacturer's written instructions. Tape and glue are not acceptable support methods.
- U. Pathways for Optical-Fiber and Communications Cable: Install pathways, metal and nonmetallic, rigid and flexible, as follows:
 - 1. 3/4-Inch Trade Size and Smaller: Install pathways in maximum lengths of 50 feet.
 - 2. 1-Inch Trade Size and Larger: Install pathways in maximum lengths of 75 feet.
 - 3. Install with a maximum of two 90-degree bends or equivalent for each length of pathway unless Drawings show stricter requirements. Separate lengths with pull or junction boxes or terminations at distribution frames or cabinets where necessary to comply with these requirements.
- V. Install pathway-sealing fittings at accessible locations according to NFPA 70 and fill them with listed sealing compound. For concealed pathways, install each fitting in a flush steel box with a blank cover plate having a finish similar to that of adjacent plates or surfaces. Install pathway-sealing fittings according to NFPA 70.
- W. Install devices to seal pathway interiors at accessible locations. Locate seals, so no fittings or boxes are between the seal and the following changes of environments. Seal the interior of all pathways at the following points:
 - 1. Where conduits pass from warm to cold locations, such as boundaries of refrigerated spaces.
 - 2. Where an underground service pathway enters a building or structure.
 - 3. Where otherwise required by NFPA 70.

- X. Comply with manufacturer's written instructions for solvent welding PVC conduit and fittings.
- Y. Expansion-Joint Fittings:
 - 1. Install in each run of aboveground RNC that is located where environmental temperature change may exceed 30 deg F, and that has straight-run length that exceeds 25 feet. Install in each run of aboveground RMC and EMT that is located where environmental temperature change may exceed 100 deg F, and that has straight-run length that exceeds 100 feet.
 - 2. Install type and quantity of fittings that accommodate temperature change listed for each of the following locations:
 - a. Outdoor Locations Not Exposed to Direct Sunlight: 125 deg F temperature change.
 - b. Outdoor Locations Exposed to Direct Sunlight: 155 deg F temperature change.
 - c. Indoor Spaces Connected with Outdoors without Physical Separation: 125 deg F temperature change.
 - d. Attics: 135 deg F temperature change.
 - e. Insert location and corresponding temperature change.
 - 3. Install fitting(s) that provide expansion and contraction for at least 0.00041 inch per foot of length of straight run per deg F of temperature change for PVC conduits. Install fitting(s) that provide expansion and contraction for at least 0.000078 inch per foot of length of straight run per deg F of temperature change for metal conduits.
 - 4. Install expansion fittings at all locations where conduits cross building or structure expansion joints.
 - 5. Install each expansion-joint fitting with position, mounting, and piston setting selected according to manufacturer's written instructions for conditions at specific location at time of installation. Install conduit supports to allow for expansion movement.
- Z. Hooks:
 - 1. Size to allow a minimum of 25 percent future capacity without exceeding design capacity limits.
 - 2. Shall be supported by dedicated support wires. Do not use ceiling grid support wire or support rods.
 - 3. Hook spacing shall allow no more than 6 inches of slack. The lowest point of the cables shall be no less than 6 inches adjacent to ceilings, mechanical ductwork and fittings, luminaires, power conduits, power and telecommunications outlets, and other electrical and communications equipment.
 - 4. Space hooks no more than 5 feet o.c.
 - 5. Provide a hook at each change in direction.
- AA. Mount boxes at heights indicated on Drawings. If mounting heights of boxes are not individually indicated, give priority to ADA requirements. Install boxes with height measured to center of box unless otherwise indicated.
- BB. Recessed Boxes in Masonry Walls: Saw-cut opening for box in center of cell of masonry block, and install box flush with surface of wall. Prepare block surface to provide a flat surface for a raintight connection between box and cover plate or supported equipment and box.
- CC. Horizontally separate boxes mounted on opposite sides of walls, so they are not in the same vertical channel.

- DD. Support boxes of three gangs or more from more than one side by spanning two framing members or mounting on brackets specifically designed for the purpose.
- EE. Fasten junction and pull boxes to or support from building structure. Do not support boxes by conduits.
- FF. Set metal floor boxes level and flush with finished floor surface.
- GG. Set nonmetallic floor boxes level. Trim after installation to fit flush with finished floor surface.

3.3 INSTALLATION OF UNDERGROUND CONDUIT

- A. Direct-Buried Conduit:
 1. Excavate trench bottom to provide firm and uniform support for conduit.
 2. Install backfill as required.
 3. After installing conduit, backfill and compact. Start at tie-in point, and work toward end of conduit run, leaving conduit at end of run free to move with expansion and contraction as temperature changes during this process. Firmly hand tamp backfill around conduit to provide maximum supporting strength. After placing controlled backfill to within 12 inches of finished grade, make final conduit connection at end of run and complete backfilling with normal compaction as specified in Section 312000 "Earth Moving."
 4. Install manufactured duct elbows for stub-ups at poles and equipment and at building entrances through floor unless otherwise indicated. Encase elbows for stub-up ducts throughout length of elbow.
 5. Install manufactured rigid steel conduit elbows for stub-ups at poles and equipment and at building entrances through floor.
 - a. Couple steel conduits to ducts with adapters designed for this purpose, and encase coupling with 3 inches of concrete around conduit for a minimum of 12 inches on each side of the coupling.
 - b. For stub-ups at equipment mounted on outdoor concrete bases and where conduits penetrate building foundations, extend steel conduit horizontally a minimum of 60 inches from edge of foundation or equipment base. Install insulated grounding bushings on terminations at equipment.
 6. Underground Warning Tape: Comply with requirements in Section 260553 "Identification for Electrical Systems."

3.4 INSTALLATION OF UNDERGROUND HANDHOLES AND BOXES

- A. Install handholes and boxes level and plumb and with orientation and depth coordinated with connecting conduits to minimize bends and deflections required for proper entrances.
- B. Unless otherwise indicated, support units on a level bed of crushed stone or gravel, graded from 1/2-inch sieve to No. 4 sieve and compacted to same density as adjacent undisturbed earth.
- C. Elevation: In paved areas, set so cover surface will be flush with finished grade. Set covers of other enclosures 1 inch above finished grade.
- D. Install handholes with bottom below frost line, below grade.

- E. Install removable hardware, including pulling eyes, cable stanchions, cable arms, and insulators, as required for installation and support of cables and conductors and as indicated. Select arm lengths to be long enough to provide spare space for future cables, but short enough to preserve adequate working clearances in enclosure.
- F. Field cut openings for conduits according to enclosure manufacturer's written instructions. Cut wall of enclosure with a tool designed for material to be cut. Size holes for terminating fittings to be used, and seal around penetrations after fittings are installed.

3.5 SLEEVE AND SLEEVE-SEAL INSTALLATION FOR COMMUNICATIONS PENETRATIONS

- A. Install sleeves and sleeve seals at penetrations of exterior floor and wall assemblies. Comply with requirements in Section 260544 "Sleeves and Sleeve Seals for Electrical Raceways and Cabling."

3.6 FIRESTOPPING

- A. Install firestopping at penetrations of fire-rated floor and wall assemblies.

3.7 PROTECTION

- A. Protect coatings, finishes, and cabinets from damage or deterioration.
 - 1. Repair damage to galvanized finishes with zinc-rich paint recommended by manufacturer.
 - 2. Repair damage to PVC coatings or paint finishes with matching touchup coating recommended by manufacturer.

END OF SECTION 270528

SECTION 271513 - COMMUNICATIONS COPPER HORIZONTAL CABLING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Category 5e twisted pair cable.
 - 2. Category 6 twisted pair cable.
 - 3. Twisted pair cable hardware, including plugs and jacks.
 - 4. Multiuser telecommunications outlet assembly.
 - 5. Cable management system.
 - 6. Cabling identification products.
 - 7. Grounding provisions for twisted pair cable.
 - 8. Source quality control requirements for twisted pair cable.

1.3 DEFINITIONS

- A. Cross-Connect: A facility enabling the termination of cable elements and their interconnection or cross-connection.
- B. EMI: Electromagnetic interference.
- C. FTP: Shielded twisted pair.
- D. F/FTP: Overall foil screened cable with foil screened twisted pair.
- E. F/UTP: Overall foil screened cable with unscreened twisted pair.
- F. IDC: Insulation displacement connector.
- G. LAN: Local area network.
- H. Jack: Also commonly called an "outlet," it is the fixed, female connector.
- I. Plug: Also commonly called a "connector," it is the removable, male telecommunications connector.
- J. RCDD: Registered Communications Distribution Designer.
- K. Screen: A metallic layer, either a foil or braid, placed around a pair or group of conductors.

- L. Shield: A metallic layer, either a foil or braid, placed around a pair or group of conductors.
- M. S/FTP: Overall braid screened cable with foil screened twisted pair.
- N. S/UTP: Overall braid screened cable with unscreened twisted pairs.
- O. UTP: Unscreened (unshielded) twisted pair.

1.4 COPPER HORIZONTAL CABLING DESCRIPTION

- A. Horizontal cable cabling system shall provide interconnections between the MDF / IDF rooms and the data outlets. Cabling system consists of horizontal cables, intermediate and main cross-connects, mechanical terminations, and patch cords or jumpers used for horizontal-to-horizontal cross-connection.
 - 1. TIA-568-D requires that a minimum of two equipment outlets be installed for each work area or as indicated on drawings.
 - 2. Horizontal cabling shall contain no more than one transition point or consolidation point between the horizontal cross-connect and the telecommunications equipment outlet.
 - 3. Bridged taps and splices shall not be installed in the horizontal cabling.
- B. A work area is approximately 100 sq. ft., and includes the components that extend from the equipment outlets to the station equipment.
- C. The maximum allowable horizontal cable length is 295 feet. This maximum allowable length does not include an allowance for the length of 16 feet to the workstation equipment or in the horizontal cross-connect.

1.5 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings: Reviewed and stamped by RCDD.
 - 1. System Labeling Schedules: Electronic copy of labeling schedules that are part of the cabling and asset identification system of the software.
 - 2. Cabling administration Drawings and printouts.
 - 3. Wiring diagrams and installation details of telecommunications equipment, to show location and layout of telecommunications equipment, including the following:
 - a. Telecommunications rooms plans and elevations.
 - b. Telecommunications pathways.
 - c. Telecommunications system access points.
 - d. Telecommunications conductor drop locations.
 - e. Typical telecommunications details.
- C. Twisted pair cable testing plan.
- D. Samples: For telecommunications jacks and plugs, in specified finish, one for each type and configuration and faceplates for color selection and evaluation of technical features.

1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For RCDD, Installer, installation supervisor, and field inspector.
- B. Product Certificates: For each type of product.
- C. Source quality-control reports.
- D. Field quality-control reports.

1.7 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For splices and connectors to include in maintenance manuals.
- B. Software and Firmware Operational Documentation:
 - 1. Software operating and upgrade manuals.
 - 2. Program Software Backup: On USB media or compact disk, complete with data files.
 - 3. Device address list.
 - 4. Printout of software application and graphic screens.

1.8 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Faceplates: One of each type.
 - 2. Jacks: Ten of each type.
 - 3. Multiuser Telecommunications Outlet Assemblies: One of each type.
 - 4. Plugs: Ten of each type.

1.9 QUALITY ASSURANCE

- A. Installer Qualifications: Cabling Installer must have personnel certified by BICSI on staff.
 - 1. Layout Responsibility: Preparation of Shop Drawings, cabling administration Drawings, and field testing program development by an RCDD.
 - 2. Installation Supervision: Installation shall be under the direct supervision of Technician Level 2 Installer, who shall be present at all times when Work of this Section is performed at Project site.
 - 3. Testing Supervisor: Currently certified by BICSI as an RCDD to supervise on-site testing.
- B. Testing Agency Qualifications: Testing agency must have personnel certified by BICSI on staff.
 - 1. Testing Agency's Field Supervisor: Currently certified by BICSI as an RCDD.

1.10 DELIVERY, STORAGE, AND HANDLING

- A. Test cables upon receipt at Project site.
 - 1. Test each pair of twisted pair cable for open and short circuits.

1.11 PROJECT CONDITIONS

- A. Environmental Limitations: Do not deliver or install cables and connecting materials until wet work in spaces is complete and dry, and temporary HVAC system is operating and maintaining ambient temperature and humidity conditions at occupancy levels during the remainder of the construction period.

1.12 COORDINATION

- A. Coordinate layout and installation of telecommunications pathways and cabling with Owner's telecommunications and LAN equipment and service suppliers.

1.13 SOFTWARE SERVICE AGREEMENT

- A. Technical Support: Beginning with Substantial Completion, provide software support for two years.
- B. Upgrade Service: Update software to latest version at Project completion. Install and program software upgrades that become available within two years from date of Substantial Completion. Upgrading software shall include operating system. Upgrade shall include new or revised licenses for use of software.
 - 1. Provide 30 days' notice to Owner to allow scheduling and access to system and to allow Owner to upgrade computer equipment if necessary.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. General Performance: Horizontal cabling system shall comply with transmission standards in TIA-568-C.1, when tested according to test procedures of this standard.
- B. Telecommunications Pathways and Spaces: Comply with TIA-569-D.
- C. Grounding: Comply with TIA-607-B.

2.2 GENERAL CABLE CHARACTERISTICS

- A. Listed and labeled by an NRTL acceptable to authorities having jurisdiction as complying with the applicable standard and NFPA 70 for the following types:
 - 1. Communications, Plenum Rated: Type CMP complying with UL 1685 or Type CMP in listed plenum communications raceway or Type CMP in listed cable routing assembly.
 - 2. Communications, Plenum Rated: Type CM, Type CMG, Type CMP, Type CMR, or Type CMX in metallic conduit installed according to NFPA 70, Article 300.22, "Wiring in Ducts, Plenums, and Other Air-Handling Spaces."
 - 3. Communications, Non-plenum: Type CMR complying with UL 1666 and ICEA S-103-701.

- 4. Communications, Non-plenum: Type CMP or Type CMR in listed plenum or riser communications raceway.
- 5. Communications, Non-plenum: Type CMP or Type CMR in metallic conduit installed according to NFPA 70, Article 300.22, "Wiring in Ducts, Plenums, and Other Air-Handling Spaces."
- B. Surface-Burning Characteristics: Comply with ASTM E84; testing by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.
 - 1. Flame-Spread Index: 25 or less.
 - 2. Smoke-Developed Index: 50 or less.
- C. RoHS compliant.

2.3 CATEGORY 5e TWISTED PAIR CABLE

- A. Description: Four-pair, balanced-twisted pair cable, with internal spline, certified to meet transmission characteristics of Category 5e cable at frequencies up to 100MHz.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 - 1. 3M.
 - 2. AMP NETCONNECT; a TE Connectivity Ltd. company.
 - 3. Belden CDT Networking Division/NORDX.
 - 4. Berk-Tek Leviton; a Nexans/Leviton alliance.
 - 5. CommScope, Inc.
 - 6. General Cable; Prysmian Group North America.
 - 7. Genesis Cable Products; Honeywell International, Inc.
 - 8. Hitachi Cable America Inc.
 - 9. Mohawk; a division of Belden Networking, Inc.
 - 10. Prysmian Cables and Systems; Prysmian Group North America.
 - 11. Superior Essex Inc.
 - 12. SYSTIMAX Solutions; a CommScope Inc. brand.
- C. Standard: Comply with NEMA WC 66/ICEA S-116-732 and TIA-568-C.2 for Category 5e cables.
- D. Shielding/Screening: Shielded twisted pairs (FTP).
- E. Cable Rating: Plenum.
- F. Jacket: Blue thermoplastic.

2.4 CATEGORY 6a TWISTED PAIR CABLE

- A. Description: Four-pair, balanced-twisted pair cable, with internal spline, certified to meet transmission characteristics of Category 6 cable at frequencies up to 250MHz.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:

1. 3M.
2. AMP NETCONNECT; a TE Connectivity Ltd. company.
3. Belden CDT Networking Division/NORDX.
4. Berk-Tek Leviton; a Nexans/Leviton alliance.
5. CommScope, Inc.
6. General Cable; Prysmian Group North America.
7. Genesis Cable Products; Honeywell International, Inc.
8. Hitachi Cable America Inc.
9. Mohawk; a division of Belden Networking, Inc.
10. Prysmian Cables and Systems; Prysmian Group North America.
11. Superior Essex Inc.
12. SYSTIMAX Solutions; a CommScope Inc. brand.

- C. Standard: Comply with TIA-568-C.2 for Category 6 cables.
- D. Conductors: 100-ohm, 23 AWG solid copper.
- E. Shielding/Screening: Shielded twisted pairs (FTP) Screened twisted pairs (F/UTP) Screened and shielded twisted pairs (F/FTP).
- F. Cable Rating: Plenum.
- G. Jacket: Blue Yellow Insert color thermoplastic.

2.5 CATEGORY 7 TWISTED PAIR CABLE

- A. Description: Four-pair, balanced-twisted pair cable, with internal spline, certified to meet transmission characteristics of Category 7 cable at frequencies up to 600MHz.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 1. Hitachi Cable America Inc.
 2. Siemon Co. (The).
- C. Standard: Comply with ISO 11801, Category F.
- D. Conductors: 100-ohm, 22 AWG solid copper.
- E. Shielding/Screening: Overall foil shield with foil shielded twisted pairs (F/FTP).
- F. Cable Rating: Plenum.
- G. Jacket: Blue thermoplastic.

2.6 TWISTED PAIR CABLE HARDWARE

- A. Description: Hardware designed to connect, splice, and terminate twisted pair copper communications cable.

- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
1. 3M.
 2. American Technology Systems Industries, Inc.
 3. AMP NETCONNECT; a TE Connectivity Ltd. company.
 4. Belden CDT Networking Division/NORDX.
 5. Berk-Tek Leviton; a Nexans/Leviton alliance.
 6. CommScope, Inc.
 7. Dynacom Corporation.
 8. General Cable; Prysmian Group North America.
 9. Genesis Cable Products; Honeywell International, Inc.
 10. Hubbell Premise Wiring; Hubbell Incorporated, Commercial and Industrial.
 11. KRONE Incorporated.
 12. Leviton Manufacturing Co., Inc.
 13. Mohawk; a division of Belden Networking, Inc.
 14. Molex Premise Networks.
 15. Panduit Corp.
 16. Prysmian Cables and Systems; Prysmian Group North America.
 17. Siemon Co. (The).
 18. Superior Essex Inc.
 19. SYSTIMAX Solutions; a CommScope Inc. brand.
- C. General Requirements for Twisted Pair Cable Hardware:
1. Comply with the performance requirements of Category 6, Category 6a or Category 7 as applicable.
 2. Comply with TIA-568-C.2, IDC type, with modules designed for punch-down caps or tools.
 3. Cables shall be terminated with connecting hardware of same category or higher.
- D. Source Limitations: Obtain twisted pair cable hardware from single source from single manufacturer.
- E. Patch Cords: Factory-made, four-pair cables in 48-inch lengths; terminated with an eight-position modular plug at each end.
1. Patch cords shall have color-coded boots for circuit identification.
- F. Plugs and Plug Assemblies:
1. Male; eight position; color-coded modular telecommunications connector designed for termination of a single four-pair, 100-ohm, unshielded or shielded twisted pair cable.
 2. Standard: Comply with TIA-568-C.2.
 3. Marked to indicate transmission performance.
- G. Jacks and Jack Assemblies:
1. Female; eight position; modular; fixed telecommunications connector designed for termination of a single four-pair, 100-ohm, unshielded or shielded twisted pair cable.
 2. Designed to snap-in to a patch panel or faceplate.
 3. Standard: Comply with TIA-568-C.2.
- H. Faceplate:

1. Two, four or six port, vertical single gang faceplates designed to mount to single gang wall boxes.
 2. Plastic Faceplate: High-impact plastic. Coordinate color with Section 262726 "Wiring Devices."
 3. Metal Faceplate: Stainless steel, complying with requirements in Section 262726 "Wiring Devices."
 4. For use with snap-in jacks accommodating any combination of twisted pair, optical fiber, and coaxial work area cords.
 - a. Flush mounting jacks, positioning the cord at a 45-degree angle.
- I. Legend:
1. Machine printed, in the field, using adhesive-tape label.
 2. Snap-in, clear-label covers and machine-printed paper inserts.

2.7 CABLE MANAGEMENT SYSTEM

- A. Description: Computer-based cable management system, with integrated database capabilities.
- B. Basis-of-Design Product: Subject to compliance with requirements, provide product indicated on Drawings or comparable product by one of the following:
 1. iTRACS Corporation.
 2. Telsoft Solutions.
- C. Document physical characteristics by recording the network, TIA details, and connections between equipment and cable.
- D. Information shall be presented in database view.
 1. AutoCAD drawing software shall be used as drawing and schematic plans software.
- E. System shall interface with the following testing and recording devices:
 1. Direct upload tests from circuit testing instrument into the personal computer.
 2. Direct download circuit labeling into labeling printer.

2.8 IDENTIFICATION PRODUCTS

- A. Comply with TIA-606-B and UL 969 for a system of labeling materials, including label stocks, laminating adhesives, and inks used by label printers.

2.9 GROUNDING

- A. Comply with requirements in Section 260526 "Grounding and Bonding for Electrical Systems" for grounding conductors and connectors.
- B. Comply with TIA-607-B.

2.10 SOURCE QUALITY CONTROL

- A. Factory test cables on reels according to TIA-568-C.1.

- B. Factory test twisted pair cables according to TIA-568-C.2.
- C. Cable will be considered defective if it does not pass tests and inspections.
- D. Prepare test and inspection reports.

PART 3 - EXECUTION

3.1 WIRING METHODS

- A. Wiring Method: Install cables in raceways and cable trays, except within consoles, cabinets, desks, and counters and except in accessible ceiling spaces, attics, and gypsum board partitions where unenclosed wiring method may be used. Conceal raceway and cables, except in unfinished spaces.
 - 1. Install plenum cable in environmental air spaces, including plenum ceilings.
 - 2. Comply with requirements for raceways and boxes specified in Section 270528 "Pathways for Communications Systems."
- B. Wiring Method: Conceal conductors and cables in accessible ceilings, walls, and floors where possible.
- C. Wiring within Enclosures: Bundle, lace, and train cables within enclosures. Connect to terminal points with no excess and without exceeding manufacturer's limitations on bending radii. Provide and use lacing bars and distribution spools. Install conductors parallel with or at right angles to sides and back of enclosure.

3.2 INSTALLATION OF PATHWAYS

- A. Comply with requirements for demarcation point, cabinets, and racks specified in Section 271100 "Communications Equipment Room Fittings."
- B. Comply with Section 270528 "Pathways for Communications Systems."
- C. Comply with Section 270536 "Cable Trays for Communications Systems."
- D. Drawings indicate general arrangement of pathways and fittings.

3.3 INSTALLATION OF TWISTED-PAIR HORIZONTAL CABLES

- A. Comply with NECA 1 and NECA/BICSI 568.
- B. General Requirements for Cabling:
 - 1. Comply with TIA-568-C.0, TIA-568-C.1, and TIA-568-C.2.
 - 2. Comply with BICSI's "Information Transport Systems Installation Methods Manual (ITSIMM), Ch. 5, "Copper Structured Cabling Systems," "Cable Termination Practices" Section.
 - 3. Do not untwist twisted pair cables more than 1/2 inch from the point of termination to maintain cable geometry.

4. Terminate all conductors; no cable shall contain unterminated elements. Make terminations only at indicated outlets, terminals, cross-connects, and patch panels.
 5. Consolidation points may be used only for making a direct connection to equipment outlets:
 - a. Do not use consolidation point as a cross-connect point, as a patch connection, or for direct connection to workstation equipment.
 - b. Locate consolidation points for twisted-pair cables at least 49 feet from communications equipment room.
 6. Cables may not be spliced. Secure and support cables at intervals not exceeding 30 inches and not more than 6 inches from cabinets, boxes, fittings, outlets, racks, frames, and terminals.
 7. Install lacing bars to restrain cables, prevent straining connections, and prevent bending cables to smaller radii than minimums recommended by manufacturer.
 8. Bundle, lace, and train conductors to terminal points without exceeding manufacturer's limitations on bending radii, but not less than radii specified in BICSI Information Transport Systems Installation Methods Manual, Ch. 5, "Copper Structured Cabling Systems," "Cable Termination Practices" Section. Use lacing bars and distribution spools.
 9. Do not install bruised, kinked, scored, deformed, or abraded cable. Do not splice cable between termination, tap, or junction points. Remove and discard cable if damaged during installation, and replace it with new cable.
 10. Cold-Weather Installation: Bring cable to room temperature before dereeling. Heat lamps shall not be used for heating.
 11. In the communications equipment room, install a 10-foot- long service loop on each end of cable.
 12. Pulling Cable: Comply with BICSI Information Transport Systems Installation Methods Manual, Ch. 5, "Copper Structured Cabling Systems," "Pulling and Installing Cable" Section. Monitor cable pull tensions.
- C. Open-Cable Installation:
1. Install cabling with horizontal and vertical cable guides in telecommunications spaces with terminating hardware and interconnection equipment.
 2. Suspend twisted pair cabling, not in a wireway or pathway, a minimum of 8 inches above ceilings by cable supports not more than 60 inches apart.
 3. Cable shall not be run through structural members or in contact with pipes, ducts, or other potentially damaging items.
- D. Installation of Cable Routed Exposed under Raised Floors:
1. Install plenum-rated cable only.
 2. Install cabling after the flooring system has been installed in raised floor areas.
 3. Coil cable 6 feet long not less than 12 inches in diameter below each feed point.
- E. Group connecting hardware for cables into separate logical fields.
- F. Separation from EMI Sources:
1. Comply with recommendations from BICSI's "Telecommunications Distribution Methods Manual" and TIA-569-D for separating unshielded copper communication cable from potential EMI sources, including electrical power lines and equipment.
 2. Separation between open communications cables or cables in nonmetallic raceways and unshielded power conductors and electrical equipment shall be as follows:
 - a. Electrical Equipment Rating Less Than 2 kVA: A minimum of 5 inches.

- b. Electrical Equipment Rating between 2 and 5 kVA: A minimum of 12 inches.
- c. Electrical Equipment Rating More Than 5 kVA: A minimum of 24 inches.
- 3. Separation between communications cables in grounded metallic raceways and unshielded power lines or electrical equipment shall be as follows:
 - a. Electrical Equipment Rating Less Than 2 kVA: A minimum of 2-1/2 inches.
 - b. Electrical Equipment Rating between 2 and 5 kVA: A minimum of 6 inches.
 - c. Electrical Equipment Rating More Than 5 kVA: A minimum of 12 inches.
- 4. Separation between communications cables in grounded metallic raceways, power lines, and electrical equipment located in grounded metallic conduits or enclosures shall be as follows:
 - a. Electrical Equipment Rating Less Than 2 kVA: No requirement.
 - b. Electrical Equipment Rating between 2 and 5 kVA: A minimum of 3 inches.
 - c. Electrical Equipment Rating More Than 5 kVA: A minimum of 6 inches.
- 5. Separation between Communications Cables and Electrical Motors and Transformers, 5 kVA or HP and Larger: A minimum of 48 inches.
- 6. Separation between Communications Cables and Fluorescent Fixtures: A minimum of 5 inches.

3.4 FIRESTOPPING

- A. Comply with TIA-569-D, Annex A, "Firestopping."
- B. Comply with "Firestopping Systems" Article in BICSI's "Telecommunications Distribution Methods Manual."

3.5 GROUNDING

- A. Install grounding according to the "Grounding, Bonding, and Electrical Protection" chapter in BICSI's "Telecommunications Distribution Methods Manual."
- B. Comply with TIA-607-B and NECA/BICSI-607.
- C. Locate grounding bus bar to minimize the length of bonding conductors. Fasten to wall, allowing at least a 2-inch clearance behind the grounding bus bar. Connect grounding bus bar to suitable electrical building ground, using a minimum No. 4 AWG grounding electrode conductor.
- D. Bond metallic equipment to the grounding bus bar, using not smaller than a No. 6 AWG equipment grounding conductor.

3.6 IDENTIFICATION

- A. Identify system components, wiring, and cabling complying with TIA-606-B. Comply with requirements for identification specified in Section 260553 "Identification for Electrical Systems."
 - 1. Administration Class: Class 1 or Class 2.
 - 2. Color-code cross-connect fields and apply colors to voice and data service backboards, connections, covers, and labels.

- B. Paint and label colors for equipment identification shall comply with TIA-606-B for Class 2 level of administration, including optional identification requirements of this standard.
- C. Cable Schedule: Install in a prominent location in each equipment room and wiring closet. List incoming and outgoing cables and their designations, origins, and destinations. Protect with rigid frame and clear plastic cover. Furnish an electronic copy of final comprehensive schedules for Project.
- D. Cabling Administration Drawings: Show building floor plans with cabling administration-point labeling. Identify labeling convention and show labels for telecommunications closets, terminal hardware and positions, horizontal cables, work areas and workstation terminal positions, grounding buses and pathways, and equipment grounding conductors.
- E. Cable and Wire Identification:
 - 1. Label each cable within 4 inches of each termination and tap, where it is accessible in a cabinet or junction or outlet box, and elsewhere as indicated.
 - 2. Each wire connected to building-mounted devices is not required to be numbered at the device if wire color is consistent with associated wire connected and numbered within panel or cabinet.
 - 3. Exposed Cables and Cables in Cable Trays and Wire Troughs: Label each cable at intervals not exceeding 15 feet.
 - 4. Label each terminal strip, and screw terminal in each cabinet, rack, or panel.
 - a. Individually number wiring conductors connected to terminal strips, and identify each cable or wiring group, extended from a panel or cabinet to a building-mounted device, with the name and number of a particular device.
 - b. Label each unit and field within distribution racks and frames.
 - 5. Identification within Connector Fields in Equipment Rooms and Wiring Closets: Label each connector and each discrete unit of cable-terminating and -connecting hardware. Where similar jacks and plugs are used for both voice and data communication cabling, use a different color for jacks and plugs of each service.
- F. Labels shall be preprinted or computer-printed type, with a printing area and font color that contrast with cable jacket color but still comply with TIA-606-B requirements for the following:
 - 1. Cables use flexible vinyl or polyester that flexes as cables are bent.

3.7 FIELD QUALITY CONTROL

- A. Tests and Inspections:
 - 1. Visually inspect jacket materials for NRTL certification markings. Inspect cabling terminations in communications equipment rooms for compliance with color-coding for pin assignments, and inspect cabling connections for compliance with TIA-568-C.1.
 - 2. Visually inspect cable placement, cable termination, grounding and bonding, equipment and patch cords, and labeling of all components.
 - 3. Test twisted pair cabling for DC loop resistance, shorts, opens, intermittent faults, and polarity between conductors. Test operation of shorting bars in connection blocks. Test cables after termination but not cross-connection.
 - a. Test instruments shall meet or exceed applicable requirements in TIA-568-C.2. Perform tests with a tester that complies with performance requirements in "Test Instruments (Normative)" Annex, complying with measurement accuracy specified

in "Measurement Accuracy (Informative)" Annex. Use only test cords and adapters that are qualified by test equipment manufacturer for channel or link test configuration.

- B. Data for each measurement shall be documented. Data for submittals shall be printed in a summary report that is formatted similarly to Table 10.1 in BICSI's "Telecommunications Distribution Methods Manual," or shall be transferred from the instrument to the computer, saved as text files, printed, and submitted.
- C. Remove and replace cabling where test results indicate that they do not comply with specified requirements.
- D. End-to-end cabling will be considered defective if it does not pass tests and inspections.
- E. Prepare test and inspection reports.

3.8 SOFTWARE SERVICE AGREEMENT

- A. Technical Support: Beginning with Substantial Completion, provide software support for two years.
- B. Upgrade Service: Update software to latest version at Project completion. Install and program software upgrades that become available within two years from date of Substantial Completion. Upgrading software shall include operating system. Upgrade shall include new or revised licenses for use of software.
 - 1. Provide 30 days' notice to Owner to allow scheduling and access to system and to allow Owner to upgrade computer equipment if necessary.

END OF SECTION 271513